

Features


- Mini female to male double-ended cordsets
- Multiple length options
- Black PVC jacket, unshielded, 7/8"-16UNF Mini straight connector
- ITC/PLTC rated cable

Models





1. Black
2. Blue
3. Green/yellow
4. Brown
5. White



Specifications

Current Rating
8 A


Voltage Rating
600 V

Construction
Coupling nut material: Nickel-plated brass
Contact carrier: Black TPU
Connector body: Black TPU
Jacket material: Black PVC

Connections
Mini (7/8"-16UNF) female to male

Operating Conditions
Operating temperature: –40 °C to +70 °C (–40 °F to +158 °F)
Storage temperature: –40 °C to +70 °C (–40 °F to +158 °F)
90% at +50 °C maximum relative humidity (non-condensing)

Cable
18 AWG
Outer diameter: 7.6 mm
Bend radius, static installation: 5× the outside diameter
Bend radius, dynamic: 10× the outside diameter
Jacket material: Black PVC
ITC – Instrumentation Tray Cable
PLTC - Power Limited Tray Cable
Sunlight resistant
UL Cold Bend at -40° C
Oil Res I and II
CMX-OUTDOOR-CMG
FT4 flame rating
MSHA rating



Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

Original Instructions
19-Mar-26

© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com

255988
p/n: 255988 Rev. A

ПРОМЭЛЕКТРОНИКА/ sales@prom-elec.com

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.

© Banner Engineering Corp. All rights reserved.