Custom Product Supplemental Instructions


Custom Model: SI-QS90E-Q5A

This product has been modified from the standard product. For complete installation information and product specifications, refer to p/n 49370 at www.bannerengineering.com, or contact Banner Engineering.


Modifications

- Derived from model SI-QS90E, p/n 49468
- Installed M12 Euro 5 pin male to wiring chamber
- De-rated electrical ratings
- Modifed Agency Approvals and markings
- Banner reserves the right to modify this product without prior notice.

Actuator engaged




Actuator removed





Shown without M12 Quick-Disconnect Connector

Wiring Diagram



5 Pin QD	SI-QS90E-Q5A contact #
Pin 1 Brown:	11
Pin 2 White:	12
Pin 3 Blue:	No connection
Pin 4 Black:	21
Pin 5 Gray:	22

Specifications for models with suffix -Q5A

Electrical Ratings

250 V AC at 4 A maximum

Certifications

Banner Engineering Europe
Park Lane, Culliganlaan 2F bus 3,
1831 Diegem, BELGIUM

c UL us
LISTED
8N35 447Y
IND. CONT. EQ.

CAUTION: Electrical installation

Two safety switches must be used for each interlock guard to achieve control reliability or Safety Category 4 per ISO 13849-1 of a machine stop circuit. Use of only one safety switch per interlock guard is not recommended.

220146

ПРОМЭЛЕКТРОНИКА/ sales@prom-elec.com