Lenses

L2

- Opposed fiber lens for range extension, qty 1
- Accepts M2.5 & M2.6 threaded fibers
- Glass
- Used with the D12 Series Fiber Optic Sensors
- Model L2-2 includes 2 lenses



L08FP

- Opposed fiber lens for range extension
- Accepts 2.2 mm outer diameter fiber jacket
- M8 x 1.0 threaded acrylic lens
- Used with the D12 Series Fiber Optic Sensors



L9

- 3.18 mm core diameter
- 19 mm bend radius
- 12.5 mm lens, 12.5 mm focal length
- 5/16-24 UNF thread
- Aluminum housing
- Suitable for all but highly corrosive environments



L9M8

- 12.5 mm lens
- For long-range or retroreflective sensing
- M8 x 1 threading
- Aluminum housing

L9SS

- 12.5 mm lens
- For long-range or retroreflective sensing
- 5/16-24 UNF thread
- Stainless steel housing



L16F

- 3.18 mm core diameter
- 19 mm bend radius
- 25 mm lens, 44 mm focal length
- 5/16-24 UNF thread
- Delrin housing
- Maximum operating temperature is 100 °C (212 °F)
- Used with MULTI-BEAM, MAXI-BEAM, and VALU-BEAM sensors



L16FM8

- 3.18 mm core diameter
- 19 mm bend radius
- 25 mm lens, 44 mm focal length
- M8 x 1 threading
- Delrin housing
- Maximum operating temperature is 100 °C (212 °F)
- Used with MULTI-BEAM, MAXI-BEAM, and VALU-BEAM sensors



Original Instructions
05-Oct-26

© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com

b_51965440
p/n: b_51965440 Rev. B

ПРОМЭЛЕКТРОНИКА/ sales@prom-elec.com

L16FAL
- 3.18 mm core diameter
- 19 mm bend radius
- 25 mm lens, 44 mm focal length
- 5/16-24 threading
- Aluminum housing
- Suitable for all but highly corrosive environments
- Used with MULTI-BEAM, MAXI-BEAM, and VALU-BEAM sensors
- CAD Files: PDF, DXF, IGS, STP



L16FALM8
- 3.18 mm core diameter
- 19 mm bend radius
- 25 mm lens, 44 mm focal length
- M8 x 1 threading
- Aluminum housing
- Suitable for all but highly corrosive environments



L16FSS
- 3.18 mm core diameter
- 19 mm bend radius
- 25 mm lens, 44 mm focal length
- 5/16-24 UNF thread
- Stainless steel housing
- Suitable for all environments
- Used with MULTI-BEAM, MAXI-BEAM, and VALU-BEAM sensors



L16FSSM8
- 3.18 mm core diameter
- 19 mm bend radius
- 25 mm lens, 44 mm focal length
- M8 x 1 threading
- Stainless steel housing
- Suitable for all environments



VE Series Smart Camera Lenses

Additional models are available. See www.bannerengineering.com.

C-Mount Megapixel Lens Focal Length—For use with WVGA, 1.3MP, or 2MP models

Focal Length	Model	Brand	Compatible with Unsealed Ring Light	Compatible with Sealed Ring Light	Compatible with 60 mm Sealed Lens Cover	Compatible with 85 mm Sealed Lens Cover
5 mm	LCF05LCMP[1] (1)	Computar	No	Yes	Yes	No
6 mm	LCF06LEVMP (1)	Evetar	Yes, with setscrews removed	Yes	Yes	No
8 mm	LCF08LMP	Computar	Yes, with LHWK-1	Yes	Yes	No
	LCF08LEVMP	Evetar	Yes, with setscrews removed	Yes	Yes	No
12 mm	LCF12LMP	Computar	Yes, with LHWK-1	Yes	Yes	No
	LCF12LEVMP (1)	Evetar	Yes, with setscrews removed	Yes	Yes	No
16 mm	LCF16LCMP	Computar	Yes, with LHWK-1	Yes	Yes	Yes
	LCF16LEVMP	Evetar	Yes, with setscrews removed	Yes	Yes	Yes
25 mm	LCF25LCMP	Computar	Yes, with LHWK-1	Yes	Yes	Yes
	LCF25LEVMP	Evetar	Yes, with setscrews removed	Yes	Yes	Yes
35 mm	LCF35LCMP	Computar	Yes, with LHWK-1	Yes	Yes	Yes
	LCF35LEVMP	Evetar	Yes, with setscrews removed	Yes	Yes	Yes
50 mm	LCF50LCMP	Computar	Yes, with LHWK-1	Yes	Yes	Yes
	LCF50LEVMP (1)	Evetar	Yes, with setscrews removed		No	Yes
75 mm	LCF75LCMP	Computar	Yes, with LHWK-1	No	No	Yes
	LCF75LEVMP[1]	Evetar	Yes, with setscrews removed	No	No	Yes

(1) Denotes specific lens used for 2MP WD and FOV examples.

© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com

C-Mount Megapixel Lens Focal Length—For use with WVGA, 1.3MP, or 2MP models

Focal Length	Model	Brand	Compatible with Sealed Ring Light	Compatible with 60 mm Sealed Lens Cover	Compatible with 85 mm Sealed Lens Cover
6 mm	LCF06LK1F	Kowa	No	No	No
8 mm	LCF08LK1F	Kowa	No	No	No
12 mm	LCF12LK1F	Kowa	Yes, with LHWK-1	Yes	No
16 mm	LCF16LK1F	Kowa	Yes, with LHWK-1	Yes	Yes
25 mm	LCF25LK1F	Kowa	Yes, with LHWK-1	Yes	Yes
35 mm	LCF35LK1F	Kowa	Yes, with LHWK-1	Yes	Yes
50 mm	LCF50LK1F	Kowa	Yes, with LHWK-1	No	Yes, with LHWK-1
75 mm	LCF75LK1F	Kowa	Yes, with LHWK-1	No	Yes, with LHWK-1

Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.

© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com