# EZ-LIGHT® One-Color General-Purpose Indicators Datasheet

## Technical Information

To view or download the latest technical information about this product, including specifications, dimensions, accessories, and wiring, go to www.bannerengineering.com.

**WARNING:**

- **Do not use this device for personnel protection**
- Using this device for personnel protection could result in serious injury or death.
- This device does not include the self-checking redundant circuitry necessary to allow its use in personnel safety applications. A device failure or malfunction can cause either an energized (on) or de-energized (off) output condition.

## Models

| Models | LED Color |
|---|---|
|  **M18GXXPQ** | Color 1: Green |
| **M18XRXPQ** | Color 2: Red |
| **M18XXYPQ** | Color 3: Yellow |
| • Nickel-plated brass housing, thermoplastic diffuser.<br>• Fully encapsulated IP67 | |
|  **K30LGXXPQ** | Color 1: Green |
| **K30LXRXPQ** | Color 2: Red |
| **K30LXXYPQ** | Color 3: Yellow |
| • 22 mm threaded polycarbonate base, translucent polycarbonate dome.<br>• Fully encapsulated IP67, IP69K per DIN 40050-9 | |
|  **K50LGXXPQ** | Color 1: Green |
| **K50LXRXPQ** | Color 2: Red |
| **K50LXXYPQ** | Color 3: Yellow |
| • 30 mm threaded polycarbonate base, translucent polycarbonate dome.<br>• Fully encapsulated IP67, IP69K per DIN 40050-9 | |
|  **K50FLGXXPQ** | Color 1: Green |
| **K50FLXRXPQ** | Color 2: Red |
| **K50FLXXYPQ** | Color 3: Yellow |
| • ABS base, translucent polycarbonate dome.<br>• Fully encapsulated IP67, IP69K per DIN 40050-9 | |
|  **K80LGXXPQ** | Color 1: Green |
| **K80LXRXPQ** | Color 2: Red |
| **K80LXXYPQ** | Color 3: Yellow |
| • Polycarbonate base, translucent polycarbonate dome.<br>• Fully encapsulated IP67 | |

The following models are no longer available for order, but are still covered by the information in this document.


© Banner Engineering Corp.


ПРОМЭЛЕКТРОНИКА/ sales@prom-elec.com

| Models | | LED Color |
|---|---|---|
|  | **T18GXXPQ** | Color 1: Green |
| | **T18XRXPQ** | Color 2: Red |
| | **T18XXYPQ** | Color 3: Yellow |
| | • Thermoplastic polyester housing, thermoplastic diffuser.<br>• Fully encapsulated IP67 | |
|  | **T30GXXPQ** | Color 1: Green |
| | **T30XRXPQ** | Color 2: Red |
| | **T30XXYPQ** | Color 3: Yellow |
| | • Thermoplastic polyester housing, thermoplastic diffuser.<br>• Fully encapsulated IP67 | |
|  | **T8LGXXPQP** | Color 1: Green |
| | **T8LXRXPQP** | Color 2: Red |
| | **T8LXXYPQP** | Color 3: Yellow |
| | • Polycarbonate/ABS alloy housing, thermoplastic diffuser.<br>• IP67 | |

Models with a quick disconnect require a mating cordset.

**T8L Models:** Standard quick-disconnect models are listed. To order the integral 4-wire cabled model, omit the suffix **QP** (for example, **T8LGXXP**).

**K30FL Models:** Standard integral 4-pin M12 quick-disconnect connector models are listed. For 2 m (6.5 ft) integral 4-wire cabled model, omit suffix **Q** (for example, **K30LGRXP**). For 150 mm (6 inch) PVC-jacketed cable with 4-pin M12 quick-disconnect connector, replace suffix **Q** with **QP** (for example, **K30LGRXPQP**). For terminal models, replace suffix **Q** with **T** (for example, **K30LGRXPT**).

**K80L Models:** Standard integral 4-pin M12 quick-disconnect connector models are listed. To order the terminal-wired model, omit suffix **Q** (for example, **K80LGXXP**).

**Other Models:** Standard integral 4-pin M12 quick-disconnect connector models are listed. To order the 2 m (6.5 ft) integral 4-wire cable model, omit suffix **Q** (for example, **M18GXXP**). To order the 150 mm (6 inch) PVC-jacketed cable with 4-pin M12 quick-disconnect connector, replace suffix **Q** with **QP** (for example, **M18GXXPQP**).

Contact Banner Engineering for other colors and color combinations.

# Wiring

| For NPN Operation | | |
|---|---|---|
| **Color 1** | **Color 2** | **Color 3** |
|  |  |  |
| Pin 1 and Pin 2 not used | Pin 4 and Pin 2 not used | Pin 1 and Pin 4 not used |

| For PNP Operation | | |
|---|---|---|
| **Color 1** | **Color 2** | **Color 3** |
|  |  |  |
| Pin 1 and Pin 2 not used | Pin 4 and Pin 2 not used | Pin 1 and Pin 4 not used |

**Wiring Key**


© Banner Engineering Corp. All rights reserved.

| | |
|---|---|
| 1. Brown (bn)<br>2. White (wh) | 3. Blue (bu)<br>4. Black (bk) |

# Specifications

**Supply Voltage and Current**

**T8L models:** 10 V DC to 30 V DC at 20 mA maximum

**T18, M18, and K30L models:** 10 V DC to 30 V DC at 25 mA maximum per LED color

**T30 models:** 10 V DC to 30 V DC at 40 mA maximum per LED color

**K50L, K50FL, and K80L models:** 18 V DC to 30 V DC at 40 mA maximum per LED color

**Indicators**

Entire translucent diffuser or dome provides indication. Green and yellow, when connected to discrete output of 3-wire or 4-wire sensors. For other colors, contact factory for availability.

**Input Response Time**

**Indicator ON/OFF:** 1 ms max.

**Operating Conditions**

**Temperature:** –40 °C to +50 °C (–40 °F to +122 °F)

**Environmental Rating**

Rated IP67. T8L not encapsulated; K80L has encapsulated electronics only; other models fully encapsulated.

K30L, K50L, and K50FL QD models meet IP69K per DIN 40050-9.

Cabled models also meet IP69K if the cable and cable entrance are protected from high-pressure spray.

**Connections**

**T8L models:** 150 mm (6 in) PVC-jacketed cable with a 4-pin M12 male quick-disconnect connector (QP) or 2 m (6.5 ft) unterminated 4-wire integral cable, depending on model

**K30L models:** Integral 4-pin M12 male quick-disconnect connector (Q), 150 mm (6 in) PVC-jacketed cable with a 4-pin M12 male quick-disconnect connector (QP), 2 m (6.5 ft) unterminated 4-wire integral cable, or 5 color-coded screw terminal for up to 16 AWG wire, depending on model. Screw terminal max torque: 0.11 N·m (1.0 lbf·in).

**K80L models:** Integral 4-pin M12 male quick-disconnect connector (Q) standard; terminal-wired models available for use with bulk cable; compression fitting optional. Contact Factory for cable information.

**Other models:** Integral 4-pin M12 male quick-disconnect connector (Q), 150 mm (6 in) PVC-jacketed cable with a 4-pin M12 male quick-disconnect connector (QP), or 2 m (6.5 ft) unterminated 4-wire integral cable, depending on model

**Construction**

See Models lists

**Required Overcurrent Protection**

**WARNING:** Electrical connections must be made by qualified personnel in accordance with local and national electrical codes and regulations.

Overcurrent protection is required to be provided by end product application per the supplied table.

Overcurrent protection may be provided with external fusing or via Current Limiting, Class 2 Power Supply.

Supply wiring leads < 24 AWG shall not be spliced.

For additional product support, go to www.bannerengineering.com.

| Supply Wiring (AWG) | Required Overcurrent Protection (A) | Supply Wiring (AWG) | Required Overcurrent Protection (A) |
|---|---|---|---|
| 20 | 5.0 | 26 | 1.0 |
| 22 | 3.0 | 28 | 0.8 |
| 24 | 1.0 | 30 | 0.5 |

**Certifications**

All models:

Banner Engineering BV
Park Lane, Culliganlaan 2F bus 3
1831 Diegem, BELGIUM

K50L, K50FL, T18, and T30 models only:

Turck Banner LTD Blenheim House
Blenheim Court
Wickford, Essex SS11 8YT
GREAT BRITAIN

K30L and K50L models only:

# Dimensions

All measurements are listed in millimeters [inches], unless noted otherwise.


© Banner Engineering Corp. All rights reserved.

### T8L Models




### T18 Models




### M18 Models




### T30 Models




### K30L Models




### K30 Terminal Models




### K50L Models




### K50FL Models




### K80L Models





© Banner Engineering Corp. All rights reserved.

# Accessories

## Cordsets

| 4-Pin Threaded M12 Cordsets—Single Ended | | | | | |
|---|---|---|---|---|---|
| **Model** | **Length** | **Style** | **Dimensions** | **Pinout (Female)** | |
| **MQDC-406** | 2 m (6.56 ft) | Straight |  |  | 1 = Brown<br>2 = White<br>3 = Blue<br>4 = Black<br>5 = Unused |
| **MQDC-415** | 5 m (16.4 ft) | | | | |
| **MQDC-430** | 9 m (29.5 ft) | | | | |
| **MQDC-450** | 15 m (49.2 ft) | | | | |
| **MQDC-406RA** | 2 m (6.56 ft) | Right-Angle |  |  | |
| **MQDC-415RA** | 5 m (16.4 ft) | | | | |
| **MQDC-430RA** | 9 m (29.5 ft) | | | | |
| **MQDC-450RA** | 15 m (49.2 ft) | | | | |

## Brackets

For more information about these and other available brackets, visit www.bannerengineering.com.

K50FL models include a 48 mm (1.9 in) circular hook-and-loop mounting kit for easy mounting with no additional hardware required.

### For use with T8L models

**SMB8MM**

- Right-angle bracket
- 300 series stainless steel

**Hole size:** A = ø 3.5, B = 4.9 × 3.6, C = ø 8.4




### For use with M18 and T18 models or base-mount T30 models

**SMB18A**

- Right-angle mounting bracket with a curved slot for versatile orientation
- 12-ga. stainless steel
- 18 mm sensor mounting hole
- Clearance for M4 (#8) hardware

**Hole center spacing:** A to B = 24.2
**Hole size:** A = ø 4.6, B = 17.0 × 4.6, C = ø 18.5





© Banner Engineering Corp. All rights reserved.

**SMB312PD**

- Right-angle mounting bracket with a curved slot for versatile orientation
- 12-ga. stainless steel
- 18 mm sensor mounting hole
- Clearance for M4 (#8) hardware

**Hole center spacing:** A to B = 24.2
**Hole size:** A = ø 4.6, B = 17 × 4.6, C = ø 18.5

**NOTE:** Not for use with plastic fiber optic sensors




**SMB1815SF**

- Swivel with set screws for mounting sensors by the cable hub
- Black reinforced thermoplastic polyester
- Stainless steel swivel locking hardware and hex wrench included

**Hole center spacing:** A = 36.0
**Hole size:** A = ø 5.0, B = ø 15.0




**SMBAMS18RA**

- Right-angle SMBAMS series bracket with 18 mm hole
- Articulation slots for 90+° rotation
- 12-ga. (2.6 mm) cold-rolled steel

**Hole center spacing:** A = 26.0, A to B = 13.0
**Hole size:** A = 26.8 × 7.0, B = ø 6.5, C = ø 19.0




**SMB18Q**

- Right-angle flanged bracket
- 18 mm sensor mounting hole
- 12-ga. stainless steel

**Hole center spacing:** A to B = 24.2
**Hole size:** A = ø 4.6, B = 17.0 × 4.6, C = ø 19.0




**SMBAMS18P**

- Flat SMBAMS series bracket with 18 mm hole
- Articulation slots for 90+° rotation
- 12-ga. (2.6 mm) cold-rolled steel

**Hole center spacing:** A = 26.0, A to B = 13.0
**Hole size:** A = 26.8 × 7.0, B = ø 6.5, C = ø 19.0




**SMB18SF**

- 18 mm swivel bracket with M18 × 1 internal thread
- Black thermoplastic polyester
- Stainless steel swivel locking hardware included

**Hole center spacing:** A = 36.0
**Hole size:** A = ø 5.3, B = ø 18.0





© Banner Engineering Corp. All rights reserved.

## For use with T30 models or base-mount K50L models

**SMB30A**
- Right-angle bracket with curved slot for versatile orientation
- Clearance for M6 (¼ in) hardware
- Mounting hole for 30 mm sensor
- 12-gauge stainless steel

**Hole center spacing:** A to B=40
**Hole size:** A=ø 6.3, B= 27.1 × 6.3, C=ø 30.5




**SMB30SC**
- Swivel bracket with 30 mm mounting hole for sensor
- Black reinforced thermoplastic polyester
- Stainless steel mounting and swivel locking hardware included

**Hole center spacing:** A=ø 50.8
**Hole size:** A=ø 7.0, B=ø 30.0




**SMBAMS30RA**
- Right-angle SMBAMS series bracket
- 30 mm hole for mounting sensors
- Articulation slots for 90°+ rotation
- 12-gauge (2.6 mm) cold-rolled steel

**Hole center spacing:** A=26.0, A to B=13.0
**Hole size:** A=26.8 × 7.0, B=ø 6.5, C=ø 31.0




**SMB30MM**
- 12-gauge stainless steel bracket with curved mounting slots for versatile orientation
- Clearance for M6 (¼ in) hardware
- Mounting hole for 30 mm sensor

**Hole center spacing:** A = 51, A to B = 25.4
**Hole size:** A = 42.6 × 7, B = ø 6.4, C = ø 30.1




**SMBAMS30P**
- Flat SMBAMS series bracket
- 30 mm hole for mounting sensors
- Articulation slots for 90°+ rotation
- 12-gauge 300 series stainless steel

**Hole center spacing:** A=26.0, A to B=13.0
**Hole size:** A=26.8 × 7.0, B=ø 6.5, C=ø 31.0




**SMB3018SC**
- 18 mm swivel side or barrel-mount bracket
- Black reinforced thermoplastic polyester
- Stainless steel swivel locking hardware included

**Hole center spacing:** A = 50.8
**Hole size:** A = ø 7.0, B = ø 18.0





© Banner Engineering Corp. All rights reserved.

## DIN-mount bracket for K80L models

**SMBDX80DIN**
- Black reinforced thermoplastic
- Bracket for mounting on a 35 mm DIN rail




# Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

**THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.**

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.

Document title: EZ-LIGHT® One-Color General-Purpose Indicators
Part number: 130865
Revision: I
Original Instructions
© Banner Engineering Corp. All rights reserved.

130865


© Banner Engineering Corp. All rights reserved.