4-pin A-Code Double-Ended M12 Female to M12 Male Cordsets with Stainless Steel Coupling Nuts

Features

- M12 female to male (double-ended), four wires, multiple length options
- Black PVC jacket, unshielded, A-code, stainless steel nut
- Straight connector options
- ITC/PLTC cable

Models

	Connector			-	Wire Gauge	-	Length	-	Coupling Nut
BC-	M12F4	-	M12M4	-	22	-	5	-	SST


M12F4 = 4-pin M12 Female


M12M4 = 4-pin M12 Male


22 = 22 Gauge

Length (m)

Stainless steel coupling nut







1 = Brown
2 = White
3 = Blue
4 = Black
5 = Unused

Specifications

Current Rating
4 A

Voltage Rating
30 V DC

Bend Radius
Static: 5× the outside diameter
Dynamic: 10× the outside diameter

Connections
Integral 4-pin M12 quick disconnect (female, male)

Construction
Coupling nut material: Stainless steel
Contact carrier: Black nylon
Connector body: Black TPU
Jacket material: Black PVC

Vibration and Mechanical Shock
Meets IEC 60068-2-6 requirements (Vibration: 10 Hz to 500 Hz; 0.35 mm amplitude, 6-hour sweep cycle, 10 sweep cycles)
Meets IEC 60068-2-27 requirements (Shock: 50G, half-sine wave, 11 ms duration)

Coding
A

Operating Conditions
Operating temperature: –40 °C to +70 °C (–40 °F to +158 °F)
Storage temperature: –40 °C to +70 °C (–40 °F to +158 °F)
90% at +50 °C maximum relative humidity (non-condensing)

Environmental Rating
IP66, IP67, IP68

Original Instructions
11-Mar-26


© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com

252791
p/n: 252791 Rev. B

ПРОМЭЛЕКТРОНИКА/ sales@prom-elec.com

Cable

- 22 AWG
- Outer diameter: 5.33 mm
- Jacket material: Black PVC
- ITC (Instrumentation Tray Cable): 105 °C, 150 V, 5 A or less
- PLTC (Power-Limited Tray Cable): 105 °C, 300 V
- Sunlight resistant
- UL Cold Bend at -40 °C
- Oil Res I and II
- CMX-OUTDOOR-CMG
- FT4 flame rating
- MSHA rating



Certifications

Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.

© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com