# EZ-LIGHT® Touch K30 Series Illuminated Buttons

## Features

*Lighted Touch Button with Bipolar Outputs*



- Rugged, cost-effective, and easy-to-install touch button with multicolor light
- Momentary versions remain activated as long as touch is present
- Latching versions start-up not activated and toggle between activated and not activated on successive touches
- Waterproof construction for washdown environments
- Ergonomically designed to eliminate hand, wrist, and arm stresses associated with repeated switch operation; requires no physical force to operate
- Can be actuated with bare hands or gloves
- 12 V DC to 30 V DC operation
- Five color options available

## Models

| Model | Function | Output | Light (not activated) | Light (activated) | Connection[1] |
|---|---|---|---|---|---|
| K30ALBTXGHQ | Latching | Bipolar, N.O. | - | Green | Integral 5-pin M12 male quick-disconnect connector |
| K30RLBTXGHQ | | Bipolar, N.C. | | | |
| K30ABTXGHQ | Momentary | Bipolar, N.O. | | | |
| K30RBTXGHQ | | Bipolar, N.C. | | | |
| K30ALBTGGHQ | Latching | Bipolar, N.O. | Green | Green | |
| K30RLBTGGHQ | | Bipolar, N.C. | | | |
| K30ABTGGHQ | Momentary | Bipolar, N.O. | | | |
| K30RBTGGHQ | | Bipolar, N.C. | | | |
| K30ALBTRGHQ | Latching | Bipolar, N.O. | Red | Green | |
| K30RLBTRGHQ | | Bipolar, N.C. | | | |
| K30ABTRGHQ | Momentary | Bipolar, N.O. | | | |
| K30RBTRGHQ | | Bipolar, N.C. | | | |

## Wiring

Cabled wiring diagrams are shown. Quick disconnect wiring diagrams are functionally identical.

**Diagram**




**Pinout**




## Specifications

**Supply Voltage**

12 V DC to 30 V DC

**Supply Current**

55 mA max current (exclusive of load)

**Supply Protection Circuitry**

Protected against reverse polarity and transient voltages

**Touch Dwell Time (momentary models only)**

If a touch dwells for longer than 60 seconds, the output and indicator color will revert back to the untouched state.

[1] Integral 5-pin M12 male quick-disconnect connector models are listed.
- To order the 150 mm (6 in) PVC cable model with a 5-pin M12 male quick-disconnect connector, replace the suffix "Q" with "QP" in the model number. For example, K30ALBTXGHQP.
- To order the 2 m (6.5 ft) PVC cable model, omit the suffix "Q" in the model number. For example, K30ALBTXGH.
- Models with a quick-disconnect connector require a mating cordset.

Original Instructions
16-Oct-25

© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com

170455
p/n: 170455 Rev. E

ПРОМЭЛЕКТРОНИКА/ sales@prom-elec.com

**Output Response Time**

150 milliseconds ON and OFF

**Output Rating**

Maximum Load: 150 mA

ON-state saturation voltage: < 2 V DC at 10 mA; < 2.5 V DC at 150 mA

OFF-state leakage current: < 10 µA at 30 V DC

**Power-Up Delay**

300 milliseconds

Latching models start up in a 'not activated' state

**Mounting**

M22 × 1.5 Threaded base, max torque 2.25 Nm (20 in·lbf)

**Connections**

Integral 5-pin M12 male quick-disconnect connector, 2 m (6.5 ft) integral PVC-jacketed cable, or 150 mm (6 in) PVC-jacketed cable with a 5-pin M12 male quick-disconnect connector

**Environmental Rating**

IP67, IP69K per ISO 20653

Cabled models also meet IP69K per ISO 20653 if the cable and cable entrance are protected from high-pressure spray.

Enclosure Type 4X, 13

**Operating Conditions**

–40 °C to +50 °C (–40 °F to +122 °F)

90% at +50 °C maximum relative humidity (non-condensing)

**Storage**

–40 °C to +70 °C (–40 °F to +158 °F)

**Vibration and Mechanical Shock**

All models meet MIL-STD-202F, Method 201A (Vibration: 10 Hz to 60 Hz maximum, 0.06 inch (1.52 mm) double amplitude, 10G maximum acceleration) requirements. Also meets IEC 60947-5-2 (Shock: 30G 11 ms duration, half sine wave) requirements.

**Construction**

Housing: polycarbonate

Translucent dome: polycarbonate

Mounting nut: PBT

**Required Overcurrent Protection**

**WARNING:** Electrical connections must be made by qualified personnel in accordance with local and national electrical codes and regulations.

Overcurrent protection is required to be provided by end product application per the supplied table.

Overcurrent protection may be provided with external fusing or via Current Limiting, Class 2 Power Supply.

Supply wiring leads < 24 AWG shall not be spliced.

For additional product support, go to www.bannerengineering.com.

| Supply Wiring (AWG) | Required Overcurrent Protection (A) | Supply Wiring (AWG) | Required Overcurrent Protection (A) |
|---|---|---|---|
| 20 | 5.0 | 26 | 1.0 |
| 22 | 3.0 | 28 | 0.8 |
| 24 | 2.0 | 30 | 0.5 |

**Certifications**

Banner Engineering BV
Park Lane, Culliganlaan 2F bus 3
1831 Diegem, BELGIUM

## Dimensions

All measurements are listed in millimeters [inches], unless noted otherwise. The measurements provided are subject to change.





© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com

# Accessories

## Cordsets

| 5-Pin Single-Ended M12 Female Cordsets | | | | |
|---|---|---|---|---|
| **Model** | **Length** | **Style** | **Dimensions** | **Pinout (Female)** |
| MQDC1-501.5 | 0.5 m (1.5 ft) | Straight |  | <br>1 = Brown<br>2 = White<br>3 = Blue<br>4 = Black<br>5 = Gray |
| MQDC1-503 | 0.9 m (2.9 ft) | | | |
| MQDC1-506 | 2 m (6.5 ft) | | | |
| MQDC1-515 | 5 m (16.4 ft) | | | |
| MQDC1-530 | 9 m (29.5 ft) | | | |
| MQDC1-560 | 18 m (59 ft) | | | |
| MQDC1-5100 | 31 m (101.7 ft) | | | |
| MQDC1-506RA | 2 m (6.5 ft) | Right-Angle |  | |
| MQDC1-515RA | 5 m (16.4 ft) | | | |
| MQDC1-530RA | 9 m (29.5 ft) | | | |
| MQDC1-560RA | 19 m (62.3 ft) | | | |

| 5-Pin Single-Ended M12 Female Stainless Steel Washdown Cordsets | | | | |
|---|---|---|---|---|
| **Model** | **Length** | **Style** | **Dimensions** | **Pinout (Female)** |
| MQDC-WDSS-0506 | 2 m (6.56 ft) | Straight |  | <br>1 = Brown<br>2 = White<br>3 = Blue<br>4 = Black<br>5 = Gray |
| MQDC-WDSS-0515 | 5 m (16.4 ft) | | | |
| MQDC-WDSS-0530 | 9 m (29.5 ft) | | | |

| 5-Pin Single-Ended M12 Female Washdown, Shielded Cordsets | | | | |
|---|---|---|---|---|
| **Model** | **Length** | **Style** | **Dimensions** | **Pinout (Female)** |
| MQDCWD-506 | 2 m (6.56 ft) | Straight |  | <br>1 = Brown<br>2 = White<br>3 = Blue<br>4 = Black<br>5 = Gray |
| MQDCWD-530 | 9 m (29.5 ft) | | | |

## Brackets

All measurements are listed in millimeters, unless noted otherwise. The measurements provided are subject to change.

**SMB22A**

- Right-angle bracket with curved slot for versatile orientation
- 12-ga. stainless steel
- Mounting hole for 22 mm sensor

**Hole center spacing:** A to B = 26.0
**Hole size:** A = ø 4.6, B = 4.6 x 16.9, C = 22.2





© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com

**SMB22FVK**

- V-clamp, flat bracket and fasteners for mounting to pipe or extensions
- Clamp accommodates 28 mm diameter tubing or 1 in. square extrusions
- 22 mm hole for mounting sensor

**Hole size:** A = ø 22.5




**SMB22RAVK**

- V-clamp, right-angle bracket and fasteners for mounting to pipe or extensions
- Clamp accommodates 28 mm diameter tubing or 1 in. square extrusions
- 22 mm hole for mounting sensor

**Hole size:** A = ø 22.5




**SMBAMS22P**

- Flat SMBAMS series bracket with 22 mm hole for mounting sensors
- Articulation slots for 90+° rotation
- 12-ga. (2.6 mm) cold-rolled steel

**Hole center spacing:** A = 26.0, A to B = 13.0
**Hole size:** A = 26.8 x 7.0, B = ø 6.5, C = ø 22.5




**SMBAMS22RA**

- Right-angle SMBAMS series bracket with 22 mm hole for mounting sensors
- Articulation slots for 90+° rotation
- 12-ga. (2.6 mm) cold-rolled steel

**Hole center spacing:** A = 26.0, A to B = 13.0
**Hole size:** A = 26.8 x 7.0, B = ø 6.5, C = ø 22.5




**TC-K30-CL**

- Touch cover

**Diameter:** A = 40.7 mm
**Height:** B = 31 mm




# Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

**THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.**

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.


© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com