

FOR-1351 Rev.1.0

7

1

2

3

4

5

6

7

8

Contacts, silver-plated		(ØA)		Wire gauge		Recommended stripping length		REVISION RECORD				
Type of products				(mm²)		(AWG)		REV	ECN	DESCRIPTION	DRFT	DATE
◆ 40A-SF-1.5		1.75		1.5		16		9.0mm				
40A-SF-2.5		2.25		2.5		14		9.0mm				
40A-SF-4.0		2.85		4.0		12		9.6mm				
40A-SF-6.0		3.5		6.0		10		9.6mm				
40A-SF-10		4.3		10.0		8		12mm				

Crimp contacts

01. Material :Copper alloy

02. Surface :hard-silver plated

03. Contact resistance :≤0.3mΩ

04. Terminal :Crimp connection

05. Wire gauge :1.5-6mm² (AWG 16-10)

06. Rohs Compliance

Technical drawing of a crimp contact. The drawing shows a side view and a cross-sectional view. The side view indicates a length of 9.6 and a width of 23.5. The cross-sectional view shows a crimped wire with a diameter of 0.9 and a crimp depth of 0.6.

PART NO.: /		NINGBO DEGSON ELECTRICAL CO., LTD	
APPD: HJS 2016.8.11		NAME: 40A-Female Contacts	
CHKD: CLK 2016.8.10		TITLE: CUSTOMER DRAWING	
DRFT: Mr. Yang 2016.08.08		DRAWING NO.: /	
THIRD ANGLE PROJECTION		DO NOT SCALE	
MM (INCH)		SCALE 5:1	