


## R13-87




| Rating                |  |
|-----------------------|--|
| 16A 125V AC 1/3HP     |  |
| 10A 250V AC 1/2HP     |  |
| Contact resistance    |  |
| 50mΩ Max              |  |
| Insulation resistance |  |
| DC 500V 100MΩ Min     |  |
| Dielectric strength   |  |
| AC 1500V 1 minute     |  |
| Cut-out               |  |

X

Y

## R13-117



| 05 <sup>A</sup> 01 | X        | Y        |
|--------------------|----------|----------|
| 0.75-1.25          | 30.2±0.1 | 22.2±0.1 |
| 1.25-2             | 30.4±0.1 | 22.2±0.1 |
| 2-3                | 30.8±0.1 | 22.2±0.1 |

### FEATURES

- \* MATERIAL: Frame is nylon (UL flame: 94V-2). Terminals are silver plated brass.
- \* Illuminated actuators are molded in PC, available with red, amber, green, blue and white colors.
- \* Snap-in mounting, easy to install switch into panel.
- \* Waterproof cover is optional.



R13- 87 - 0 2

R13-117 - 0 1

| FUNCTION |  | TERMINAL |                              |
|----------|--|----------|------------------------------|
| A        |  | 0 1      | .250" SQ<br>For R13-117 only |
|          |  | 0 2      | .187" SQ<br>For R13-87 only  |
| B        |  |          |                              |
| C        |  |          |                              |
| D        |  |          |                              |
| E        |  |          |                              |
| F        |  |          |                              |
| G        |  |          |                              |
| H        |  |          |                              |
| I        |  |          |                              |

\* ( ) =momentary

