


■Features

- High Luminous LEDs
- 10mm Round Standard Directivity
- Superior Weather-resistance
- UV Resistant Epoxy
- Color Diffused Type

■Applications

- Electronic Signs And Signals
- Small Area Illuminations
- Back Lighting
- Other Lighting

■Outline Dimension




■Absolute Maximum Rating

(Ta=25°C)

Item	Symbol	Value		Unit
		YG/Y/O/R	B/PG	
DC Forward Current	I _F	30	30	mA
Pulse Forward Current*	I _{FP}	100	100	mA
Reverse Voltage	V _R	5	5	V
Power Dissipation	P _D	78	108	mW
Operating Temperature	Topr	-30 ~ +85		°C
Storage Temperature	Tstg	-40 ~ +100		°C
Lead Soldering Temperature	Tsol	260°C/5sec		-

*Pulse width Max.10ms Duty ratio max 1/10

■Directivity



■Electrical -Optical Characteristics

(Ta=25°C)

Part Number	Color			V _F (V)			I _R (μA)	I _v (mcd)			Wd(nm)*			2θ1/2(deg)
				Min.	Typ.	Max.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Typ.
				I _F =20mA			V _R =5V	I _F =20mA			I _F =20mA			
OSB5YUA1K4A	Blue	B		2.8	3.1	3.6	10	150	220	-	465	470	475	180
OSG5TAA1K4A	Pure Green	PG		2.8	3.1	3.6	10	220	330	-	520	525	530	180
OSG8NUA1K4A	Yellow Green	YG		1.8	2.1	2.6	10	20	30	-	565	570	575	180
OSY5LUA1K4A	Yellow	Y		1.8	2.1	2.6	10	30	45	-	585	590	595	180
OSY5JAA1K4A	Yellow	Y		1.8	2.1	2.6	10	150	220	-	585	590	595	180
OSO5JAA1K4A	Orange	O		1.8	2.1	2.6	10	150	220	-	600	605	610	180
OSR5JAA1K4A	Red	R		1.8	2.1	2.6	10	150	220	-	620	625	630	180
OSR6LUA1K4A	Red	R		1.8	2.1	2.6	10	30	45	-	630	640	650	180

*1 Tolerance of measurements of dominant wavelength is ±1nm

*2 Tolerance of measurements of luminous intensity is ±15%

*3 Tolerance of measurements of forward voltage is ±0.1V

LED & Application Technologies

