








TOP VIEW




END VIEW
SECTION A-A




SIDE VIEW
SECTION B-B



BOTTOM BOX



INSIDE LID



INSIDE BOX

ACCEPTS M3
SELF-TAPPING
SCREW

Dimensions:
mm
[inches]

Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory (modshop@hammondmg.com) for quotes
Solid models of this enclosure available in .stp or .x_t
(Part number and text placement/orientation on our products are subject to change,
we do not recommend using them as a locating reference for modification purposes)

NOTE

Purchased assembly includes box, lid, string gasket, 4 PCB screws, and 4 lid screws.

Recommended Torque : (43-50) Ozf.in / (30-35) cN.m

RP Enclosure

General Purpose ABS Light Grey (UL94 HB)	RP1095BF
General Purpose ABS Light Grey with Polycarbonate Clear Lid (UL94 HB)	RP1095CBF
Polycarbonate Off-White (UL94-V2)	RP1090BF
Polycarbonate Off-White with Clear Lid (UL94-V2)	RP1090CBF

ACCESSORIES

Lid Screw (M3.5-0.6 X 10mm) (50 Pkg)	SC619-50
PCB Screw (M3 X 6mm Self-tapping) (50 Pkg)	SC622-50
General Purpose ABS Black Inner Panel 3mm Thick	STC109
Metal Inner Panel 1mm Thick	STA109
String Gasket EPDM Grey (2 Pkg)	RP108GASKET



**HAMMOND
MANUFACTURING.**

RP109 BF

www.hammondmg.com