






[illegible]

NOTES:

1.MATERIAL:

HOUSING: THERMOPLASTIC. UL 94V-0 RATED, COLOR: BLACK.
CONTACT: COPPER ALLOY.
SHELL: COPPER ALLOY
MYLAR: KAPTON TAPE.

2.FINISH;

CONTACT: UNDERPLATED 50u"MIN. NICKEL OVERALL
100u" MIN. MATTE TIN PLATED ON SOLDERING AREA,
SELECTIVE GOLD PLATED ON CONTACT AREA.

SHIELD: CODE N: NICKEL 40u" ~120u" PLATED OVERALL.
T: SELECTIVE 60u" MIN. MATTE TIN ON LEGS OVER 40u"~120u" NICKEL.

3.10033526-X3212XLF MEETS THE EUROPEAN UNION DIRECTIVE AS DESCRIBE
IN GS-22-008 AND ITS HSG WILL WITHSTAND EXPOSE TO 260 DEGREE C
PEAK TEMPTURE FOR 10 SECONDS IN A IR REFLOW APPLICATION.

4. PRODUCT SPEC: GS-12-174 ; PACKAGE SPEC: GS-14-873.

5. PRODUCT ORDERING DATA :

FOR LEAD-FREE

10033526 - N X X X X M LF
 T T T T T T LF LF: Lead Free

- M: WITH MYLAR
BLANK: WITHOUT MYLAR



PACKAGING METHOD:
2: TAPE & REEL PACKAGING

POST OPTION:
1 : WITH PLASTIC POST.
2 : WITHOUT PLASTIC POST.

- HSG MATERIAL:
1 OR 2 : HIGH TEMP THERMOPLASTIC

- PLATING IN CONTACT AREA:
3 : 30u" Au.

— N: NICKEL FOR SHIELD.
T: SELECTIVE TIN ON LEGS.



RECOMMENDED PCB LAYOUT FOR 10033526-XXX2X
GENERAL TOLERANCE $+/-0.05\text{mm}$

[illegible]