












	1	2	3	4	5	6	7	8
F	OB-SERIES CABLE COLLET(CABLE OD)							
	CABLE CLAMP SET			CABLE DIA RANGE				
	TYPE		CODE ①	MAX	MIN △C			
E	FLBB-XXFGMS-XCP-XXX △B		201	3.2	2.2			
204			4.2	3.3				
207			5.2	4.3				
--			--	--				
D	KEY POINT ②							
	CODE	G	A	B	C	J	F	
C	GRAPHIC	0° 	30° 	60° 	90° 	45° 	155° 	
	PIN CONFIGURATION (Solder Definition) ③							
B	GRAPHIC	 2 PIN	 3 PIN	 4 PIN	 5 PIN	 6 PIN	 7 PIN	 9 PIN
A	UNIT:mm TOLERANCE ±0.5MM	TITLE FLO OB FI CONNECTOR		Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO DWG NO FLBB-XXFGMS-XCP-XXX CUSTOMER ALTW	DRAWN BY Ouyang CHECKED BY Mafei APPROVED BY Jerry	DATE 2019/09/04 DATE 2019/09/04 DATE 2019/09/04
	1	2	3	4	5	6	7	8WI0814-03-表單01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

FLBB-XXFGMS-XCP-XXX △B

CABLE OD ①

KEY POINT ②

PIN CONFIGURATION ③

SIZE(CONNECTOR)