

Customer Information Sheet

DRAWING No.: M22-19X00XX

SHEET 2 OF 2


IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm



SPECIFICATIONS:

MATERIALS:

MOULDING = GLASS FILLED POLYESTER UL94V-0
CONTACT = BERYLLIUM COPPER

FINISH:

CONTACT:

05 = 0.13μ GOLD ON CONTACT FACE OVER NICKEL

46 = 3μ 100% TIN OVER NICKEL

MOULDING COLOUR = SEE ORDER CODE

ELECTRICAL:

CURRENT RATING AT 25°C = 2A MAX

WORKING VOLTAGE = 250V AC/DC

VOLTAGE PROOF = 500V AC/DC @ 50Hz

CONTACT RESISTANCE (MAXIMUM):

TIN/LEAD = 20mΩ INITIAL

25mΩ AFTER CONDITIONING

GOLD = 15mΩ INITIAL

20mΩ AFTER CONDITIONING

INSULATION RESISTANCE (MINIMUM):

INITIAL = 1000MΩ

AFTER CONDITIONING = 1000MΩ

ENVIRONMENTAL:

TEMPERATURE RANGE = -40°C TO +85°C

MECHANICAL:

DURABILITY:

TIN/LEAD = 50 OPERATIONS

GOLD = 300 OPERATIONS

INSERTION FORCE = 10N MAX

WITHDRAWAL FORCE = 1N MIN

FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C013XX (LATEST ISSUE)

OBSOLETE

M22-1930046

All other combinations still active products

ORDER CODE:

M22-19X00XX

MOULDING COLOUR

0 = BLACK

1 = BLUE

2 = RED

3 = LIGHT GREY

CONTACT FINISH

05 = GOLD

46 = 100% TIN

MSP	6	09.12.14	12158
NAME	ISS.	DATE	C/NOTE
APPROVED: M.PERREN			
CHECKED: S.BENNETT			
DRAWN: W.J.BOURNE			
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm

X.X = ±0.25mm

X.XX = ±0.10mm

X.XXX = ±0.01mm

ANGLES = ±5°

UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH: SEE ABOVE

S/AREA: mm²

TITLE:

2mm PITCH JUMPER SOCKET
ASSEMBLY (OPEN TOP)

DRAWING NUMBER:

M22-19X00XX

SHT
2
OF
2