

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

変更

DESCRIPTION

DATE

DWN

APVD

J

—

P

LTR

REDRAWN W/CHANGE

ECR-12-021403

13DEC2012

TS

KB

1

2

3

4

5

6

1

2

3

4

5

6

9.1

6.5

2.95

2.25

0

3.5

7

10.5

14

17.5

22

21.6±0.5

24.4REF

1

2

1

2

10.6±0.5

15.9REF

-A-

△ MUST BE KEPT BETWEEN -A- AND 2

△ TO BE MATED WITH THE CAP HOUSING SMOOTHLY

3. APPLIED RECEPTACLE CONTACT PART NUMBER; 173630 AND 173631

4. APPLIED CAP HOUSING; 174930, etc.

△ -A- 面より2mmの範囲で測定

△ 相手ハウジングと所定の機能を満足して嵌合できること

3. 内装するリセプタクルコンタクト型番173630 及び 173631

4. 嵌合相手ハウジング型番; 174930 他

V-2	自然色 (NATURAL)	1-174923-1	
HB	黄 (YELLOW)	174923-7	
	灰 (GRAY)	174923-6	
	青 (BLUE)	174923-5	
	緑 (GREEN)	174923-4	
	黒 (BLACK)	174923-2	
自然色 (NATURAL)	174923-1		
使用材料難燃グレード (FLAMMABILITY OF MATERIAL)		色 (COLOR)	型番 (PART NUMBER)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
一般公差

0 PLC ±—

1 PLC ±—

2 PLC ±—

3 PLC ±—

4 PLC ±—

ANGLES ±—

TOLERANCES UNLESS OTHERWISE SPECIFIED:
一般公差

10_± : ±0.2

30_± > 10 : ±0.25

100_± > 30 : ±0.3

ANGLE : ±3°

MATERIAL
材料

PBT

FINISH
仕上

—

DWN

T.SHINOHARA

13DEC2012

CHK

K.BETSUI

13DEC2012

APVD

K.BUTSUI

13DEC2012

PRODUCT SPEC
製品規格

108-5264

APPLICATION SPEC
取付適用規格

—

WEIGHT

—

CUSTOMER DRAWING

TE Connectivity

070 SERIES MULTI-LOCK CONNECTOR
6POSITION PLUG HOUSING

SIZE

A3

CAGE CODE

00779

DRAWING NO
番号

C-174923

RESTRICTED TO

—

SCALE
尺度

2:1

SHEET

1 OF 1

REV

E2

1470-19 (3/11)

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА