

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC
FT

DIST
0

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
J1		REVISED PER ECO-11-004820	11MAR11	RK	HMR

AMP MARKING

4 PLC

.107
.000
.213

PERIPHERAL SEAL BONDED IN PLACE
SEE TABLE

.148
.000
.148

1.435±.025

1.125±.010
2 PLC

1.125±.010
2 PLC

1.435±.025

1.125±.010
2 PLC

Ø.150
4 HOLES

1.635 MAX

.420±.015

.094±.010

1.050±.010

206425-1

HOUSING

1.110 MAX DIA

15/16-20 UNEF-2A

.125 MAX PANEL

Ø1.210

1.125±.010
2 PLC

1.125±.010
2 PLC

Ø.150+
-
Ø.150
4 HOLES

DETAIL A

RECOMMENDED PANEL CUTOUT

AMP MARKING

R.062
4 PLC

.107
.000
.213

.148
.000
.148

1.161 MAX

1.310 MAX DIA

1.635 MAX

.420±.015

.094±.010

1.050±.010
DIA

206425-2

HOUSING

1.110 MAX DIA

15/16-20 UNEF-2A

DETAIL B

NOTES:

1. CAVITY IDENTIFICATION ON FRONT AND REAR FACE.

2. WILL ACCEPT (3) TYPE XII SOCKET CONTACTS.

△ PART NUMBER AND "AMP" INSIGNIA CAN BE LOCATED ON ANY FLANGE EDGE.

4-40 THREADED INSERTS	NO	A	206425-5
.150±.003	YES	A	206425-3
.150±.003	NO	B	206425-2
.150±.003	NO	A	206425-1
C	PERIPHERAL SEAL	SEE DETAIL	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M.BINNER CHK R.STONE APVD -	06/01/94 6-23-94	NAME	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC 108-10024 APPLICATION SPEC -	
		0 PLC ± - 1 PLC ± - 2 PLC ± .005 3 PLC ± - 4 PLC ± - ANGLES ± - FINISH -		SIZE A1	
MATERIAL HOUSING: NYLON, BLACK SEAL: ELASTOMER, GREY		WEIGHT -		CAGE CODE 00779	
CUSTOMER DRAWING		SCALE 2:1		SHEET 1 OF 1	
				REV J1	

4805 (3/11)

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА