







TOP VIEW




SECTION B-B
END VIEW




SECTION A-A
SIDE VIEW



USEABLE PANEL AREA




INSIDE BOTTOM



INSIDE TOP

MAXIMUM PCB LAYOUT
DRAWINGS ARE AVAILABLE

Dimensions:
mm
[inches]



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory (modshop@hammfg.com) for quotes
Solid models of this enclosure available in .stp or .x_t
(Part number and text placement/orientation on our products are subject to change,
we do not recommend using them as a locating reference for modification purposes)

NOTE

Purchased assembly includes box, lid, 2 Panels and 4 cover screws
Molded from FR ABS (UL94-V0) plastic

Recommended Cover screw torque -- 21-28 ozf-in (15-20 cN-m)

1552

1552D Regular Enclosure

Fire Retardant ABS Grey	1552D5GY
Fire Retardant ABS Black	1552D5BK

ACCESSORIES

1552D End Panel (Pkg 10)	1552DPLGY-10 (Grey)
	1552DPLBK-10 (Black)
1552D cover screw [#2 X 3/4" Self-Tap] (Pkg 50)	SC551-50 (Grey)
	SC551BK-50 (Black)
1552D Cable gland Kit [1 Cable Gland, 1 Tie Down, 2 Tie down screws]	1552DPGKITGY (Grey)
	1552DPGKITBK (Black)
1552 Wall Mount Holder	1552DHGY (Grey)
	1552DHBK (Black)
Tie Down Screw [#2 X 1/4" Self-Tap] (Pkg 50)	SC508-50
P.C. Board Plastite Self Tapping Screw [#2 x 3/16" Self-Tap] (PKG 100)	1553WTS100

HAMMOND
MANUFACTURING
1552D5
www.hammondmfg.com

REV: 15.10.2019