Mureva boxes
Accessories

Accessories for cable entries without strain relief

	ISO diameter	Diameter of cable / conduit (mm)	Diameter of drilling (mm)	Colour	Reference	Qty per package
	Grommets					
P120649 P120645 P120647	Flexible grommet suitable for unthreaded holes. For fast installation by using either EVA (easy valve access) membrane entry, i.e. direct entry of rigid cables 4-14 mm², or stepped entry, by removing a step of the desired diameter for cables or conduits from 14 mm² to 20, 25, 32 and 40 mm² respectively. Degree of protection IP55. Usage temperature: -25°C...+40°C. Material: SBS					
		4-20	Ø 23	Grey RAL 7035	**ISM71071**	10
				White RAL 9003	**IMT36130**	10
				Dark grey RAL 7004	**ENN08131**	10
		4-25	Ø 29	Grey RAL 7035	**ISM71072**	10
				White RAL 9003	**IMT36131**	10
				Dark grey RAL 7004	**ENN08132**	10
		4-32	Ø 36	Grey RAL 7035	**ISM71073**	10
		4-40	Ø 44	Grey RAL 7035	**ISM71074**	10
	TET grommets					
P60848	Grommet suitable for holes with metric thread and various diameters. IP67 Material: EPDM					
	M12	Ø 3 / 5	Ø 12 - 13	Grey	**IMT36179**	50
	M16	Ø 5 / 7	Ø 16 - 17	Grey	**IMT36180**	50
	M20	Ø 7 / 10	Ø 20 - 21	Grey	**IMT36181**	50
	M25	Ø 10 / 14	Ø 25 - 26	Grey	**IMT36182**	50
	M32	Ø 14 / 20	Ø 32 - 33	Grey	**IMT36183**	50
	M40	Ø 20 / 26	Ø 40 - 41	Grey	**IMT36184**	25
	M50	Ø 26 / 35	Ø 50 -51	Grey	**IMT36185**	25

Accessories for coupling

	Type	For boxes (mm)	For trunking (mm)	Color	Reference	Qty per package
	Coupling kit					
P120839	Coupling M32 to be used to connect two boxes (from 105 x 105 mm) with M32 knock-outs. Enables side-by-side mounting of boxes without reduction of the IP classification Material: Polystyrene					
	Coupling	From 175 x 150 x 80		Grey	**13934**	2

Accessories for fixing

	Universal fixing for IPN profiles and cable trays					
P100907	Universal fixing intended for the fixing of < 105 x 105 mm (internal dimension) junction boxes on IPN profiles from 2 to 12 mm and all types of cable trays Material: Steel					
	Universal fixing			Grey	**ENN08167**	10
	Universal fixing for mesh trays					
P120644	Universal fixing intended for the fixing of < 105 x 105 mm (internal dimension) junction boxes on all types of mesh trays Material: PA6 with 30% glass-fibre					
	Universal fixing			Grey	**ENN08162**	10
	Fixing lugs					
P120661	Fixing lugs intended for mounting of < 105 x 105 mm junction boxes. Fixing is made outside the waterproof space Material:					
	Fixing lugs				**NSYAEFTB**	4

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА