

1	2	3	4	5	6	7																																																																			
				FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人																																																																			
A							A																																																																		
B							B																																																																		
LED PIN LED PIN 12 10 2.5 3 1NO1NC IN THIS WAY 6 Max. 25 38.5 2 TOP M16X1 THE SHADED PART IS ILLUMINATED Ø18 20^{+0.1}₀ Ø22^{+0.2}₀ PANEL CUTOUT Ø24 Ø21 0.7 SEAL RING (IP40 HAS NO GASKET)							B																																																																		
C							C																																																																		
SCHEMATIC NO NC C + R - SINGLE-BREAKPOINT QUICK-ACTING CONTACT SWITCHES WITH THREE TERMINALS							C																																																																		
D							D																																																																		
SPECIFICATIONS: 1.SWITCH RATING: Ui:250V, Ith:5A. 2.MECHANICAL LIFE: ≥1,000,000 cycles. 3.ELECTRICAL LIFE: ≥50,000 cycles. 4.INITIAL CONTACT RESISTANCE: ≤50mΩ. 5.INSULATION RESISTANCE: ≥100MΩ(500VDC). 6.POWER-FREQUENCY WITHSTAND VOLTAGE: BETWEEN CONTACT AND LAMP TERMINALS: AC 2,000V, RMS 50HZ, 1min; BETWEEN TERMINALS OF THE SAME POLE: AC 1,500V, RMS 50HZ, 1min; BETWEEN TERMINALS OF DIFFERENT POLE: AC 2,000V, RMS 50HZ, 1min. 7.OPERATING TEMPERATURE: -25℃~ +55℃(NO FREEZING, KEEP THE AIR FLOWING AROUND PUSHBUTTON). 8.OPERATING FORCE: ABOUT 1.7N(1NO1NC), ABOUT 3N(2NO2NC). 9.OPERATING TRAVEL: ABOUT 3mm. 10.FRONT FANEL PROTECTION DEGREE: IP40/IP65. 11.TERMINAL TYPE: PIN TERMINAL(2.8 X 0.5mm). 12.GENERAL TOLERANCE:0-18mm=±0.25, 18-80mm=±0.52. MATERIALS: 1.CONTACT: SILVER ALLOY. 2.BUTTON: PC. 3.BODY: PC. 4.BASE: PBT. PART NUMBER: LAS1-A☆Y-□■T/△/▲/◎ <table><tr><td>"☆"</td><td>CODE OF VARIETY</td><td>"△"</td><td>CAP OR LAMP COLOR</td><td>"▲"</td><td>LAMP VOLTAGE</td></tr><tr><td>P</td><td>BLACK FRAME</td><td>R</td><td>RED</td><td>6V</td><td>AC/DC 6V</td></tr><tr><td>W</td><td>SILVERY FRAME</td><td>G</td><td>GREEN</td><td>12V</td><td>AC/DC 12V</td></tr><tr><td>"□"</td><td>CONTACT STRUCTURE</td><td>Y</td><td>YELLOW</td><td>24V</td><td>AC/DC 24V</td></tr><tr><td>11</td><td>1NO1NC</td><td>B</td><td>BLUE</td><td>110V</td><td>AC/DC 110V</td></tr><tr><td>22</td><td>2NO2NC</td><td>W</td><td>WHITE</td><td>220V</td><td>AC/DC 220V</td></tr><tr><td colspan="4"></td><td colspan="2">OTHER VOLTAGE CAN BE MADE TO ORDER</td></tr><tr><td>"■"</td><td>OPERATION MODE</td><td colspan="4"></td></tr><tr><td>NO LETTER</td><td>MOMENTARY</td><td colspan="4"></td></tr><tr><td>Z</td><td>LATCHING</td><td colspan="4"></td></tr></table><table><tr><td>"◎"</td><td>IP CLASS</td></tr><tr><td>NO LETTER</td><td>IP40</td></tr><tr><td>P</td><td>IP65</td></tr></table>							"☆"	CODE OF VARIETY	"△"	CAP OR LAMP COLOR	"▲"	LAMP VOLTAGE	P	BLACK FRAME	R	RED	6V	AC/DC 6V	W	SILVERY FRAME	G	GREEN	12V	AC/DC 12V	"□"	CONTACT STRUCTURE	Y	YELLOW	24V	AC/DC 24V	11	1NO1NC	B	BLUE	110V	AC/DC 110V	22	2NO2NC	W	WHITE	220V	AC/DC 220V					OTHER VOLTAGE CAN BE MADE TO ORDER		"■"	OPERATION MODE					NO LETTER	MOMENTARY					Z	LATCHING					"◎"	IP CLASS	NO LETTER	IP40	P	IP65	D
"☆"	CODE OF VARIETY	"△"	CAP OR LAMP COLOR	"▲"	LAMP VOLTAGE																																																																				
P	BLACK FRAME	R	RED	6V	AC/DC 6V																																																																				
W	SILVERY FRAME	G	GREEN	12V	AC/DC 12V																																																																				
"□"	CONTACT STRUCTURE	Y	YELLOW	24V	AC/DC 24V																																																																				
11	1NO1NC	B	BLUE	110V	AC/DC 110V																																																																				
22	2NO2NC	W	WHITE	220V	AC/DC 220V																																																																				
				OTHER VOLTAGE CAN BE MADE TO ORDER																																																																					
"■"	OPERATION MODE																																																																								
NO LETTER	MOMENTARY																																																																								
Z	LATCHING																																																																								
"◎"	IP CLASS																																																																								
NO LETTER	IP40																																																																								
P	IP65																																																																								
E							E																																																																		
1	2	3	4	5	6	7																																																																			

BRAND 品牌

ONPOW 欧宝龙®

红波按钮制造有限公司

ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

TITLE 名称	LAS1-AP(W) SERIES PUSHBUTTON SWITCHES	UNIT 单位	mm
DWG NO. 图号	LAS1-AP(W)Y-T	SCALE 比例	1.2 : 1
FILE NAME 档案名称	LAS1-AP(W)Y-T .DWG	SHEET 张	1/1
DRAWN 制图	YDY 2024/10/18	REV. 更改	V1.0