



CFPS-39x

Surface mount 3.2 x 2.5mm crystal oscillator in a hermetically sealed ceramic package with a seam sealed metal lid.

Fast Make capability: CFPP-39 programmable oscillator is the nearest

Model Name	Description
CFPS-39	A 3.3V Version
CFPS-40	A 2.5V Version
CFPS-41	A 1.8V Version

ISSUE 5; October 2018

Description

- Surface mount 3.2 x 2.5mm crystal oscillator in a hermetically sealed ceramic package with a seam sealed metal lid.
- Fast Make capability: CFPP-39 programmable oscillator is the nearest equivalent fast make model.

Frequency Parameters

- Frequency: 2.0MHz to 125.0MHz
- Frequency Stability: $\pm 25.00\text{ppm}$ to $\pm 100.00\text{ppm}$
- Ageing: $\pm 3\text{ppm}$ max per year @ 25°C

Electrical Parameters

- Supply Voltage: 3.3V $\pm 10\%$

Operating Temperature Ranges

- 10 to 70°C
- 40 to 85°C

Output Details

- Output Compatibility: CMOS
- Drive Capability: 15pF max

Output Control

- Standby Operation:
Logic '1' (>70% VS) to pad 1 enables oscillator output
Logic '0' (<30% VS) to pad 1 disables oscillator output; when disabled the oscillator output goes to the high impedance state
No connection to pad 1 enables oscillator output
Standby Current: 10µA max
Start-Up Time: 10ms max

Environmental Parameters

- Storage Temperature Range: -55 to 125°C
- Shock: MIL-STD-202F, Method 213B: 1000G, 0.5ms, 1/2 sine wave
- Vibration: MIL-STD-202F, Method 204D, Test Condition D: 20G (10Hz-2000Hz), 4hrs in 3 mutually perpendicular planes (total 12hrs)

Manufacturing Details


- Maximum Process Temperature: 260°C (10secs max)

Ordering Information


- Frequency*
- Model*
- Output
- Frequency Stability*
- Operating Temperature Range*
- Supply Voltage
- Example
10.0MHz CFPS-39
CMOS $\pm 50\text{ppm}$ -10 to 70C 3.3V

Compliance



- RoHS Status (2011/65/EU): Compliant
- REACH Status: Compliant
- MSL Rating (JDEC-STD-033): Not Applicable




Outline (mm)



- Pad Connections
1. Enable/Disable
 2. GND
 3. Output
 4. +Vs



Test Circuit




ISSUE 5; October 2018

Packaging Details

- Pack Style: Reel Tape & reel in accordance with EIA-481-D
Pack Size: 1,000
- Pack Style: Cutt In tape, cut from a reel
Pack Size: 100
- Pack Style: Bulk Loose in bulk pack
Pack Size: 100

Wave Form



Electrical Specification - maximum limiting values 3.3V $\pm$ 10%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
2.0MHz	9.999999MHz	-10 to 70	± 25.0	7	5	45/55%
		-40 to 85	± 25.0	7	5	45/55%
10.0MHz	19.999999MHz	-10 to 70	± 25.0	7	5	45/55%
		-40 to 85	± 25.0	7	5	45/55%
20.0MHz	31.999999MHz	-10 to 70	± 25.0	12	5	45/55%
		-40 to 85	± 25.0	12	5	45/55%
32.0MHz	50.0MHz	-10 to 70	± 25.0	20	5	45/55%
		-40 to 85	± 25.0	20	5	45/55%
50.000001MHz	125.0MHz	-10 to 70	± 25.0	30	5	40/60%
		-40 to 85	± 25.0	30	5	40/60%

This document was correct at the time of printing; please contact your local sales office for the latest version.

[Click to view latest version on our website.](#)

ISSUE 5; October 2018

Description

- Surface mount 3.2 x 2.5mm crystal oscillator in a hermetically sealed ceramic package with a seam sealed metal lid.
- Fast Make capability: CFPP-40 programmable oscillator is the nearest equivalent fast make model.

Frequency Parameters

- Frequency: 2.0MHz to 125.0MHz
- Frequency Stability: $\pm 25.00\text{ppm}$ to $\pm 100.00\text{ppm}$
- Ageing: $\pm 3\text{ppm}$ max per year @ 25°C

Electrical Parameters

- Supply Voltage: 2.5V $\pm 5\%$

Operating Temperature Ranges

- 10 to 70°C
- 40 to 85°C

Output Details

- Output Compatibility: CMOS
- Drive Capability: 15pF max

Output Control

- Standby Operation:
Logic '1' (>70% VS) to pad 1 enables oscillator output
Logic '0' (<30% VS) to pad 1 disables oscillator output; when disabled the oscillator output goes to the high impedance state
No connection to pad 1 enables oscillator output
Standby Current: 10 μ A max
Start-Up Time: 10ms max

Environmental Parameters

- Storage Temperature Range: -55 to 125°C
- Shock: MIL-STD-202F, Method 213B: 1000G, 0.5ms, 1/2 sine wave
- Vibration: MIL-STD-202F, Method 204D, Test Condition D: 20G (10Hz-2000Hz), 4hrs in 3 mutually perpendicular planes (total 12hrs)

Manufacturing Details

- Maximum Process Temperature: 260°C (10secs max)

Ordering Information


- Frequency*
- Model*
- Output
- Frequency Stability*
- Operating Temperature Range*
- Supply Voltage
- Example
10.0MHz CFPS-40
CMOS $\pm 50\text{ppm}$ -10 to 70C 2.5V

Compliance


- RoHS Status (2011/65/EU): Compliant
- REACH Status: Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

Packaging Details



- Pack Style: Reel: Tape & reel in accordance with EIA-481-D
Pack Size: 1,000
- Pack Style: Cutt: In tape, cut from reel
Pack Size: 100




Outline (mm)



Pad Connections
1. Enable/Disable
2. GND
3. Output
4. +Vs




Test Circuit



ISSUE 5; October 2018

Wave Form



Electrical Specification - maximum limiting values 2.5V $\pm$ 5%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		$^{\circ}\text{C}$	ppm	mA	ns	%
2.0MHz	9.999999MHz	-10 to 70	± 25.0	6	5	40/60%
		-40 to 85	± 25.0	6	5	40/60%
10.0MHz	19.999999MHz	-10 to 70	± 25.0	8	5	40/60%
		-40 to 85	± 25.0	8	5	40/60%
20.0MHz	31.999999MHz	-10 to 70	± 25.0	8	5	40/60%
		-40 to 85	± 25.0	8	5	40/60%
32.0MHz	50.0MHz	-10 to 70	± 25.0	20	5	40/60%
		-40 to 85	± 25.0	20	5	40/60%
50.000001MHz	125.0MHz	-10 to 70	± 25.0	30	5	40/60%
		-40 to 85	± 25.0	30	5	40/60%

This document was correct at the time of printing; please contact your local sales office for the latest version.

[Click to view latest version on our website.](#)

ISSUE 5; October 2018

Description

- Surface mount 3.2 x 2.5mm crystal oscillator in a hermetically sealed ceramic package with a seam sealed metal lid.
- Fast Make capability: CFPP-41 programmable oscillator is the nearest equivalent fast make model.

Frequency Parameters

- Frequency: 2.0MHz to 125.0MHz
- Frequency Stability: $\pm 25.00\text{ppm}$ to $\pm 100.00\text{ppm}$
- Ageing: $\pm 3\text{ppm}$ max per year @ 25°C

Electrical Parameters

- Supply Voltage: 1.8V $\pm 5\%$

Operating Temperature Ranges

- 10 to 70°C
- 40 to 85°C

Output Details

- Output Compatibility: CMOS
- Drive Capability: 15pF max

Output Control

- Standby Operation:
Logic '1' (>70% VS) to pad 1 enables oscillator output
Logic '0' (<30% VS) to pad 1 disables oscillator output;
when disabled the oscillator output goes to the high impedance state
No connection to pad 1 enables oscillator output
Standby Current: 10µA max
Start-Up Time: 10ms max

Environmental Parameters

- Storage Temperature Range: -55 to 125°C
- Shock: MIL-STD-202F, Method 213B: 1000G, 0.5ms, 1/2 sine wave
- Vibration: MIL-STD-202F, Method 204D, Test Condition D: 20G (10Hz-2000Hz), 4hrs in 3 mutually perpendicular planes (total 12hrs)

Manufacturing Details


- Maximum Process Temperature: 260°C (10secs max)

Ordering Information


- Frequency*
- Model*
- Output
- Frequency Stability*
- Operating Temperature Range*
- Supply Voltage
- Example
10.0MHz CFPS-41
CMOS $\pm 50\text{ppm}$ -10 to 70C 1.8V

Compliance


- RoHS Status (2011/65/EU): Compliant
- REACH Status: Compliant
- MSL Rating (JDEC-STD-033): Not Applicable



Outline (mm)




Pad Connections
1. Enable/Disable
2. GND
3. Output
4. +Vs



Underside View

Test Circuit




ISSUE 5; October 2018

Packaging Details

- Pack Style: Reel Tape & reel in accordance with EIA-481-D
Pack Size: 1,000
- Pack Style: Cutt In tape, cut from a reel
Pack Size: 100

Wave Form



Electrical Specification - maximum limiting values 1.8V ±5%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
2.0MHz	9.999999MHz	-10 to 70 -40 to 85	±25.0 ±25.0	5 5	7 7	40/60% 40/60%
10.0MHz	19.999999MHz	-10 to 70 -40 to 85	±25.0 ±25.0	6 6	7 7	40/60% 40/60%
20.0MHz	31.999999MHz	-10 to 70 -40 to 85	±25.0 ±25.0	6 6	6 6	40/60% 40/60%
32.0MHz	50.0MHz	-10 to 70 -40 to 85	±25.0 ±25.0	15 15	6 6	40/60% 40/60%
50.000001MHz	125.0MHz	-10 to 70 -40 to 85	±25.0 ±25.0	25 25	6 6	40/60% 40/60%

This document was correct at the time of printing; please contact your local sales office for the latest version.

[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200

Germany: 0800 1808 443

France: 0800 901 383

USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com