




快恢复二极管 Fast Recovery Rectifier

- 特征 Features
- I_o 1.5A
 - VRRM 50V-1000V
 - 耐正向浪涌电流能力高
 - High surge current capability

- 用途 Applications
- 整流用 Rectifier

- 极限值（绝对最大额定值）
Limiting Values (Absolute Maximum Rating)

- 外形尺寸和印记 Outline Dimensions and Mark



参数名称 Item	符号 Symbol	单位 Unit	条件 Conditions	FR15						
				1G	2G	3G	4G	5G	6G	7G
反向重复峰值电压 Repetitive Peak Reverse Voltage	V_{RRM}	V		50	100	200	400	600	800	1000
正向平均电流 Average Forward Current	$I_{F(AV)}$	A	正弦半波 60Hz,电阻负载,Ta=75℃ 60Hz Half-sine wave, Resistance load, Ta=75℃	1.5						
正向（不重复）浪涌电流 Surge(Non-repetitive)Forward Current	I_{FSM}	A	正弦半波 60Hz, 一个周期, Ta=25℃ 60Hz Half-sine wave, 1 cycle, Ta=25℃	50						
结温 Junction Temperature	T_J	℃		-55~+150						
储存温度 Storage Temperature	T_{STG}	℃		-55 ~ +150						

- 电特性（Ta=25℃ 除非另有规定）
Electrical Characteristics (Ta=25℃ Unless otherwise specified)

参数名称 Item	符号 Symbol	单位 Unit	测试条件 Test Condition		FR15						
					1G	2G	3G	4G	5G	6G	7G
正向峰值电压 Peak Forward Voltage	V _{FM}	V	I _{FM} =1.5A		1.3						
反向峰值电流 Peak Reverse Current	I _{RRM1}	μA	V _{RM} =V _{RRM}	T _a =25℃	2.5						
	T _a =125℃			100							
反向恢复时间 Reverse Recovery time	t _{tr}	ns	I _F =0.5A I _R =1A I _{RR} =0.25A		150			250	500		
热阻(典型) Thermal Resistance(Typical)	R _{θJ-A}	℃/W	结和环境之间 Between junction and ambient		55						
结电容 Typical junction capacitance	C _j	pF	Measured at 1MHZ and Applied Reverse Voltage of 4.0 V.D.C.		35						

■特性曲线（典型） Characteristics(Typical)

FIG.1 正向电流降额曲线
FORWARD CURRENT DERATING CURVE




FIG.2 最大正向浪涌冲击耐受力
MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3 典型正向特性曲线
TYPICAL FORWARD CHARACTERISTICS




FIG.4 典型反向特性曲线
TYPICAL REVERSE CHARACTERISTICS




FIG.5 反向恢复时间试验电路及测试波形示意图
Diagram of circuit and Testing wave form of reverse recovery time

