CERAMIC SMD MICRO MINIATURE MICROPROCESSOR CRYSTAL

ABM7

Pb in Glass
(exempt per RoHS 2002/95/EC Annex (5))

RoHS Compliant

6.0 x 3.5 x 1.4mm

FEATURES:

- Low in height (1.4 mm max.)
- Ceramic package assures high reliability
- Small size SMD, suitable for high density applications
- Superior heat-resistant glass sealing
- Wide operating temperature available

APPLICATIONS:

- Computers, Modems, Communication equipment
- Thin equipment
- Industrial wide temperature applications

STANDARD SPECIFICATIONS:

Parameters	Minimum	Typical	Maximum	Units	Notes
Frequency Range	8.000	-----	50.000 (*)	MHz	Fundamental
Operation mode	8.000	-----	39.999999	MHz	Fundamental AT-cut (Standard)
	40.000	-----	80.000	MHz	3rd OT AT-cut (Standard)
	40.000	-----	50.000	MHz	Fundamental AT-cut (See options)
Operating Temperature	-10	-----	+60	ºC	See options
Storage Temperature	-40	-----	+90	ºC	
Frequency Tolerance @+25°C	-50	-----	+50	ppm	See options
Frequency Stability over the Operating Temperature (ref. to +25°C)	-50	-----	+50	ppm	See options
Equivalent series resistance	See table 1 below			Ω	-----
Shunt capacitance (C0)	-----	-----	7	pF	-----
Load capacitance (CL)	-----	18	-----	pF	See options
Drive Level	-----	10	100	µW	
Aging@25°C±3°C	-----	-----	±5	ppm	First year
Insulation Resistance	500	-----	-----	MΩ	@ 100Vdc

(*) Frequency above 40MHz based on availability. Please contact ABRACON

Table 1

Frequency (MHz)	ESR(Ω) max.	Operation Mode
8.000 – 9.999	**100**	**Fundamental**
10.000 – 15.999	**60**	**Fundamental**
16.000 – 50.000	**50**	**Fundamental**
40.000 – 80.000	**70**	**3rd Overtone**

OPTIONS AND PART IDENTIFICATION: (left blank if standard)

ABM7-[ ]MHz -[ ]-[ ]-[ ]-[ ]-[ ]-[ ]-[ ]

Frequency in MHz
e.g. 14.31818MHz
14.31818MHz
26.000MHz

Load Capacitance (pF)
Please specify CL in pF or S for series (8 to 33pF)
Please contact ABRACON for other values

Custom ESR if other than standard
R□
□: Specify a value in Ω
(e.g.: R40)

Operating Temp.
- E: 0°C ~ +70°C
- B: -20°C ~ +70°C
- C: -30°C ~ +70°C
- N: -30°C ~ +85°C
- D: -40°C ~ +85°C
- J(***): -40°C ~ +105°C
- K(***): -40°C ~ +125°C
- L(***):-55°C to +125°C

Freq. Tolerance
- 1: ± 10 ppm
- 7: ± 15 ppm
- 2: ± 20 ppm
- 3: ± 25 ppm
- 4: ± 30 ppm

Freq. Stability
- U: ± 10 ppm(*)
- G: ± 15 ppm(**)
- X: ± 20 ppm
- W: ± 25 ppm
- Y: ± 30 ppm
- H: ± 35 ppm
- Q: ± 100 ppm

(***) ±100 ppm **only**

Mode
F: Fund AT for >40MHz

Packaging
- Blank: Bulk
- T: 1k or 2kpcs/reel
- T2: 250pcs/reel

(*) -10°C to 60°C only.
(**) Contact ABRACON for availability for -40°C to +85°C

ABRACON IS ISO9001:2008 CERTIFIED

ABRACON CORPORATION

Visit www.abracon.com for Terms & Conditions of Sale **Revised: 12.13.10**
30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА

CERAMIC SMD MICRO MINIATURE MICROPROCESSOR CRYSTAL

ABM7

6.0 x 3.5 x 1.4mm

OUTLINE DRAWING:







Note: Due to the availability of raw materials, this part may be manufactured with the chamfer on pin 1. Be advised that this does not affect the electrical characteristics of the crystal in any way.

Dimensions: inch (mm)

TAPE & REEL:

T: 1000pcs/reel or 2000pcs/reel

T2: 250pcs/reel



Dimensions: mm

REFLOW PROFILE:



ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com