

AZ850

MICROMINIATURE POLARIZED RELAY

FEATURES

- Microminiature size: Height: .197 inches (5 mm); Length: .551 inches (14 mm); Width: .354 inches (9 mm)
- High sensitivity, 79 mW pickup
- Monostable and bistable (latching) single coil and two coil versions available
- Meets FCC Part 68.302 1500 V lightning surge
- DIP terminal layout, fits 10 pin IC socket
- Epoxy sealed for automatic wave soldering and cleaning
- UL file E43203, CSA file 73363



CONTACTS

Arrangement	DPDT (2 Form C) Bifurcated crossbar contacts
Ratings	Resistive load: Max. switched power: 30 W or 62.5 VA Max. switched current: 1 A Max. switched voltage: 220 VDC or 250 VAC Max. carry current: 2 A
Rated Load UL/CSA	1 A at 30 VDC 0.5 A at 125 VAC
Material	Silver palladium; gold clad
Resistance	< 50 milliohms initially

COIL (Polarized)

Power At Pickup Voltage (typical)	Single side stable: 79–142 mW Bistable (latching) single coil: 56–84 mW Bistable (latching) two coil: 113–169 mW
Max. Continuous Dissipation	875 mW at 20°C (68°F) ambient
Temperature Rise	18°C (32°F) at nominal coil voltage
Temperature	Max. 105°C (221°F)

NOTES

1. All values at 20°C (68°F).
2. Relay has fixed coil polarity.
3. Relay may pull in with less than "Must Operate" value.
4. Relay adjustment may be affected if undue pressure is exerted on relay case.
5. For complete isolation between the relay's magnetic fields, it is recommended that a .197" (5.0 mm) space be provided between adjacent relays.
6. Specifications subject to change without notice.

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1 x 10 ⁸ 2 x 10 ⁵ at 1 A, 30 VDC 1 x 10 ⁵ at 0.5 A, 125VAC
Operate Time (typical)	2 ms at nominal coil voltage
Release Time (typical)	1 ms at nominal coil voltage (with no coil suppression)
Set Time (bistable versions)	2 ms at nominal coil voltage (typical)
Reset Time (bistable versions)	2 ms at nominal coil voltage (typical)
Dropout	Greater than 10% of nominal coil voltage
Capacitance	Contact to contact: 0.4 pF Contact set to contact set: 0.2 pF Contact to coil: 0.9 pF
Dielectric Strength (at sea level)	1000 Vrms between contact sets 1000 Vrms across contacts 1250 Vrms contact to coil Meets FCC part 68.302 1500 V lightning surge
Insulation Resistance	1000 megohms min. at 25°C, 500 VDC, 50% RH
Ambient Temperature Operating Storage	At nominal coil voltage -40°C (-40°F) to 70°C (158°F) -40°C (-40°F) to 105°C (221°F)
Vibration	.130" DA at 10–55 Hz
Shock	50 g
Enclosure	LCP
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	250°C (482°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	1.5 grams

ZETTLER electronics

Logistic Design (UK) Limited. Unit 3, Eagle Centre Way, Luton LU4 9US www.zettlerrelay.com sales@zettlerrelay.com
Telephone +44 (0) 1582 599 600 Fax +44 (0) 1582 599 700

AZ850

RELAY ORDERING DATA

SINGLE SIDE STABLE					ORDER NUMBER
COIL SPECIFICATIONS					
Nominal Coil VDC	Max. Continuous VDC	Coil Resistance ± 10%	Must Operate VDC		
3	7.5	64.3	2.1	AZ850-3	
4.5	11.25	145.2	3.15	AZ850-4.5	
5	12.5	178	3.5	AZ850-5	
6	15.0	257	4.2	AZ850-6	
9	22.5	579	6.3	AZ850-9	
12	30.0	1,028	8.4	AZ850-12	
24	48.0	2,880	16.8	AZ850-24	
BISTABLE (LATCHING) SINGLE COIL					
COIL SPECIFICATIONS				ORDER NUMBER	
Nominal Coil VDC	Max. Continuous VDC	Coil Resistance ± 10%	Must Operate VDC		
3	8.7	90	2.1	AZ850P1-3	
4.5	13.0	203	3.2	AZ850P1-4.5	
5	14.5	250	3.5	AZ850P1-5	
6	17.4	360	4.2	AZ850P1-6	
9	26.1	810	6.3	AZ850P1-9	
12	34.8	1440	8.4	AZ850P1-12	
24	57.6	3840	16.8	AZ850P1-24	
BISTABLE (LATCHING) TWO COIL					
COIL SPECIFICATIONS				ORDER NUMBER	
Nominal Coil VDC	Max. Continuous VDC	Coil Resistance ± 10%			Must Operate VDC
		Coil I	Coil II		
3	6.0	45	45	AZ850P2-3	
4.5	13.0	102	102	AZ850P2-4.5	
5	10.0	125	125	AZ850P2-5	
6	12.0	180	180	AZ850P2-6	
9	18.0	405	405	AZ850P2-9	
12	24	720	720	AZ850P2-12	
24	40	1,920	1,920	AZ850P2-24	

MECHANICAL DATA

		PC BOARD LAYOUT
WIRING DIAGRAMS SINGLE SIDE STABLE DEENERGIZED OR RESET CONDITION Watch for polarity BISTABLE (LATCHING) TWO COIL RESET CONDITION Watch for polarity VIEWED TOWARDS TERMINALS		

Dimensions in inches with metric equivalents in parentheses. Tolerance: ± 0.010 "

ZETTLER electronics

Logistic Design (UK) Limited. Unit 3, Eagle Centre Way, Luton LU4 9US www.zettlerrelay.com sales@zettlerrelay.com
Telephone +44 (0) 1582 599 600 Fax +44 (0) 1582 599 700

1999-10-27