

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C201809	2020/11/20	Vicky	△B X3
C	C210237	2021/03/29	Ruru	△C X2
D	C230014	2022/12/30	Ruru	△D X2




△B MSDPXXMR-SDPFR-SBXXX

XX: No. Of Pin

XXX: 0.5~99Meters
A05: 0.5 Meter
001: 1 Meter
002: 2 Meters
:
099: 99 Meters






Note: △B △C
* RoHS Compliant
* QC Important dimension
* C1
△D Waterproof rate: IP68, mated 1m/24h
IP69K, mated
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
Nut: Thermoplastic, Black
Outer mold: Thermoplastic, Black
* C2
△D Waterproof rate: IP68, mated 1m/24h
IP69K, mated
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
O-Ring: Rubber, Green
Nut: Thermoplastic, Black
Outer mold: Thermoplastic, Black
* Cable: UL20549, 22#*4C, OD=4.0mm, PUR Jacket, Black
* Cable length tolerance: 0.5M < L ≤ 1M: +60/-0 mm
1M < L ≤ 3M: +120/-0 mm
3M < L ≤ 5M: +160/-0 mm
5M < L ≤ 10M: ±100 mm
10M < L ≤ 20M: ±200 mm
20M < L ≤ 30M: ±300 mm
30M < L ≤ 99M: ±500 mm


Pin Out		
5	--	
4	Black	黑
3	Blue	藍
2	White	白
1	Brown	棕
Pin #	Wire	

C2



4P

C1



4P

Pin Assignments Front View

UNIT: mm

TOLERANCE

±0.5 mm

TITLE: ACC, SEN, D Code, DB-ENDED MF △C

SCALE: 1:1 | SIZE: A4 | SHEET: 1 OF 1

REV.: D | WC-REV.: A.5 | QC: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Ruru	2018-12-12
DWG NO: △B MSDPXXMR-SDPFR-SBXXX	CHECKED BY: Rita	DATE: 2018-12-12
CUSTOMER: ALTW	APPROVED BY: Max	DATE: 2018-12-12

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА