Technical Data
Data Sheet N2749, REV.-

S4D02120T
1200V SIC POWER SCHOTTKY RECTIFIERS

SOD-123FL

Features

- 175°C T_J operation
- Ultra-low switching loss
- Switching speeds independent of operating temperature
- Low total conduction losses
- High forward surge current capability
- High package isolation voltage
- Terminals finish: 100% Pure Tin
- "-A" is an AEC-Q101 qualified device
- Pb − Free Device
- All SMC parts are traceable to the wafer lot
- Additional electrical and life testing can be performed upon request

Circuit Diagram

Description

This 1200V 2A diode is high voltage Schottky rectifier that has very low total conduction losses and very stable switching characteristics over temperature extremes. The S4D02120T is ideal for energy sensitive, high frequency applications in challenging environments.

Applications

- Alternative energy inverters
- Power Factor Correction (PFC)
- Free-Wheeling diodes
- Switching supply output rectification
- Reverse polarity protection

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА

Technical Data
Data Sheet N2749, REV.-

RoHS Pb

Maximum Ratings@T_A=25°C unless otherwise specified

Characteristics	Symbol	Condition	Max.	Units
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_{DC}	-	1200	V
Average Rectified Forward Current	$I_{F(AV)1}$	Tc=25°C	5	A
	$I_{F(AV)2}$	Tc=145°C	2	A
Repetitive Peak Forward Surge Current	I_{FRM1}	10ms, Half Sine pulse, Tc =25°C	18	A
	I_{FRM2}	10ms, Half Sine pulse, Tc =110°C	12	A
Peak One Cycle Non-Repetitive Surge Current	I_{FSM1}	10ms, Half Sine pulse, Tc =25°C	10	A
	I_{FSM2}	10ms, Half Sine pulse, Tc =110°C	8	A
Power Dissipation	P_{tot1}	Tc =25℃	15	W
	P_{tot2}	Tc =110℃	6.5	W

Electrical Characteristics@T_A=25°C unless otherwise specified

Characteristics	Symbol	Condition	Typ.	Max.	Units
Forward Voltage Drop*	V_{F1}	@ 2A, Pulse, T_J = 25 °C	1.4	1.8	V
	V_{F2}	@ 2A, Pulse, T_J = 175 °C	2.0	2.5	V
Reverse Current*	I_{R1}	@V_R = rated V_R T_J = 25 °C	1	10	uA
	I_{R2}	@V_R = rated V_R T_J = 175 °C	2	40	uA
Junction Capacitance	C_T	VR=0V, Tj=25℃,f=1MHz	160	-	pF
Reverse Recovery Charge	Q_c	I_F = 2A, di/dt = 200A/μs V_R = 800 V, T_J =25°C	12.33	-	nC
Capacitance Stored Energy	E_C	V_R = 800 V, T_J =25°C	6.33	-	μJ

* Pulse width < 300 μs, duty cycle < 2%

Technical Data
Data Sheet N2749, REV.-

Thermal-Mechanical Specifications:

Characteristics	Symbol	S4D02120T	Units
Junction Temperature	T_J	-55 to +175	°C
Storage Temperature	T_{stg}	-55 to +175	°C
Typical Thermal Resistance Junction to Case	R_{qJC}	10	°C/W

Marking Diagram

Where XXXX is YYWWL

S = Device Type
12 = Reverse Voltage (1200V)
2 = Forward Current (2A)
T = Package type
YY = Year
WW = Week
L = Lot Number

Cautions: Molding resin
Epoxy resin UL:94V-0

Ordering Information

Device	Package	Shipping
S4D02120T	SOD-123FL	3000pcs / reel

For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.

Ratings and Characteristics Curves



Fig.1-Typical Forward Voltage Characteristics



Fig.2-Typical Reverse Characteristics



Fig.3-Capacitance vs. Reverse Voltage



Fig.4-Total Capacitance Charge vs. Reverse Voltage



Fig.5-Capacitance Stored Energy



Fig.6-Power Derating



Fig.7-Current Derating

Technical Data
Data Sheet N2749, REV.-

Carrier Tape & Reel Specification SOD-123FL



项目	规格(mm)	允差(mm)	项目	规格(mm)	允差(mm)
W	8.00	+0.30/-0.10	A0	2.05	±0.10
E1	1.75	±0.10	B0	3.95	±0.10
F	3.50	±0.05	K0	1.45	±0.10
D0	1.50	+0.1/-0.0	T	0.23	±0.02
D1	1.00	+0.25/-0.0	10*P0	40.00	±0.20
P0	4.00	±0.10	α1	4°max	
P1	4.00	±0.10	β1	8°max	
P2	2.00	±0.05	$B1_{max}$	4.35	
			$E2_{min}$	6.25	

Mechanical Dimensions SOD-123FL



Technical Data
Data Sheet N2749, REV.-

DISCLAIMER:
1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment , and safety equipment) , safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement .
3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..