IXYS
INTEGRATED CIRCUITS DIVISION



CPC1916
Single-Pole, Normally Open OptoMOS® Power SIP Relay

Parameter	Rating	Units
Blocking Voltage	100	V_P
Load Current	2.5	A_{rms} / A_{DC}
On-Resistance (max)	0.34	Ω

Features

- Handle Load Currents Up to $2.5A_{DC}/A_{rms}$
- $2500V_{rms}$ Input/Output Isolation
- Power SIP Package
- High Reliability
- No Moving Parts
- Low Drive Power Requirements
- Arc-Free With No Snubbing Circuits
- No EMI/RFI Generation
- Flammability Rating UL 94 V-0

Applications

- Industrial Controls
- Motor Control
- Robotics
- Medical Equipment—Patient/Equipment Isolation
- Instrumentation
- Multiplexers
- Data Acquisition
- Electronic Switching
- I/O Subsystems
- Meters (Watt-Hour, Water, Gas)
- IC Equipment
- Home Appliances

Description

IXYS Integrated Circuits brings OptoMOS® technology, reliability, and compact size to a new family of high-power, solid state relays. As part of that family, the CPC1916 is a single-pole, normally open (1-Form-A) solid state relay.

The CPC1916 employs optically coupled MOSFET technology to provide $2500V_{rms}$ of input to output isolation. The optically coupled outputs, that use patented OptoMOS architecture, are controlled by a highly efficient infrared LED. The combination of low on-resistance and high load-current handling capabilities makes the relay suitable for a variety of high-performance switching applications.

Approvals

- UL 508 Certified Component: File E69938

Ordering Information

Part #	Description
CPC1916Y	4-Pin (8-Pin Body) Power SIP Package (25 per tube)

Pin Configuration



Switching Characteristics of Normally Open Devices



Pb RoHS e3

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА

Absolute Maximum Ratings @ 25ºC

Parameter	Ratings	Units
Blocking Voltage	100	V_P
Reverse Input Voltage	5	V
Input control Current	50	mA
Peak (10ms)	1	A
Input Power Dissipation [1]	150	mW
Total Power Dissipation [2]	2400	mW
Isolation Voltage, Input to Output	2500	V_{rms}
Operational Temperature	-40 to +85	°C
Storage Temperature	-40 to +125	°C

[1] Derate linearly 1.33 mW / ºC
[2] Derate linearly 20 mW / ºC

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at conditions beyond those indicated in the operational sections of this data sheet is not implied.

Typical values are characteristic of the device at +25°C, and are the result of engineering evaluations. They are provided for information purposes only, and are not part of the manufacturing testing requirements.

Electrical Characteristics @ 25ºC

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Output Characteristics						
Load Current, Continuous	Free air	I_L	-	-	2.5	A_{rms} / A_{DC}
Peak Load Current	t ≤ 10ms	I_{LPK}	-	-	±6	A_P
On-Resistance [1]	I_L=1A	R_{ON}	-	-	0.34	Ω
Off-State Leakage Current	V_L=100V_P	I_{LEAK}	-	-	1	µA
Switching Speeds						
Turn-On	I_F=10mA, V_L=10V	t_{on}	-	-	5	ms
Turn-Off		t_{off}	-	-	3	
Input Characteristics						
Input Control Current to Activate	I_L=1A	I_F	-	3.3	10	mA
Input Control Current to Deactivate	-	I_F	0.3	-	-	mA
Input Voltage Drop	I_F=10mA	V_F	0.9	1.35	1.56	V
Reverse Input Current	V_R=5V	I_R	-	-	10	µA
Common Characteristics						
Capacitance, Input/Output	V_{IO}=0V, f=1MHz	C_{IO}	-	2	-	pF

[1] Measurement taken within 1 second of on-time.

Thermal Characteristics

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Thermal Impedance (junction to case)	-	$R_{\theta JC}$	-	1.5	-	°C/W

PERFORMANCE DATA*

Typical LED Forward Voltage Drop
(N=50, I_F=10mA, T_A=25°C)



Typical Turn-On Time
(N=50, I_F=10mA, I_L=5mA$_{DC}$, T_A=25°C)



Typical Turn-Off Time
(N=50, I_F=10mA, I_L=5mA$_{DC}$, T_A=25°C)



Typical On-Resistance Distribution
(N=50, I_F=10mA, I_L=1.0A$_{DC}$, T_A=25°C)



Typical Blocking Voltage Distribution
(N=50, T_A=25°C)



Typical LED Forward Voltage Drop
vs. Temperature



Typical Turn-On Time
vs. LED Forward Current
(I_L=100mA$_{DC}$)



Typical Turn-Off Time
vs. LED Forward Current
(I_L=100mA$_{DC}$)



Typical I_F for Switch Operation
vs. Temperature
(I_L=100mA$_{DC}$)



Typical Turn-On Time vs. Temperature
(I_L=100mA$_{DC}$)



Typical Turn-Off Time vs. Temperature
(I_L=100mA$_{DC}$)



*Unless otherwise noted, data presented in these graphs is typical of device operation at 25°C.
For guaranteed parameters not indicated in the written specifications, please contact our application department.

PERFORMANCE DATA*

Typical On-Resistance vs. Temperature (I_F=10mA, I_L=1.0A_{DC})



Typical Load Current vs. Load Voltage (I_F=10mA, T_A=25ºC)



Maximum Load Current vs. Temperature



Typical Blocking Voltage vs. Temperature



Typical Leakage vs. Temperature at Measured across Pins 3 & 4 (V_L=100V)



Energy Rating Curve (Free Air, No Heat Sink)



*Unless otherwise noted, data presented in these graphs is typical of device operation at 25ºC.
For guaranteed parameters not indicated in the written specifications, please contact our application department.

Manufacturing Information

Moisture Sensitivity

All plastic encapsulated semiconductor packages are susceptible to moisture ingression. IXYS Integrated Circuits classifies its plastic encapsulated devices for moisture sensitivity according to the latest version of the joint industry standard, **IPC/JEDEC J-STD-020**, in force at the time of product evaluation. We test all of our products to the maximum conditions set forth in the standard, and guarantee proper operation of our devices when handled according to the limitations and information in that standard as well as to any limitations set forth in the information or standards referenced below.

Failure to adhere to the warnings or limitations as established by the listed specifications could result in reduced product performance, reduction of operable life, and/or reduction of overall reliability.

This product carries a Moisture Sensitivity Level (MSL) classification as shown below, and should be handled according to the requirements of the latest version of the joint industry standard **IPC/JEDEC J-STD-033**.

Device	Moisture Sensitivity Level (MSL) Classification
CPC1916Y	MSL 1

ESD Sensitivity

This product is **ESD Sensitive**, and should be handled according to the industry standard **JESD-625**.

Soldering Profile

Provided in the table below is the Classification Temperature (T_C) of this product and the maximum dwell time the body temperature of this device may be (T_C - 5)ºC or greater. The classification temperature sets the Maximum Body Temperature allowed for this device during lead-free reflow processes. For through-hole devices, and any other processes, the guidelines of **J-STD-020** must be observed.

Device	Classification Temperature (T_c)	Dwell Time (t_p)	Max Reflow Cycles
CPC1916Y	245ºC	30 seconds	1

Board Wash

IXYS Integrated Circuits recommends the use of no-clean flux formulations. Board washing to reduce or remove flux residue following the solder reflow process is acceptable provided proper precautions are taken to prevent damage to the device. These precautions include, but are not limited to: using a low pressure wash and providing a follow up bake cycle sufficient to remove any moisture trapped within the device due to the washing process. Due to the variability of the wash parameters used to clean the board, determination of the bake temperature and duration necessary to remove the moisture trapped within the package is the responsibility of the user (assembler). Cleaning or drying methods that employ ultrasonic energy may damage the device and should not be used. Additionally, the device must not be exposed to flux or solvents that are Chlorine- or Fluorine-based.

MECHANICAL DIMENSIONS

CPC1916Y



PCB Hole Pattern



Note: Pin-to-pin tolerances are non-cumulative.

Dimensions
mm
(inches)

For additional information please visit our website at: www.ixysic.com

IXYS Integrated Circuits makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in IXYS Integrated Circuits' Standard Terms and Conditions of Sale, IXYS Integrated Circuits assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of IXYS Integrated Circuits' product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. IXYS Integrated Circuits reserves the right to discontinue or make changes to its products at any time without notice.

Specification: DS-CPC1916-R07
©Copyright 2018, IXYS Integrated Circuits
OptoMOS® is a registered trademark of IXYS Integrated Circuits
All rights reserved. Printed in USA.
6/19/2018