





REV.	DATE	DESCRIPTION
NC	06/07/99	INITIAL RELEASE
A	03/20/07	UPDATE DRAWING FORMAT, ADD BODY X-SEC.



RECOMMENDED
CABLE STRIPPING DIM'S



8					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020”	APPROVALS		DATE		Amphenol Connex							
7						DRAWN	G.R.S.	03/20/07									
6						CHECKED											
5						ISSUED				PART DESCRIPTION TNC CRIMP PLUG (RG-178B/U, 196A/U CABLE)							
4	FERRULE	COPPER	NICKEL	1		SHEET	1 OF 1										
3	CONTACT PIN	PHOS. BRONZE	GOLD	1	DO NOT SCALE DRAWING	C:/122/122429.DWG		DWG. NO.		122429.DWG		REV. A		SIZE A		SCALE NA	
2	INSULATOR	DELTRIN	NATURAL	1													
1	BODY	BRASS	NICKEL	1													
	DESCRIPTION	MATERIAL	FINISH	QTY													