Dual 1 Form A Solid State Relay



Features

- Dual Channel (LH1510)
- Current Limit Protection
- Isolation Test Voltage 5300 V_{RMS}
- Typical R_{ON} 10 Ω
- Load Voltage 200 V
- Load Current 120 mA
- High Surge Capability
- Clean Bounce Free Switching
- Low Power Consumption
- SMD Lead Available on Tape and Reel
- Lead-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

Agency Approvals

- UL1577, File No. E52744 System Code H or J, Double Protection
- CSA - Certification 093751
- BSI/BABT Cert. No. 7980
- DIN EN 60747-5-2 (VDE0884)
  DIN EN 60747-5-5 pending
- FIMKO Approval

Applications

General Telecom Switching
- On/off Hook Control
- Ring Delay
- Dial Pulse
- Ground Start
- Ground Fault Protection

Instrumentation

Industrial Controls

Description

The LH1522 dual 1 Form A relays are SPST normally open switches that can replace electromechanical relays in many applications. They are constructed using a GaAIAs LED for actuation control and an integrated monolithic die for the switch output. The die, fabricated in a high-voltage dielectrically isolated technology is comprised of a photodiode array, switch control circuitry, and MOSFET switches. In addition, the LH1522 SSRs employ current-limiting circuitry, enabling them to pass FCC 68.302 and other regulatory surge requirements when overvoltage protection is provided.

Order Information

Part	Remarks
LH1522AAC	Tubes, SMD-8
LH1522AACTR	Tape and Reel, SMD-8
LH1522AB	Tubes, DIP-8

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА

Absolute Maximum Ratings, T_{amb} = 25 °C

Stresses in excess of the absolute Maximum Ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute Maximum Ratings for extended periods of time can adversely affect reliability.

SSR

Parameter	Test condition	Symbol	Value	Unit
LED continuous forward current		I_F	50	mA
LED reverse voltage	$I_R \leq 10$ µA	V_R	8.0	V
DC or peak AC load voltage	$I_L \leq 50$ µA	V_L	200	V
Continuous DC load current , one pole operating		I_L	200	mA
Continuous DC load current , two poles operating		I_L	140	mA
Peak load current (single shot)	t = 100 ms	I_P	2)	
Ambient temperature range		T_{amb}	- 40 to + 85	°C
Storage temperature range		T_{stg}	- 40 to + 150	°C
Pin soldering temperature	t = 10 s max	T_{sld}	260	°C
Input/output isolation test voltage	t = 1.0 s, I_{ISO} = 10 µA max	V_{ISO}	5300	V_{RMS}
Pole-to-pole isolation voltage (S1 to S2) 1), (dry air, dust free, at sea level)			1600	V
Output power dissipation (continuous)		P_{diss}	600	mW

1) Breakdown occurs between the output pins external to the package.

2) Refer to Current Limit Performance Application Note 58 for a discussion on relay operation during transient currents.

Electrical Characteristics, T_{amb} = 25 °C

Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements.

Input

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
LED forward current, switch turn-on	I_L = 100 mA, t = 10 ms	I_{Fon}		1.0	2.0	mA
LED forward current, switch turn-off	V_L = ± 150 V	I_{Foff}	0.2	1.1		mA
LED forward voltage	I_F = 10 mA	V_F	1.15	1.26	1.45	V

Output

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
ON-resistance	I_F = 5.0 mA, I_L = 50 mA	R_{ON}	6.0	10	15	Ω
OFF-resistance	I_F = 0 mA, V_L = ± 100 V	R_{OFF}	0.5	5000		GΩ
Current limit	I_F = 5.0 mA, t = 5.0 ms, V_L = ± 5.0 V	I_{LMT}	300	360	460	mA
Off-state leakage current	I_F = 0 mA, V_L = ± 100 V	I_O		0.02	200	nA
	I_F = 0 mA, V_L = ± 200 V	I_O			1.0	µA

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Output capacitance	I_F = 0 mA, V_L = 1.0 V	C_O		60		pF
	I_F = 0 mA, V_L = 50 V	C_O		15		pF
Pole-to-pole capacitance (S1 to S2)	I_F = 5.0 mA			0.5		pF
Switch offset	I_F = 5.0 mA	V_{OS}		0.15		V

Transfer

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Capacitance (input-output)	V_{ISO} = 1.0 V	C_{IO}		1.1		pF
Turn-on time	I_F = 10.0 mA, I_L = 50 mA	t_{on}		1.0	2.0	ms
Turn-off time	I_F = 10.0 mA, I_L = 50 mA	t_{off}		0.7	2.0	ms

Typical Characteristics (Tamb = 25 °C unless otherwise specified)



Figure 1. Recommended Operating Conditions



Figure 3. LED Current for Switch Turn-on vs. Temperature



Figure 2. LED Voltage vs. Temperature



Figure 4. Current Limit vs. Temperature



Figure 5. LED Dropout Voltage vs. Temperature



Figure 6. ON-Resistance vs. Temperature



Figure 7. Variation in ON-Resistance vs. LED Current



Figure 8. Switch Capacitance vs. Applied Voltage



Figure 9. Insertion Loss vs. Frequency



Figure 10. Output Isolation



Figure 11. Leakage Current vs. Applied Voltage



Figure 12. Leakage Current vs. Applied Voltage at Elevated Temperatures



Figure 13. Switch Breakdown Voltage vs. Temperature



Figure 14. Switch Offset Voltage vs. Temperature



Figure 15. Switch Offset Voltage vs. LED Current



Figure 16. Turn-on Time vs. Temperature



Figure 17. Turn-off Time vs. Temperature



Figure 18. Turn-on Time vs. LED Current



Figure 19. Turn-off Time vs. LED Current

Package Dimensions in Inches (mm)



Package Dimensions in Inches (mm)



Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operatingsystems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design
and may do so without further notice.
Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423

Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.