


**Product number FCN15302_RONDA-WW**

Family	Ronda	FWHM	(simulated) 62
Type	Assembly	Efficiency	(simulated) 89 %
LED	CXA/B 15xx	cd/lm	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	19.8 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	["socket", "screw"]		
Status	Production ready		

**Product number FCN15303_RONDA-WWW**

Family	Ronda	FWHM	(simulated) 90
Type	Assembly	Efficiency	(simulated) 87 %
LED	CXA/B 15xx	cd/lm	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	19.8 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	["screw", "socket"]		
Status	Production ready		


**Product number FCN15314_RONDA-WAS**

Family	Ronda	FWHM	(simulated) Asymmetric
Type	Assembly	Efficiency	(simulated) 86 %
LED	CXA/B 15xx	cd/lm	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	25.42 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

Developed especially for wall washing applications at ~1:3 ratio assembly setup.

**Product number FCN15315_RONDA-WW**

Family	Ronda	FWHM	(simulated) 62
Type	Assembly	Efficiency	(simulated) 89 %
LED	CXA/B 15xx	cd/lm	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	19.8 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		


**Product number FCN15316_RONDA-WWW**

Family	Ronda	FWHM	(simulated) 90
Type	Assembly	Efficiency	(simulated) 87 %
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	19.8 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

**Product number FCN15357_RONDA-ZT45**

Family	Ronda	FWHM	(simulated) Asymmetric
Type	Assembly	Efficiency	(simulated) 87 %
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	20.66 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

Double asymmetric beam. Developed especially for wall washing, corridor and supermarket applications @ ~1:2 ratio aisle assemblies (aisle width = wall height).

**Product number FCN15366_RONDA-ZT45**

Family	Ronda	FWHM	(simulated) Asymmetric
Type	Assembly	Efficiency	(simulated) 87 %
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	20.66 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	""		
Status	Production ready		

Double asymmetric beam. Developed especially for wall washing, corridor and supermarket applications @ ~1:2 ratio aisle assemblies (aisle width = wall height).

**Product number FCN15499_RONDA-W**

Family	Ronda	FWHM	(simulated) 42
Type	Assembly	Efficiency	88 %
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	19.8 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	""		
Status	Production ready		

**Product number FCN15621_RONDA-W**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 19.8 mm
 Style Round
 Optic Material -
 Holder Material -
 Fastening ""
 Status Production ready

FWHM (simulated) 42
 Efficiency 88 %
 cd/lm -
 Gerber File Available


**Product number FN15731_RONDA-WAS-B**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 22.3 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ["socket"]
 Status Sample approved

FWHM (simulated) Asymmetric
 Efficiency (simulated) 86 %
 cd/lm (simulated) 1.100
 Gerber File Available

BJB 47.319.2xxx 50mm / Stucchi 8xxx/G2 50mm /
 Ideal chip lok jr compatible

Developed especially for wall washing applications at
 ~1:3 ratio assembly setup.

**Product number FN15733_RONDA-ZT45-B**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 15.4 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Sample approved

FWHM (simulated) Asymmetric
 Efficiency (simulated) 87 %
 cd/lm -
 Gerber File Available

BJB 47.319.2xxx 50mm / Stucchi 8xxx/G2 50mm /
 Ideal chip lok jr (50-20, 50-30) compatible

Double asymmetric beam. Developed especially for
 wall washing, corridor and supermarket applications
 @ ~1:2 ratio aisle assemblies (aisle width = wall
 height)

**Product number FN15734_RONDA-S-B**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 14.6 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Production ready

FWHM (simulated) 24
 Efficiency (simulated) 85 %
 cd/lm -
 Gerber File Available

BJB 47.319.2xxx 50mm / Stucchi 8xxx/G2 50mm /
 Ideal chip lok jr (50-20, 50-30) compatible

**Product number FN15735_RONDA-W-B**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 14.6 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Sample approved

FWHM (simulated) 42
 Efficiency (simulated) 88 %
 cd/lm -
 Gerber File Available


BJB 47.319.2xxx 50mm / Stucchi 8xxx/G2 50mm /
 Ideal chip lok jr (50-20, 50-30) compatible

**Product number FN15736_RONDA-WW-B**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 14.6 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Sample approved

FWHM (simulated) 62
 Efficiency (simulated) 89 %
 cd/lm -
 Gerber File Available


BJB 47.319.2xxx 50mm / Stucchi 8xxx/G2 50mm /
 Ideal chip lok jr (50-20, 50-30) compatible

**Product number FN15737_RONDA-WWW-B**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 14.6 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Sample approved

FWHM (simulated) 90
 Efficiency 87 %
 cd/lm -
 Gerber File Available


BJB 47.319.2xxx 50mm / Stucchi 8xxx/G2 50mm /
 Ideal chip lok jr (50-20, 50-30) compatible

**Product number FN15738_RONDA-REC-60-B**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 14.6 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Production ready

FWHM (simulated) 62+62
 Efficiency (simulated) 90 %
 cd/lm -
 Gerber File Available

BJB 47.319.2xxx 50mm / Stucchi 8xxx/G2 50mm /
 Ideal chip lok jr (50-20, 50-30) compatible

**Product number FCN15740_RONDA-REC-60**

Family	Ronda	FWHM	(simulated) 62+62
Type	Pack	Efficiency	(simulated) 89 %
LED	CXA/B 15xx	cd/Im	-
Color	Clear	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	""		
Status	Sample approved		

Product number FCN15209_RONDA-WAS

Family	Ronda	FWHM	Asymmetric degrees
Type	Assembly	Efficiency	91 %
LED	CXA/B 15xx	cd/Im	0.950
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	25.42 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	["snaps", "socket", "clips", "screw"]		
Status	Production ready		

Developed especially for wall washing applications at ~1:3 ratio assembly setup.

Product number FN15380_RONDA-WAS

Family	Ronda	FWHM	Asymmetric degrees
Type	Assembly	Efficiency	91 %
LED	CXA/B 15xx	cd/Im	0.950
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	22.3 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

Developed especially for wall washing applications at ~1:3 ratio assembly setup.

Product number FN15380_RONDA-WAS

Family	Ronda	FWHM	NULL degrees
Type	Assembly	Efficiency	(simulated) 86 %
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	22.3 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		


Developed especially for wall washing applications at ~1:3 ratio assembly setup.

**Product number FN15381_RONDA-WWW**


Family	Ronda	FWHM	NULL degrees
Type	Assembly	Efficiency	(simulated) 87 %
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

**Product number FN15381_RONDA-WWW**

Family	Ronda	FWHM	NULL degrees
Type	Assembly	Efficiency	(simulated) 87 %
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

**Product number FN15387_RONDA-WW**

Family	Ronda	FWHM	NULL degrees
Type	Assembly	Efficiency	(simulated) 89 %
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	""		
Status	Production ready		

**Product number FN15387_RONDA-WW**

Family	Ronda	FWHM	NULL degrees
Type	Assembly	Efficiency	(simulated) 89 %
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	""		
Status	Production ready		

**Product number FN15388_RONDA-ZT45**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 15.4 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Production ready

FWHM NULL degrees
 Efficiency (simulated) 87 %
 cd/lm -
 Gerber File Available

Double asymmetric beam. Developed especially for wall washing, corridor and supermarket applications @ ~1:2 ratio aisle assemblies (aisle width = wall height).

**Product number FN15388_RONDA-ZT45**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 15.4 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Production ready

FWHM NULL degrees
 Efficiency (simulated) 87 %
 cd/lm -
 Gerber File Available

Double asymmetric beam. Developed especially for wall washing, corridor and supermarket applications @ ~1:2 ratio aisle assemblies (aisle width = wall height).

**Product number FN15388_RONDA-ZT45**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 15.4 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Production ready


FWHM NULL degrees
 Efficiency 88 %
 cd/lm -
 Gerber File Available

Double asymmetric beam. Developed especially for wall washing, corridor and supermarket applications @ ~1:2 ratio aisle assemblies (aisle width = wall height).


**Product number FN15552_RONDA-W**

Family Ronda
 Type Assembly
 LED CXA/B 15xx
 Color White
 Diameter 69.9 mm
 Height 14.6 mm
 Style Round
 Optic Material PMMA
 Holder Material -
 Fastening ""
 Status Production ready


FWHM NULL degrees
 Efficiency 88 %
 cd/lm -
 Gerber File Available

**Product number FN15622_RONDA-REC-60**


Family	Ronda	FWHM	NULL degrees
Type	Pack	Efficiency	(simulated) 89 %
LED	CXA/B 15xx	cd/Im	-
Color	Clear	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

**Product number FN15679_RONDA-S**

Family	Ronda	FWHM	NULL degrees
Type	Assembly	Efficiency	-
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["screw"]		
Status	Production ready		

**Product number FN15679_RONDA-S**

Family	Ronda	FWHM	NULL degrees
Type	Assembly	Efficiency	-
LED	CXA/B 15xx	cd/Im	-
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["screw"]		
Status	Production ready		


**Product number FN15977_RONDA-WAS2**

Family	Ronda	FWHM	(simulated) Asymmetric
Type	Assembly	Efficiency	(simulated) 86 %
LED	CXA/B 15xx	cd/Im	(simulated) 1.100
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

Developed especially for wall washing applications at ~1:3 ratio assembly setup.

**Product number FN15993_RONDA-O**

Family	Ronda	FWHM	(simulated) 49+21
Type	Assembly	Efficiency	-
LED	CXA/B 15xx	cd/Im	(simulated) 2.140
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	17.28 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

**Product number FN15997_RONDA-O-B**

Family	Ronda	FWHM	(simulated) Asymmetric
Type	Assembly	Efficiency	-
LED	CXA/B 15xx	cd/Im	(simulated) 0.000
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	22.3 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		


BJB 47.319.2xxx 50mm / Stucchi 8xxx/G2 50mm / Ideal chip lok jr compatible

**Product number FN15998_RONDA-O-C**

Family	Ronda	FWHM	(simulated) Asymmetric
Type	Assembly	Efficiency	-
LED	CXA/B 15xx	cd/Im	(simulated) 0.000
Color	Clear	Gerber File	Available
Diameter	53.9 mm		
Height	16.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	["socket"]		
Status	Production ready		

**Product number FN15552_RONDA-W**

Family	Ronda	FWHM	63 degrees
Type	Assembly	Efficiency	91 %
LED	CXA/B 15xx	cd/Im	0.750
Color	White	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	""		
Status	Production ready		

**Product number FCN15739_RONDA-REC-60**

Family	Ronda	FWHM	63 degrees
Type	Pack	Efficiency	91 %
LED	CXA/B 15xx	cd/Im	0.750
Color	Clear	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	""		
Status	Sample approved		

**Product number FN15789_RONDA-REC-90**

Family	Ronda	FWHM	87 degrees
Type	Pack	Efficiency	91 %
LED	CXA/B 15xx	cd/Im	0.500
Color	Clear	Gerber File	Available
Diameter	69.9 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	""		
Status	Production ready		

Developed especially for office applications.

**Product number FCN15790_RONDA-REC-90**

Family	Ronda	FWHM	87 degrees
Type	Pack	Efficiency	91 %
LED	CXA/B 15xx	cd/Im	0.500
Color	Clear	Gerber File	Available
Diameter	69.9 mm		
Height	19.8 mm		
Style	Round		
Optic Material	-		
Holder Material	-		
Fastening	""		
Status	Sample approved		

Developed especially for office applications.

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.



PRODUCT DATASHEET

Ronda series

last update 20/12/2016

GENERAL INFORMATION


- Product series especially designed & optimized for CXA/B 15xx series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Lens material optical grade PMMA with high UV and temperature resistance. Allows use of high current and temperature conditions.

Please find more information about used material from below:

http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%20N%20UL94_Yellow%20Card.pdf

<http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%20N%20PLEXIGLAS-Datasheet.pdf>

Note! Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.



Front plate examples

Examples

D=49.9

Optic

D=69.9mm

Ledil-clamp / TE / Bender-wirth / other twist and lock socket types (holder A)


BJB and Stucchi 50mm (holder B)

LES size up to ~14mm, see compatibility www.ledil.com

Horizontal fix: M3 Nut + bolt


Rotation fix

Vertical fix: M3 Screw / Twist and lock / Snap


Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L		LEDiL Ledil Oy Salorankatu 10 FIN 24240 SALO Finland	
THIRD ANGLE PROJECTION: 		DRAWING TITLE RONDA-family	
This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.		SIZE A3	PART NUMBER -
		SCALE 1:1	WEIGHT - SHEET 1/3

See more details on page 2 and 3


Bottom view




Front view




Top view



Front panel location suggestion when seamless look needed




Detail A




Isometric view

* Ensure from 3d according specific optic version


Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L		LEDiL Ledil Oy Salorankatu 10 FIN 24240 SALO Finland	
THIRD ANGLE PROJECTION: 		DRAWING TITLE RONDA-family	
This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.		SIZE A3	PART NUMBER -
		SCALE 1:1	WEIGHT - SHEET 2/3

OPTIC/HOLDER ASSEMBLY


1. Place pin on the side of the lens into relative hole on the holder.



2. Press the lens under clips on the holder, ensuring both clips are fixed.



TYPICAL CONNECTOR ASSEMBLY (including solderless BENDER WIRTH as example)



1. Ensure correct relation of clamp and connector before screwing. Recommended torque 0.6Nm.

2. Assemble LED, BENDER&WIRTH connector and C13658_CLAMP-VER013-18 clamp on heatsink with M3 screw.


3. Attach optic by aligning the holes in the holder with hooks and turning the optic holder clockwise until it locks.

Bender&Wirth model 4xx Typ L1


Align clamp positioning pin with holes in the connector.

Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L		LEDiL Ledil Oy Salorankatu 10 FIN 24240 SALO Finland	
THIRD ANGLE PROJECTION: 		DRAWING TITLE RONDA-family	
This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.		SIZE A3	PART NUMBER -
		SCALE 1:1	WEIGHT - SHEET 3/3

Luminaire: FCN15357_RONDA-ZT45_CXA1520_SIMULATED_1000LM
Lamps: 1 x 1000lm




Luminaire: LEDiL Oy F15156_RONDA-WAS_(CXA1520)
Lamps: 1 x Cree_CXA1520_(CXA1520-30F-N4-N0H-0001)_982.885lm@250mA_P=8.57638W_I=0.250A




Luminaire: LEDiL Oy FCN15739_RONDA-REC-60_(CXA1520)

Lamps: 1 x Cree_CXA1520_(CXA1520-30F-N4-N0H-00001)+C14123_CLAMP-CXA15-


18_1003.41lm@250mA_P=8.57488W_I=0.25A



Luminaire: LEDiL Oy FCN15790_RONDA-REC-90 (CXA1520)
Lamps: 1 x Cree_CXA1520_(CXA1520-30F-N4-N0H-00001)+C14123_CLAMP-CXA15-
18_1003.41lm@250mA_P=8.57488W_I=0.25A




Luminaire: FCN15357_RONDA-ZT45_CXA1520_SIMULATED_1000LM
Lamps: 1 x 1000lm




Luminaire: LEDiL Oy F15156_RONDA-WAS_(CXA1520)

Lamps: 1 x Cree_CXA1520_(CXA1520-30F-N4-N0H-0001)_982.885lm@250mA_P=8.57638W_I=0.250A



Luminaire: LEDiL Oy FCN15739_RONDA-REC-60_(CXA1520)

Lamps: 1 x Cree_CXA1520_(CXA1520-30F-N4-N0H-00001)+C14123_CLAMP-CXA15-
18_1003.41lm@250mA_P=8.57488W_I=0.25A



Luminaire: LEDiL Oy FCN15790_RONDA-REC-90_(CXA1520)

Lamps: 1 x Cree_CXA1520_(CXA1520-30F-N4-N0H-00001)+C14123_CLAMP-CXA15-18_1003.41lm@250mA_P=8.57488W_I=0.25A

