

8500 Rocker Switches - Miniature

10A 250Vac Single & Double Pole



Key Features

- Miniature rocker switch
- Ratings up to 15A, 250Vac
- Single & double pole in same body size
- Illuminated & non-illuminated
- Matching indicators
- Industry standard panel cut-out
- Rotary and push button actuator options
- BioCote antimicrobial option
- Panel cut out: 19.3 x 12.9


Approvals and specifications

- 10(6)A 250Vac T125 IE4 (non lit types)
6(4)A 250Vac T125 5E4 (50,000 Operations)
10(6)A 250Vac T100 (lit types)
- UL CSA 15A Non Ind 250Vac, 14A Ind 250Vac, 10A 277Vac
UL CSA 250Vac 1/2hp, 125Vac 1/4hp
UL 105°C, (non lit) file E45221, CSA file LR10990
- BioCote antimicrobial additive. Independently verified to ISO22196:2007.
- 3mm contact gap.



Terminal	Function	Rocker	Body	Body Colour	Rocker Colour
H 4.8 x 0.8	 ON OFF Switches are ON when pressed over terminal 1	H Slotted for custom caps 	B Standard body with terminal barrier 	B Black	B Black
K 2.6 x 0.8 Right angle version of K terminal available on 8500 only	8500 ON - OFF Single pole (Uses terminals 1a & 2a)	R Semi-rotary (not lit) 	BC Body without terminal barrier 	R Red	R Red
L 2.6 x 0.8 Right angle version of K terminal available on 8500 only	8503 ON (lit) - OFF Single pole	D Paddle lever (not lit) 	BC Body without terminal barrier 	W White	W White
R 1.5 x 0.8 Right angle version of K terminal available on 8500 only	8550 ON - OFF Double pole	V Curved (not lit) 	BC Body without terminal barrier 		
T 1.0 x 0.8 Right angle version of K terminal available on 8500 only	8553 ON (lit) - OFF Double pole	V Curved (lit) 	BC Body without terminal barrier 		
T 1.0 x 0.8 Right angle version of K terminal available on 8500 only	8580 Available with H terminals only Indicator UL/CSA E63363	X Two colour (not lit) 	BC Body without terminal barrier 		
T 1.0 x 0.8 Right angle version of K terminal available on 8500 only	8580 Available with H terminals only Indicator UL/CSA E63363	A Softline lens 	BC Body without terminal barrier 		
T 1.0 x 0.8 Right angle version of K terminal available on 8500 only	8580 Available with H terminals only Indicator UL/CSA E63363	P Push button operation (8500 only) See drawing opposite	BC Body without terminal barrier 		

Dimensions



“B” body with barrier for H, T and K terminals



“BC” body w/o barrier primarily for L or R terminals (can be used for all terminals)



‘PO’ Actuator and body - push button function (8500 only)



Insert Colour	Lamp Voltage	Legend	Legend Colour	Options	Biocote
X Rocker Only	Blank	Blank	Blank	Finish Matt finish only.	B Biocote
R Red	2 125V Neon	076	B Black	Colour Call sales for custom colours. A full range is available for large orders.	
W White	3 250V Neon		W White	Legend printing Select from the examples or call sales for custom legends.	
Leave blank for other Rocker types	7 12V Filament			Lamp voltage Call sales for details of available voltages.	
	8 24V Filament			Protective cover L167 Snaps on to bodies with V or X style rockers and A lens. This reduces panel thickness by 0.8mm.	
					
				BioCote Antimicrobial Additive Moulded components have antimicrobial properties using BioCote silver ion technology.	

Examples



H8500VB
T8500VB ---



H8550VB
T8550VB



H8550HB ---
T8550HB ---



H8550XB ---
T8550XB ---



H8550RB Semi-rotary
A splash proofing option



H8500PO ---
Pushbutton option



H8553VB ---
T8553VB ---



H8580AB ---