




1. MATERIALS AND FINISHES:
BODY - BRASS, NICKEL PLATING
CONTACT - BRASS, GOLD PLATING
INSULATOR - PTFE, NATURAL
2. ELECTRICAL:
A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC-4 GHz
C. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS, MIN.
3. MECHANICAL:
A. DURABILITY: 500 CYCLES, MIN.
B. TEMPERATURE RANGE: -65°C TO 165°C
4. WHEN CRIMPING CONTACT PIN TO CABLE, CRIMP WITH AMP 227-944 (M22520/5-01) AND DIE SET 227-1221-09, CAVITY (M22520/5-09, CLOSURE 'B')
5. WHEN CRIMPING FERRULE TO CABLE, CRIMP WITH AMPHENOL 227-944 (M22520/5-01) AND DIE SET 227-1221-09 CAVITY (M22520/5-09, CLOSURE 'A')
6. PACKAGE THIS CONNECTOR IN BAG 999-225



REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A2	APPEARANCE WAS CHANGED\N/A	15-APR-03		
A3	BODY WAS CHANGED\N/A\06-30-05'	30-JUN-05		
B	SHELL WAS 31-1500-C\RD-DM06092201C	14-OCT-06		
H	SPRING WAS CHANGED\RD-DM09112701T1	17-MAR-10	47921	SH
J	UPDATE DESCRIPTION TO INCLUDE RD-316	13-OCT-22	16356	SH



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person, to anyone for any purpose is not to be regarded by implication or otherwise in licensing, granting right to permitting such holder or any other person to manufacture, use, or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE METRIC (INCHES) AND TOLERANCES ARE: $<0.5\text{mm} = \pm 0.05\text{mm}$ [$<0.020 = \pm 0.002$] $0.5 - 6\text{mm} = \pm 0.1\text{mm}$ [$0.020 - 0.236 = \pm 0.004$] $>6.00 - 30\text{mm} = \pm 0.2\text{mm}$ [$>0.236 - 1.181 = \pm 0.008$] $>30.00 - 120\text{mm} = \pm 0.3\text{mm}$ [$>1.181 - 4.725 = \pm 0.012$]			MATERIAL ENGR.1 Y. KOUSIDIS ENGR.2 JACK LIANG DATE 15-AUG-22			TITLE BNC PLUG MIL-CRIMP 23329, (FOR DOUBLE BRAIDED, RG-188U & RD-316			Amphenol RF					
THIRD ANGLE PROJ. 			REFERENCE			EAR#			SIZE B			DRAWING NO. 31-315-1005			REV J		
ANGLES = $\pm 1^\circ$			SHEET NO. 2 OF 2			SCALE: 3.0:1.0			ITEM NO. 31-315-1005								
									PART NO. 31-315-1005								