






LOC		DIST		REVISIONS						
				變更						
		P	LTR	DESCRIPTION		ECN		DATE	DWN	APVD
			D	再作成 (REDRAWN)		FJ00-0871-98		8 Jun 98	my	MS



寸法公差は±0.20
(TOLERANCE: ±0.20)
パネル取付穴
(RECOMENDED PANEL OPENING DIMENSION)

注記;

1. 使用端子型番は170359, 170360, 170361, 170362
2. 嵌合相手ハウジング型番は172167
3. 適用パネル厚 0.8~2.0mm
4. 取付穴打抜方向とハウジングの挿入方向は同じとする。
5. 表1参照

NOTE;

1. APPLICABLE CONT P/N: 170359, 170360, 170361, 170362
2. MATING HSG P/N: 172167
3. APPLICABLE PANEL THICKNESS: 0.8~2.0mm
4. HOUSING INSERTION INTO THE PANEL CUT-OUT MUST BE DONE IN THE SAME DIRECTION WITH PUNCH KNOCKING.
5. SEE TABLE 1

表 1 (TABLE 1)	
トレードマーク (TRADE MARK)	生産場所 (MANUFACTURING PLACES)
-AMP OR AMP	日本 (JAPAN)
-+AMP OR AMP	中国 (CHINA (PRC))

黒 (BLACK)	1-172159-9
青 (BLUE)	1- -6
緑 (GREEN)	1- -5
赤 (RED)	1- -2
自然色 (NATURAL)	172159-1
色 (COLOR)	型番 (P/N)
WIRE RANGE 配合電線断面積	INSULATION DIA 被覆外径

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		OWN M. Yamashita 8 Jun 98 CHK M. Shiro 15 Jun 98 APVD M. Shiro 15 Jun 98		NAME 名称 4極ミニユニバーサルメイトンロックキャップハウジング (UL94V-0) 4Pos MINI UNIVERSAL MATE-N-LOCK CONN. CAP HOUSING (UL94V-0)	
DIMENSIONS: 単位: 概 mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 一般公差 (GENERAL TOLERANCES) ±0.3	PRODUCT SPEC 製品規格 108-5138	INSTRUCTION SHEET 取扱い説明書 IS-105J	SIZE A3	CAGE CODE 00779
MATERIAL 材料 66ナイロン UL94V-0 (66NYLON UL94V-0)	FINISH 仕上 —	WEIGHT —	INSTRUCTION SHEET 取扱い説明書 IS-105J	DRAWING NO 番号 C-172159	
CUSTOMER DRAWING				RESTRICTED TO	
SCALE 尺度 2-1				SHEET 1 OF 1	