

Technical drawings of the cable assembly showing dimensions in inches and millimeters.

**Top View (Left):** Shows the overall dimensions of the cable assembly. The total length is 4.10 [1.162]. The length of the braided shield section is 12.40 [4.89]. The length of the outer jacket section is 3.00 [1.118]. The length of the inner jacket section is 2.24 [0.88].

**Top View (Right):** Shows the recommended cable stripping dimensions. The length of the stripped section is 2.50 [0.98].

**Side View (Left):** Shows the cross-sectional dimensions of the cable. The outer diameter is 4.50 [1.77]. The inner diameter of the braided shield is .40 [0.016]. The inner diameter of the inner jacket is .85 [0.033].

**Side View (Right):** Shows the cross-sectional dimensions of the cable. The outer diameter is .50 [0.020]. The inner diameter of the braided shield is .50 [0.020]. The inner diameter of the inner jacket is 2.20 [0.87].

**Bottom View (Left):** Shows the cross-sectional dimensions of the cable. The outer diameter is 6.10 [2.40]. The inner diameter of the braided shield is 2.20 [0.87]. The inner diameter of the inner jacket is 1.25 [0.049].

**Bottom View (Right):** Shows the cross-sectional dimensions of the cable. The outer diameter is 2.20 [0.87]. The inner diameter of the braided shield is 1.25 [0.049].

**Bottom View (Far Right):** Shows the cross-sectional dimensions of the cable. The outer diameter is 2.20 [0.87]. The inner diameter of the braided shield is 1.25 [0.049].

NOTE:

1. CONTACT PIN TO SOLDER

# Amphenol Connex