



Pushing Performance

# Han B Hood Top Entry HC 4 Pegs M25 black



|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 30 716 0426                                                                        |
| Specification      | Han B Hood Top Entry HC 4 Pegs M25 black                                              |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19307160426">https://b2b.harting.com/19307160426</a> |

## Identification

|                             |                   |
|-----------------------------|-------------------|
| Category                    | Hoods/Housings    |
| Series of hoods/housings    | Han® B            |
| Type of hood/housing        | Hood              |
| Description of hood/housing | Black             |
| Type                        | High construction |

## Version

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Locking type         | Double locking lever                              |
| Size                 | 16 B                                              |
| Version              | Top entry                                         |
| Cable entry          | 1x M25                                            |
| Field of application | Standard hoods/housings for industrial connectors |

## Technical characteristics

|                                        |                                                                    |
|----------------------------------------|--------------------------------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C                                                    |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67 in combination with special bulkhead mounted housings |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                                                      |

## Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast   |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 9005 (jet black) |



Pushing Performance

## Material properties

|                             |           |
|-----------------------------|-----------|
| RoHS                        | compliant |
| ELV status                  | compliant |
| China RoHS                  | e         |
| REACH Annex XVII substances | No        |
| REACH ANNEX XIV substances  | No        |
| REACH SVHC substances       | No        |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 222.2 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |