

Accessories - programming aids

UB-PROG2



Programming device

- For ultrasonic sensors series

UB300			
UB400	-12GM	-E4	
UB500	-18GM40	-E5	
UB1000	-18GM75	-I	-V15
UB2000	-30GM	-U	
UB4000	-F54		
UB6000			

... whose teach-in input is on pin 2.

- Simple TEACH-IN of the switching distances A1/A2 or the measuring window.
- Simple selection of the output function:
Window mode, normally open/normally closed function.
One switching distance, normally open/normally closed function.
Monitoring of the detection range.

UB-PROG3




Programming device

- For ultrasonic sensors series


UB500		-E01	
UB1000	-18GM75	-E23	
		-E6	-V15
		-E7	

... whose teach-in input is on pin 5.

- Simple TEACH-IN of the switching distances A1/A2 or the measuring window.
- Simple selection of the output function:
Window mode, normally open/normally closed function.
One switching distance, normally open/normally closed function.
Monitoring of the detection range.



The unit can be switched from the V15 cable connection socket and the V15 plug connection on the sensor for the TEACH-IN procedure.
The switching distances/measuring window and output function can be taught in using the A1 and A2 buttons.
The taught-in switching distances and functions are retained when the programming unit is removed and/or the power is switched off.



The unit can be switched from the V15 cable connection socket and the V15 plug connection on the sensor for the TEACH-IN procedure.
The switching distances/measuring window and output function can be taught in using the A1 and A2 buttons.
The taught-in switching distances and functions are retained when the programming unit is removed and/or the power is switched off.