

R6 SERIES ROCKER SWITCH


ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS




APPLICATIONS / MARKETS



Commercial Appliances



Industrial Controls




Floor Care Appliances



Instrumentation



Medical/Dental



Electrical Housewares

RoHS

SPECIFICATIONS

Electrical Rating: 10A 125VAC [UL, cUL]
6A 250VAC [UL, cUL]

Mechanical Life: 30,000 Cycles

Electrical Life: 10,000 Cycles

Contact Resistance: < 20mΩ (Initial)

Insulation Resistance: > 1,000MΩ at 500VDC

Dielectric Strength: > 1,500VAC for 1 Minute (Initial)

Operating Temperature: -20°C to 65°C

Storage Temperature: -30°C to 80°C

Panel Thickness: 0.75 - 3.00mm

FEATURES & BENEFITS

- Slim-line package design
- Maintained and momentary functions

PART NUMBER CONFIGURATOR

Series



R6

Function



A - SPST On - Off
B - SPST (On) - Off

Housing Color



BLK - Black
GRY - Grey

Actuator Color



BLK - Black
RED - Red
GRY - Grey

Marking



A - Dot
E - Blank
F - I/O Vertical

Termination



F - Faston

NOTES:

() denotes function is momentary

Specifications subject to change without notice 11.16.2021



E-SWITCH®



www.e-switch.com

800.867.2717


1

R6 SERIES ROCKER SWITCH


BODY DIMENSIONS




MARKING OPTIONS



A - DOT



E - BLANK



F - I/O VERTICAL



E-SWITCH®

www.e-switch.com

800.867.2717

2

ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS