



16A 12V DC
6A 14VT
6-10A 28V DC

FEATURES

* Watertight boot (R13-66A-29) is optional (refer page 72).

16A 12V DC, 6A 28V DC

16A 12V DC, 6A 28V DC

16A 12V DC, 10A 28V DC, 6A 14VT
for A, B, C, D, E, F, G, H, I, L

R13-66

X
Y

	X	Y
0.75-1.25	19.2±0.1	13.0±0.1
1.25-2.0	19.4±0.1	13.0±0.1
2.0-3.0	19.8±0.1	13.0±0.1

R13-66 8



	X	Y
0.75-1.5	19.4±0.1	13.0±0.1
1.5-2.5	19.8±0.1	13.0±0.1

ROCKER

A/B/BF/C/D/E/F
G/H/I



B, BF transparent



B6/B6F



A8/B8/B8F/C8/E8/F8



LP



FUNCTION

A
2P SPST

A 5
2P SPST

A 8
2P SPST

A P
2P SPST

B
3P SPST (NEON)

B F
3P SPST (NEON)

B 2
3P SPST (LED)

B 2 F
3P SPST (LED)

B 4
3P SPST (LED)

B 4 F
3P SPST (LED)

B 6
3P SPST (LED)

B 6 F
3P SPST (LED)

B 8
3P SPST (LED)

B 8 F
3P SPST (LED)

C
3P SPST

C P
3P SPST

C 8
3P SPST

D
3P SPST

D P
3P SPST

E
2P SPST

E 8
2P SPST

F
2P SPST

F 8
2P SPST

G
3P SPST

H
3P SPST

H P
3P SPST

I
3P SPST

I P
3P SPST

L
4P SPST (LED)

L F
4P DPST (LED)

L P
4P SPST (LED)

TERMINAL

0 2 .187" SQ

0 5 S0

AC/DEFI/NI

0 9 PC

AC/DEFI/NI

1 0 PC ANGLE

AC/DEFI/NI

1 2 S0

AC/DEFI/NI

