

MS-500シリーズ / SERIES

品番 PARTS No.	MS-500□ -B	MS-500□ -BC	MS-500□ -F	MS-500□ -MF	MS-500□ -B2	MS-500□ -B-PC	MS-500□ -B-RI	MS-500□ -B-VT
回路 CIRCUITS								
SPST (2P)	ON-OFF K	ON-OFF K	ON-OFF K	ON-OFF K	ON-OFF K	—	—	—
SPDT (3P)	ON-ON A	ON-ON A	ON-ON A	ON-ON A	ON-ON A	ON-ON A	ON-ON A	ON-ON A
	ON-(ON) B	ON-(ON) B	ON-(ON) B	ON-(ON) B	—	ON-(ON) B	ON-(ON) B	ON-(ON) B
	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C
	ON-OFF-(ON) D	ON-OFF-(ON) D	ON-OFF-(ON) D	ON-OFF-(ON) D	—	ON-OFF-(ON) D	ON-OFF-(ON) D	ON-OFF-(ON) D
	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E	—	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E
DPDT (6P)	ON-ON F	ON-ON F	ON-ON F	ON-ON F	ON-ON F	ON-ON F	ON-ON F	ON-ON F
	ON-(ON) G	ON-(ON) G	ON-(ON) G	ON-(ON) G	—	ON-(ON) G	ON-(ON) G	ON-(ON) G
	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H
	ON-OFF-(ON) I	ON-OFF-(ON) I	ON-OFF-(ON) I	ON-OFF-(ON) I	—	ON-OFF-(ON) I	ON-OFF-(ON) I	ON-OFF-(ON) I
	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J	—	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J
レバーカラー	シルバー	R(赤), B(黒), W(白) Y(黄), G(青)	シルバー	R(赤), B(黒), W(白) Y(黄), G(青)	シルバー	シルバー	シルバー	シルバー
端子形状	半田端子	半田端子	半田端子	半田端子	半田端子	PC端子	ライトアングル	バーチカル
COLOR	Chrome Plated Brass	Red, Black, White Yellow, Blue	Chrome Plated Brass	Red, Black, White Yellow, Blue	Chrome Plated Brass	Chrome Plated Brass	Chrome Plated Brass	Chrome Plated Brass
TERMINALS	Solder Terminal	Solder Terminal	Solder Terminal	Solder Terminal	Solder Terminal	P.C. Terminal	Right Angle Mounting	Vertical Mounting

MS-500シリーズ / SERIES

受注生産 / Only for large quantity order

品番 PARTS No.	MS-500□ -LL-S	MS-500□ -LL-P	MS-500□ -B-PCB	MS-500□ -B-PS	MS-500□ -CL	MS-500□ -L	MS-500□ -ML	MS-500□ -PL
回路 CIRCUITS								
SPST (2P)	ON-OFF K	ON-OFF K	—	—	ON-OFF K	ON-OFF K	ON-OFF K	ON-OFF K
SPDT (3P)	ON-ON A	ON-ON A	ON-ON A	ON-ON A	ON-ON A	ON-ON A	ON-ON A	ON-ON A
	—	—	ON-(ON) B	ON-(ON) B	ON-(ON) B	ON-(ON) B	ON-(ON) B	ON-(ON) B
	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C	ON-OFF-ON C
	—	—	ON-OFF-(ON) D	ON-OFF-(ON) D	ON-OFF-(ON) D	ON-OFF-(ON) D	ON-OFF-(ON) D	ON-OFF-(ON) D
	—	—	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E	(ON)-OFF-(ON) E
DPDT (6P)	ON-ON F	ON-ON F	ON-ON F	ON-ON F	ON-ON F	ON-ON F	ON-ON F	ON-ON F
	—	—	ON-(ON) G	ON-(ON) G	ON-(ON) G	ON-(ON) G	ON-(ON) G	ON-(ON) G
	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H	ON-OFF-ON H
	—	—	ON-OFF-(ON) I	ON-OFF-(ON) I	ON-OFF-(ON) I	ON-OFF-(ON) I	ON-OFF-(ON) I	ON-OFF-(ON) I
	—	—	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J	(ON)-OFF-(ON) J
レバーカラー	シルバー	シルバー	シルバー	シルバー	R(赤), B(黒), W(白) Y(黄), G(青)	シルバー	R(赤), B(黒), W(白)	R(赤), B(黒), W(白) Y(黄), G(青)
端子形状	半田端子	PC端子	PC端子	半田端子	半田端子	半田端子	半田端子	半田端子
COLOR	Chrome Plated Brass	Chrome Plated Brass	Chrome Plated Brass	Chrome Plated Brass	Red, Black, White Yellow, Blue	Chrome Plated Brass	Red, Black, Cream	Red, Black, White Yellow, Blue
TERMINALS	Solder Terminal	P.C. Terminal	P.C. Terminal	Solder Terminal	Solder Terminal	Solder Terminal	Solder Terminal	Solder Terminal

MS-500シリーズ／SERIES

ご注文の際は下記の例に準じてご用命下さい。

ORDERING INFORMATION

MS-500 A - MF - R
 1 2 3

1	回 路 CIRCUIT	スイッチ特性 SWITCHING FUNCTION	レバー振れ角度 Lever Travel Angle
K	SPST (2P)	ON-OFF	24°± 4°
A	SPDT (3P)	ON-ON	20°± 4°
B	SPDT (3P)	ON- (ON)	
C	SPDT (3P)	ON-OFF-ON	12°± 2°
D	SPDT (3P)	ON-OFF- (ON)	
E	SPDT (3P)	(ON) -OFF-(ON)	24°± 4°
F	DPDT (6P)	ON-ON	
G	DPDT (6P)	ON- (ON)	20°± 4°
H	DPDT (6P)	ON-OFF-ON	12°± 2°
I	DPDT (6P)	ON-OFF- (ON)	
J	DPDT (6P)	(ON) -OFF-(ON)	


注記／NOTE
(ON) =ノンロック／Momentary

2	操作形状	Shape of OperationPart
B	バット状レバー	Bat type Lever
BC	バット状レバー (塩ビキャップ付)	Bat type Lever with Color Cap
F	金属フラットレバー	Metal Flat Lever
MF	モールドフラットレバー	Mould FlatColor Lever
PL	プラスチックキャップレバー	Plastic Cap Color Lever
CL	カラーチップ付レバー	Lever with Color TipTop
L	金属ロングレバー	Metal Long Lever
LL	ロックレバー	Metal Lock Lever
ML	モールドロングレバー	Mould Long ColorLever
B2	バット状ショートレバー	Bat Type Short Lever


3	操作部色 又は端子形状	Top Color or Shape of Terminal
R	赤	Red
K	黒	Black
W	白	White
Y	黄	Yellow
U	青	Blue
S	半田端子	Solder Terminal
P/PC	P端子	PC Terminal
PCB	P端子ブラケットマウント付き	PC Terminal With Bracket mount
RI	ライトアングル	Right Angle Mounting Terminal
VT	バーチカル	Vertical Mounting Terminal
PS	半田端子防滴スイッチ	Splash Proof Type

電流容量	絶縁抵抗	絶縁耐圧	接触抵抗
RATING	INSULATION RESISTANCE	VOLTAGE BREAKDOWN	CONTACT RESISTANCE
6A.125V.AC	DC.500V 100MΩ以上 (MIN)	端子間 Between the teminals AC.1000V/分間 (Minute) 充電部と非充電部 Between the terminals and actuator AC.1500V/分間 (Minute)	20mΩ 以下 (MAX)


外形図／Dimensions




MS-500F-B




MS-500A-BC




MS-500A-F



MS-500A-MF



MS-500A-B2



MS-500F-B-PC


Technical drawing of a stepped shaft. The shaft has two sections: a smaller diameter section on the left and a larger diameter section on the right. The diameter of the smaller section is labeled $\Phi 2.4$. The diameter of the larger section is labeled $\Phi 6.2$. The length of the larger diameter section is labeled 6.4. The drawing shows the shaft in a side view with centerlines and dimension lines.

MS-500シリーズ／SERIES


受注生産／Only for large quantity order

外形図／Dimensions

MS-500□-LL-P




MS-500C-LL-P




MS-500F-LL-P

MS-500□-B-PCB




MS-500A-B-PCB

MS-500□-LL-S




MS-500A-LL-S

MS-500□-CL




MS-500F-CL

MS-500□-L




MS-500A-L

MS-500□-ML




MS-500F-ML

MS-500□-PL




MS-500A-PL

外形図／Dimensions




(3P) MS-500A-B-VT




(6P) MS-500F-B-VT

回路 CIRCUIT	レバー振れ角度 Lever Travel Angle
A	24° ± 4°
B	20° ± 4°
C・D・E	12° ± 2°
F	24° ± 4°
G	20° ± 4°
H・I・J	12° ± 2°


取付穴参考寸法
Mounting Hole




取付穴参考寸法
Mounting Hole



外形図／Dimensions




MS-500A-B-RI




MS-500F-B-RI

回路 CIRCUIT	レバー振れ角度 Lever Travel Angle
A	24° ± 4°
B	20° ± 4°
C・D・E	12° ± 2°
F	24° ± 4°
G	20° ± 4°
H・I・J	12° ± 2°

取付穴参考寸法 Mounting Hole




取付穴参考寸法 Mounting Hole



MS-500シリーズ／SERIES


防滴タイプ／Splash Proof Type

MS-500□-B-PS




MS-500A-B-PS


取付穴参考寸法
Mounting Hole



取付板厚
Panel Thickness



取付例
Mounting Example



注 記：本製品はパネルシールを目的としたスイッチであり、水中で使用するものではありません。

スイッチに水がかかった場合は、必ず水分を拭き取ってからご使用下さい。

NOTE : This switch is designed for sealing the panel and prevent a water leakage into the equipment, however not designed for the use in the water.

If the switch is covered with water, please be sure to wipe off the water before using.