





Electric Components > Products > Circular Connectors > Circular Connectors Power M 23 >
Power Connectors M 23 Panel Connector, Male Thread, Single Hole Mounted, Front Mounting, M 20 >
[Panel Connector, Single Hole Mounted, Front Mounting, Thread M 20 x 1,5 7.621.000.000](#)

Panel Connector, Single Hole Mounted, Front Mounting, Thread M 20 x 1,5 7.621.000.000

characteristic of connection	Crimp
Contact material	Copper-Zinc alloy
Contact surface	Nickel plated, Gold plated (0,25µm) Nickel
for cables mm	7 – 17 mm
Housing material	Copper-Zinc alloy Die Casting
Housing surface	other surface upon request Nickel plated brass
Inserts	PBT Fire protection class V-0 Thermoplastic Polyamid PA 6 (Nylon 6/6)
Male thread	M 20 x 1,5
Mating cycles	> 1000
Operating-Temperature	-40 – 125 °C
Protection	IP 67 / IP 69 K per EN 60 629 (connected)
Seal ring	Buna-N standard Viton (FPM)
Type	Thread M 20 x 1,5

Optional: Gasket, M 20 x 1,5, Locking Nut

Thread M 20 x 1,5



Certificates



RoHS VDE CSA



EAC