OptiMOS™3 Power-Transistor

Features

- Ideal for high frequency switching and sync. rec.
- Optimized technology for DC/DC converters
- Excellent gate charge x $R_{DS(on)}$ product (FOM)
- N-channel, normal level
- 100% avalanche tested
- Pb-free plating; RoHS compliant
- Qualified according to JEDEC[1] for target applications

Product Summary

V_{DS}	60	V
$R_{DS(on),max}$	5.7	mΩ
I_D	60	A

Halogen-Free

RoHS

Type	IPA057N06N3 G
Package	PG-TO220-3-31
Marking	057N06N



Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	T_C=25 °C[2]	60	A
		T_C=100 °C	43	
Pulsed drain current[3]	$I_{D,pulse}$	T_C=25 °C	240	
Avalanche energy, single pulse[4]	E_{AS}	I_D=80 A, R_{GS}=25 Ω	77	mJ
Gate source voltage	V_{GS}		±20	V
Power dissipation	P_{tot}	T_C=25 °C	38	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 175	°C
IEC climatic category; DIN IEC 68-1			55/175/56	

[1] J-STD20 and JESD22
[2] Current is limited by bondwire; with an R_{thJC}=1.3 K/W the chip is able to carry 108 A.
[3] See figure 3 for more detailed information
[4] See figure 13 for more detailed information

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics						
Thermal resistance, junction - case	R_{thJC}		-	-	4	K/W
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=1 mA	60	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=58 µA	2	3	4	
Zero gate voltage drain current	I_{DSS}	V_{DS}=60 V, V_{GS}=0 V, T_j=25 °C	-	0.1	1	µA
		V_{DS}=60 V, V_{GS}=0 V, T_j=125 °C	-	10	100	
Gate-source leakage current	I_{GSS}	V_{GS}=20 V, V_{DS}=0 V	-	1	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=10 V, I_D=60 A	-	4.6	5.7	mΩ
Gate resistance	R_G		-	1.2	-	Ω
Transconductance	g_{fs}	$\|V_{DS}\|>2\|I_D\|R_{DS(on)max}$, I_D=60 A	41	82	-	S

[5)] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm^2 (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=30 V, f=1 MHz	-	5000	6600	pF
Output capacitance	C_{oss}		-	1100	1500	
Reverse transfer capacitance	C_{rss}		-	38	-	
Turn-on delay time	$t_{d(on)}$	V_{DD}=30 V, V_{GS}=10 V, I_D=80 A, R_G=1.6 Ω	-	24	-	ns
Rise time	t_r		-	68	-	
Turn-off delay time	$t_{d(off)}$		-	32	-	
Fall time	t_f		-	9	-	
Gate Charge Characteristics[6)]						
Gate to source charge	Q_{gs}	V_{DD}=30 V, I_D=80 A, V_{GS}=0 to 10 V	-	28	-	nC
Gate to drain charge	Q_{gd}		-	6	-	
Switching charge	Q_{sw}		-	19	-	
Gate charge total	Q_g		-	61	82	
Gate plateau voltage	$V_{plateau}$		-	5.6	-	V
Output charge	Q_{oss}	V_{DD}=30 V, V_{GS}=0 V	-	50	66	nC
Reverse Diode						
Diode continous forward current	I_S	T_C=25 °C	-	-	60	A
Diode pulse current	$I_{S,pulse}$		-	-	240	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=60 A, T_j=25 °C	-	0.9	1.2	V
Reverse recovery time	t_{rr}	V_R=30 V, I_F=80A, di_F/dt=100 A/µs	-	52	-	ns
Reverse recovery charge	Q_{rr}		-	59	-	nC

[6)] See figure 16 for gate charge parameter definition

1 Power dissipation

P_{tot}=f(T_C)



2 Drain current

I_D=f(T_C); V_{GS}≥10 V



3 Safe operating area

I_D=f(V_{DS}); T_C=25 °C; D=0

parameter: t_p



4 Max. transient thermal impedance

Z_{thJC}=f(t_p)

parameter: D=t_p/T



5 Typ. output characteristics

I_D=f(V_{DS}); T_j=25 °C

parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)}$=f(I_D); T_j=25 °C

parameter: V_{GS}



7 Typ. transfer characteristics

I_D=f(V_{GS}); |V_{DS}|>2|I_D|$R_{DS(on)max}$

parameter: T_j



8 Typ. forward transconductance

g_{fs}=f(I_D); T_j=25 °C



9 Drain-source on-state resistance

$R_{DS(on)}$=f(T_j); I_D=60 A; V_{GS}=10 V



10 Typ. gate threshold voltage

$V_{GS(th)}$=f(T_j); V_{GS}=V_{DS}

parameter: I_D



11 Typ. capacitances

C=f(V_{DS}); V_{GS}=0 V; f=1 MHz



12 Forward characteristics of reverse diode

I_F=f(V_{SD})

parameter: T_j



13 Avalanche characteristics

I_{AS}=f(t_{AV}); R_{GS}=25 Ω

parameter: $T_{j(start)}$



14 Typ. gate charge

V_{GS}=f(Q_{gate}); I_D=60 A pulsed

parameter: V_{DD}



15 Drain-source breakdown voltage

$V_{BR(DSS)}$=f(T_j); I_D=1 mA



16 Gate charge waveforms



PG-TO220-3-31



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.55	4.85	0.179	0.191
A1	2.55	2.85	0.100	0.112
A2	2.42	2.72	0.095	0.107
b	0.65	0.85	0.026	0.033
b1	0.95	1.33	0.037	0.052
b2	0.95	1.51	0.037	0.059
b3	0.65	1.33	0.026	0.052
b4	0.65	1.51	0.026	0.059
c	0.40	0.63	0.016	0.025
D	15.85	16.15	0.624	0.636
D1	9.53	9.83	0.375	0.387
E	10.35	10.65	0.407	0.419
e	2.54		0.100	
e1	5.08		0.200	
N	3		3	
H	29.45	29.75	1.159	1.171
L	13.45	13.75	0.530	0.541
L1	3.15	3.45	0.124	0.136
øP	2.95	3.20	0.116	0.126
Q	3.15	3.50	0.124	0.138

REFERENCE ../..
SCALE 0 2.5 5mm
EUROPEAN PROJECTION
ISSUE DATE 08-01-2007
FILE TO220_2

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2010 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.