

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC

DIST

CM

53

REV

DATE

DESCRIPTION

DATE

DWN

APVD

V3

REVISED PER ECO-12-003860

08MAR12

JR

TM

4

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

27.43
REF

SEE DETAIL A

11.68

27.43±0.38

SEE DETAIL B

6

33.02

20.32

3

AMP

VIEW A—A

350736-4 ONLY

350736-4 3-DIMENSIONAL MODEL

NTS

3-DIMENSIONAL MODEL

NTS

PARTIAL DETAIL A

OPTIONAL CONSTRUCTION

4

DETAIL B

350736-4 ONLY

1. MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOK™ CAP OR HEADER.

2. SMALL NICKS ARE PERMITTED ON THE CIRCUIT TOWERS WHICH COULD INCREASE THE INITIAL HOUSING MATING FORCE BY UP TO 4.4 NEWTONS [1.0 LBS]. NO INDIVIDUAL NICKED TOWER SHALL INCREASE THIS FORCE BY OVER 2.2 NEWTONS [.5 LBS].

3. DIMENSION INDICATED IS AS MOLDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR.

4. FOUR RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION. OR SIX RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OPTIONAL.

5. NOT MANUFACTURED IN U.S.

6. UNDERWRITERS RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ONCE ON EACH SIDE OF HOUSING.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
K. WHITAKER
20FEB92

CHK
R. SWING
20FEB92

APVD
D. SELF
24FEB92

NAME

TE Connectivity

DIMENSIONS:

mm

0. PLC ± -

1. PLC ± -

2. PLC ± 0.13

3. PLC ± -

4. PLC ± -

ANGLES ± 0°30'

TOLERANCES UNLESS OTHERWISE SPECIFIED:

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

MATERIAL NYLON,UL 94V-0

FINISH -

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A1

00779

C=350736

-

CUSTOMER DRAWING

SCALE 4:1

SHEET 1 OF 1

REV V3

METRIC

4805 (3/11)

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА