






NOTES:

1. METALSHELLS: STEEL; min. 320µ" TIN
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: 30µ" HARD GOLD OVER min. 50µ" NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
4. NO CONTACTS ON POS. A1 - A4
5. CONNECTOR IS PART MARKED: 3009W4PCM99A10X CONEC ABC
6. = CHECK DIMENSION

Directive 2002/95/EC
„RoHS“
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR
REPRODUCED IN ANY WAY, AND MAY NOT
BE PASSED ON TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH
DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
2004	date	name	
drawn	26.08.	Lehnenkühler	
appd.	27.08.	Mickenbecker	
norm			
d-old			

tolerance	
scale:	2:1 (5:1)
material:	SEE NOTES
title:	D-SUB COMBINATION MALE 9W4P SOLDER CUP
dwg no:	AutoCAD 2004 13K1A1237
part no:	3009W4PCM99A10X

scale:	2:1 (5:1)
material:	SEE NOTES
title:	D-SUB COMBINATION MALE 9W4P SOLDER CUP
dwg no:	AutoCAD 2004 13K1A1237
part no:	3009W4PCM99A10X