HIRSCHMANN® Test & Measurement
A BRAND OF SKS

SKS Kontakttechnik GmbH

Measuring leads

4 mm system

MLN SIL 200/1

Product	MLN SIL 200/1
description	Measuring lead, at either end 4 mm diameter plug with caged spring and 4 mm diameter socket for tower construction. Nickel-plated copper beryllium contact spring. Highly flexible, double insulated stranded lead, grip and lead shatter-proof. Built in colour indicator for easy identification of insulation damages.
operating instruction	BA401
article-no. / *colour	9340941xx 00 black 01 red 02 blue 03 yellow 04 green 88 yellow green Ni
drawing	
	
technical data	
rated voltage[1]	30 VAC / 60 VDC
measurement cat. acc. to IEC 61010	O [3]
rated current[1] (consider derating curve)	16 A
material plug	brass, nickel plated
housing material	PA
temperature range acc. To IEC61010[2]	-15 °C to +70 °C
inflammability class acc. to UL 94 (only valid for basic material of housing)	V-2
cable length	200 cm

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА

conductor size	1 mm²
cable material	SIL
contact resistance	40 mOhm
standard	IEC 61010

(1) for normal environmental conditions -5°C to +40°C
(2) contact the manufacturer for applications at deviating temperature ranges
(3) without rated measurement category, for other circuits that are not directly connected to mains
stand: 20.07.2018