




LOC		DIST		REVISIONS				
P	LTR	DESCRIPTION			DATE	DWN	APVD	
L1	REVISED	PER	ECO-15-010630		27JUL2015	NK	MZ	

D



C



RECOMMENDED PANEL CUTOUT

DETAIL A

B



DETAIL B

- 1 CAVITY IDENTIFICATION ON FRONT AND REAR FACE.
- 2 WILL ACCEPT THIRTY-SEVEN (37) MULTIMATE SOCKET CONTACTS.
- 3 NO 4 FASTENER RECOMMENDED FOR MOUNTING.
- 4 NYLON 6/6, NATURAL.
- 5 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE 5	STANDARD	NO	3.81 [.150] DIA HOLE	A	4 206306-8-
	SMALL PACK	NO	3.81 [.150] DIA HOLE	A	-206306-6-
	STANDARD	NO	4-40 THREADED INSERT	A	206306-5
	STANDARD	YES	-	B	206306-4
	STANDARD	YES	3.81 [.150] DIA HOLE	A	206306-3
	STANDARD	NO	-	B	206306-2
	STANDARD	NO	3.81 [.150] DIA HOLE	A	206306-1
PACKAGING		PERIPHERAL SEAL	C	SEE DETAIL	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN D.GELTZ CHK R.STONE APVD A.FRANTUM	07/26/93 08/11/93 08/13/93	NAME	
DIMENSIONS: MM [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC 108-10024	
MATERIAL HOUSING: NYLON, BLACK INSERT: BRASS		FINISH -		RESTRICTED TO -	
WEIGHT -		SCALE 2:1		SHEET 1 OF 1	
CUSTOMER DRAWING		DRAWING NO 00779		REV L1	