



Hinged MicroSpeeder with self positioning ring head, tilting through 90° to both sides.



7-piece Hinged MicroSpeeder set.

No swapping over: a real time saver! Extra long design.

The 72-teeth inner ring gear made of special high alloy steel allows ratcheting even when the spanner can only be moved through 5°. Nevertheless, the torque transmission capacity far exceeds the DIN/ISO standards. CrV steel shaft with optimum surface protection: double nickel-plating and single matt-finished chrome-plating. Socket sizes easy to read due to laser marking!

The self positioning action of the hinged ring side substantially reduces work load, while its flexibility and durability remain unmatched. The self positioning action of the ring is ideal for tight locations.

One each 8, 10, 13, 16, 17, 18 and 19mm of the long version, in a sturdy powder coated steel box.

NO 23 068



Hinged MicroSpeeder, individually

NO 23 045	Size	8mm
NO 23 046	Size	9mm
NO 23 047	Size	10mm
NO 23 048	Size	11mm
NO 23 049	Size	12mm
NO 23 050	Size	13mm
NO 23 051	Size	14mm
NO 23 052	Size	15mm
NO 23 053	Size	16mm
NO 23 054	Size	17mm
NO 23 055	Size	18mm
NO 23 056	Size	19mm
NO 23 058	Size	21mm
NO 23 059	Size	22mm
NO 23 061	Size	24mm

**2 YEAR
GUARANTEE!**

For full
professional use!



Inversible joint: Unbeatable
in tight places!



Compact design allows for
minimal
outer dimensions (A+B).



Where old generation
spanners cannot be
repositioned
the Speeder's ratchet
function
takes over.



A very slim head provides
shelter
to the fully encapsulated
drive.