ALPHA & OMEGA SEMICONDUCTOR

# AON7804

## 30V Dual N-Channel MOSFET

## General Description

The AON7804 is designed to provide a high efficiency synchronous buck power stage with optimal layout and board space utilization. It includes two low $R_{DS(ON)}$ MOSFETs in a dual DFN3x3 package. The AON7804 is well suited for use in compact DC/DC converter applications.

## Product Summary

| | |
|---|---|
| $V_{DS}$ | 30V |
| $I_D$ (at $V_{GS}$=10V) | 22A |
| $R_{DS(ON)}$ (at $V_{GS}$=10V) | < 21mΩ |
| $R_{DS(ON)}$ (at $V_{GS}$ = 4.5V) | < 26mΩ |

100% UIS Tested
100% $R_g$ Tested
ESD protected

Green Product

DFN 3x3A_Dual

Top View




Bottom View




Top View




**Absolute Maximum Ratings $T_A$=25°C unless otherwise noted**

| Parameter | | Symbol | Maximum | Units |
|---|---|---|---|---|
| Drain-Source Voltage | | $V_{DS}$ | 30 | V |
| Gate-Source Voltage | | $V_{GS}$ | ±20 | V |
| Continuous Drain Current | $T_C$=25°C | $I_D$ | 22 | A |
| | $T_C$=100°C | | 14 | |
| Pulsed Drain Current [C] | | $I_{DM}$ | 48 | |
| Continuous Drain Current | $T_A$=25°C | $I_{DSM}$ | 9 | A |
| | $T_A$=70°C | | 7 | |
| Avalanche Current [C] | | $I_{AS}$, $I_{AR}$ | 19 | A |
| Avalanche energy L=0.1mH [C] | | $E_{AS}$, $E_{AR}$ | 18 | mJ |
| Power Dissipation [B] | $T_C$=25°C | $P_D$ | 17 | W |
| | $T_C$=100°C | | 7 | |
| Power Dissipation [A] | $T_A$=25°C | $P_{DSM}$ | 3.1 | W |
| | $T_A$=70°C | | 2 | |
| Junction and Storage Temperature Range | | $T_J$, $T_{STG}$ | -55 to 150 | °C |

**Thermal Characteristics**

| Parameter | | Symbol | Typ | Max | Units |
|---|---|---|---|---|---|
| Maximum Junction-to-Ambient [A] | t ≤ 10s | $R_{\theta JA}$ | 30 | 40 | °C/W |
| Maximum Junction-to-Ambient [A D] | Steady-State | | 60 | 75 | °C/W |
| Maximum Junction-to-Case | Steady-State | $R_{\theta JC}$ | 6.2 | 7.5 | °C/W |



sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА

**Electrical Characteristics ($T_J$=25°C unless otherwise noted)**

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|---|---|---|---|---|---|---|
| **STATIC PARAMETERS** | | | | | | |
| $BV_{DSS}$ | Drain-Source Breakdown Voltage | $I_D$=250µA, $V_{GS}$=0V | 30 | | | V |
| $I_{DSS}$ | Zero Gate Voltage Drain Current | $V_{DS}$=30V, $V_{GS}$=0V | | | 1 | µA |
| | | $T_J$=55°C | | | 5 | |
| $I_{GSS}$ | Gate-Body leakage current | $V_{DS}$=0V, $V_{GS}$= ±20V | | | 10 | µA |
| $V_{GS(th)}$ | Gate Threshold Voltage | $V_{DS}$=$V_{GS}$ $I_D$=250µA | 1.2 | 1.8 | 2.4 | V |
| $I_{D(ON)}$ | On state drain current | $V_{GS}$=10V, $V_{DS}$=5V | 48 | | | A |
| $R_{DS(ON)}$ | Static Drain-Source On-Resistance | $V_{GS}$=10V, $I_D$=8A | | 17 | 21 | mΩ |
| | | $T_J$=125°C | | 23 | | |
| | | $V_{GS}$=4.5V, $I_D$=7A | | 21 | 26 | mΩ |
| $g_{FS}$ | Forward Transconductance | $V_{DS}$=5V, $I_D$=9A | | 30 | | S |
| $V_{SD}$ | Diode Forward Voltage | $I_S$=1A,$V_{GS}$=0V | | 0.75 | 1 | V |
| $I_S$ | Maximum Body-Diode Continuous Current | | | | 15 | A |
| **DYNAMIC PARAMETERS** | | | | | | |
| $C_{iss}$ | Input Capacitance | $V_{GS}$=0V, $V_{DS}$=15V, f=1MHz | 600 | 740 | 888 | pF |
| $C_{oss}$ | Output Capacitance | | 77 | 110 | 145 | pF |
| $C_{rss}$ | Reverse Transfer Capacitance | | 50 | 82 | 115 | pF |
| $R_g$ | Gate resistance | $V_{GS}$=0V, $V_{DS}$=0V, f=1MHz | 0.5 | 1.1 | 1.7 | Ω |
| **SWITCHING PARAMETERS** | | | | | | |
| $Q_g$(10V) | Total Gate Charge | $V_{GS}$=10V, $V_{DS}$=15V, $I_D$=8A | 12 | 15 | 18 | nC |
| $Q_g$(4.5V) | Total Gate Charge | | 6 | 7.5 | 9 | nC |
| $Q_{gs}$ | Gate Source Charge | | | 2.5 | | nC |
| $Q_{gd}$ | Gate Drain Charge | | | 3 | | nC |
| $t_{D(on)}$ | Turn-On DelayTime | $V_{GS}$=10V, $V_{DS}$=15V, $R_L$=1.7Ω, $R_{GEN}$=3Ω | | 5 | | ns |
| $t_r$ | Turn-On Rise Time | | | 3.5 | | ns |
| $t_{D(off)}$ | Turn-Off DelayTime | | | 19 | | ns |
| $t_f$ | Turn-Off Fall Time | | | 3.5 | | ns |
| $t_{rr}$ | Body Diode Reverse Recovery Time | $I_F$=8A, dI/dt=500A/µs | 6 | 8 | 10 | ns |
| $Q_{rr}$ | Body Diode Reverse Recovery Charge | $I_F$=8A, dI/dt=500A/µs | 14 | 18 | 22 | nC |

A. The value of $R_{\theta JA}$ is measured with the device mounted on 1in$^2$ FR-4 board with 2oz. Copper, in a still air environment with $T_A$ =25°C. The Power dissipation $P_{DSM}$ is based on $R_{\theta JA}$ t ≤ 10s value and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.

B. The power dissipation $P_D$ is based on $T_{J(MAX)}$=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150°C. Ratings are based on low frequency and duty cycles to keep initial $T_J$ =25°C.

D. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to case $R_{\theta JC}$ and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300µs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedence which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=150°C. The SOA curve provides a single pulse rating.

G. The maximum current rating is package limited.

H. These tests are performed with the device mounted on 1 in$^2$ FR-4 board with 2oz. Copper, in a still air environment with $T_A$=25°C.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




**Figure 7: Gate-Charge Characteristics**




**Figure 8: Capacitance Characteristics**




**Figure 9: Maximum Forward Biased Safe Operating Area (Note F)**




**Figure 10: Single Pulse Power Rating Junction-to-Case (Note F)**




**Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)**

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 12: Single Pulse Avalanche capability (Note C)




Figure 13: Power De-rating (Note F)




Figure 14: Current De-rating (Note F)




Figure 15: Single Pulse Power Rating Junction-to-Ambient (Note H)




Figure 16: Normalized Maximum Transient Thermal Impedance (Note H)

Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms




Diode Recovery Test Circuit & Waveforms