


DW: 11/0.16AM

CONDUCTOR: 1/0.57BC

INSULATION: HDPE



JACKET: PVC

AL/MY

CROSS PE

CONSTRUCTION:

[(1/0.57BC)*4P+PE CROSS]+DW(11/0.16AM)+AL/MY

CONSTRUCTION DESCRIPTION :

1. CONDUCTOR: 1/0.57 ± 0.005BC

ID: 0.98 ± 0.02mm

MATERIAL: HDPE (210)

2. PE CROSS: HDPE (8380), OD: 4.3 ± 0.1mm

3. STANDING DIRECTION: RIGHT

4. AL Foil: 18mm*0.025mm

5. Drain Wire: 11/0.16AM

6. OUTER DIAMETER: 6.2 ± 0.15mm

MATERIAL: 45P PVC

COLOR: GREY

7. MAKING:

NETWORK SYSTEMS CABLE FTP ANSI TIA/EIA 568-B.2-1 23AWG (4PR) OR

ISO/IEC11801 VERIFIED CAT 6 1M (2M, ..., 15M, ..., 305M)

8. PACKING: 305M/R

CORE COLOR :

blue/white&blue

brown/white&brown

orang/white&orang

green/white&green

REMAKE:

1. THE ID AND OD OF THE WIRE MUST BE EXACT, CAN NOT REDUCE THE CENTRE.

2. THICKNESS OF COAT BY EQUALITY: 0.55mm, THE LEAST THICKNESS: 0.50mm

3. THICKNESS OF CORE BY EQUALITY: 0.2mm, THE LEAST THICKNESS: 0.18mm

4. IMPEDANCE: 100 Ω ± 15%

RATING TEMPERATURE: -20°C TO 60°C

STANDARDS: ISO/IEC11801, TIA/EIA 568-B.2-1



VCOM International Ltd.

DRAWING NO.

PRODUCT NO.

ITEM:

SAM-AC-106G

NC624

CAT6 FTP 0.57BC

APPROVED BY

CHECKED BY


DRAWN BY

CUSTOMER

PAGE

UNIT

SCALE



A/0

2013-01-18

xiang

1 of 1

mm

REV

DESCRIPTION

DATE