Opto Plus LED Corp.
0.4” Case Mold Type LED Display
OPD-S4030G-BW
OPD-S4031G-BW

FEATURES

- 0.4 inch (10.16 mm) Digit Height.
- Low current operation.
- Case mold type.
- Black face, White segment.
- RoHS compliant, Pb Free.

DESCRIPTION

The OPD-S4030G-BW & OPD-S4031G-BW are 0.4 inch (10.16 mm) height single 7-segment display.

This device utilizes Yellow Green LED chip which are made from GaP on a transparent GaP substrate.

The display has Black face, White segment.

DEVICE

PART NO Yellow Green	DESCRIPTION
OPD-S4030G-BW	Common Anode
OPD-S4031G-BW	Common Cathode

RoHS Compliance **Pb free.**

Opto Plus LED Corp. 7F-3, No.496 , Bannan Road, Jhonghe Dist., New Taipei City 235, Taiwan (R.O.C)
Website: www.opled.com.tw E-mail: sales@opled.com.tw Tel: 886-2-2222-5698 Fax: 886-2-2222-2566

sales@prom-elec.com / ООО ПРОМЭЛЕКТРОНИКА

Opto Plus LED Corp.
0.4” Case Mold Type LED Display
OPD-S4030G-BW
OPD-S4031G-BW

● MECHANICAL DIMENSIONS



NOTES: Dimension is in millimeters. Tolerance is ± 0.25 mm unless otherwise noted.

● TYPICAL INTERNAL EQUIVALENT CIRCUIT



Opto Plus LED Corp. 7F-3, No.496 , Bannan Road, Jhonghe Dist., New Taipei City 235, Taiwan (R.O.C)
Website: www.opled.com.tw E-mail: sales@opled.com.tw Tel: 886-2-2222-5698 Fax: 886-2-2222-2566

G: YELLOW GREEN (GaP/GaP)

ABSOLUTE MAXIMUM RATING AT Ta=25°C

Parameter	Symbol	Yellow Green	Unit
Power dissipation per dice	P_{AD}	70	mW
Derating Liner from 25℃ per dice	-	0.33	mA／℃
Continuous forward current per dice	I_{AF}	25	mA
Peak current per dice (duty cycle 1/10, 1kHz)	I_{PF}	90	mA
Reverse voltage per dice	V_R	5	V
Operating temperature	T_{OPR}	-25 to +85	℃
Storage temperature	T_{STG}	-25 to +85	℃

ELECTRICAL - OPTICAL CHARACTERISTICS AT Ta=25°C

Characteristic	Symbol	Condition	Min.	Type	Max.	Unit
Forward voltage	V_F	I_F =20mA	-	2.0	2.6	V
Reverse current	I_R	V_R =5V	-	-	10	μA
Peak wavelength	λ_P	I_F =20mA	-	568	-	nm
Dominant wavelength	λ_D	I_F =20mA	-	570	-	nm
Luminous intensity	I_V	I_F =20mA	-	5	-	mcd
Spectral radiation bandwidth	$\Delta\lambda$	I_F =20mA	-	30	-	nm

Opto Plus LED Corp. 7F-3, No.496 , Bannan Road, Jhonghe Dist., New Taipei City 235, Taiwan (R.O.C)
Website: www.opled.com.tw E-mail: sales@opled.com.tw Tel: 886-2-2222-5698 Fax: 886-2-2222-2566

● G: YELLOW GREEN (GaP/GaP) CURVE

Typical Electro-optical Characteristic Curves

(25 ℃ Free Air Temperature Unless Otherwise Specified)



Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE



Fig.2 RELATIVE INTENSITY VS. FORWARD CURRENT



Fig.3 FORWARD VOLTAGE VS. TEMPERATURE



Fig.4 RELATIVE INTENSITY VS. TEMPERATURE



Fig.5 RELATIVE INTENSITY VS. WAVELENGTH



Fig.6 MAX. ALLOWABLE DC CURRENT VS. AMBIENT TEMPERATURE

Opto Plus LED Corp. 7F-3, No.496 , Bannan Road, Jhonghe Dist., New Taipei City 235, Taiwan (R.O.C)
Website: www.opled.com.tw E-mail: sales@opled.com.tw Tel: 886-2-2222-5698 Fax: 886-2-2222-2566

RECOMMEND SOLDERING PROFILE



SOLDERING IRON

Basic spec is ≦4 sec when 260°C. If temperature is higher, time should be shorter (+10°C→1 sec). Power dissipation of Iron should be smaller than 15W, and temperature should be controllable. Surface temperature of the device should be under 230°C.

REWORK

Customer must finish rework within ≦4 sec under 245℃.

Opto Plus LED Corp. 7F-3, No.496 , Bannan Road, Jhonghe Dist., New Taipei City 235, Taiwan (R.O.C)
Website: www.opled.com.tw E-mail: sales@opled.com.tw Tel: 886-2-2222-5698 Fax: 886-2-2222-2566