

SIEMENS

Catalog
Extract
LV 10

Edition
04/2023

SENTRON • SIVACON • ALPHA

Low-Voltage Power Distribution and Electrical Installation Technology

Monitoring Devices

[siemens.com/lowvoltage](https://www.siemens.com/lowvoltage)

Innovative solutions for industrial controls and power distribution

Reliable components and systems are essential in ensuring smooth power distribution in buildings and industrial plants.

With SIRIUS, SENTRON, SIVACON and ALPHA, we offer an innovative portfolio for standard-compliant and demand-oriented applications.

Efficient engineering tools and innovative cloud-based solutions can be flexibly tailored to individual requirements.

We are there when you need us

Your personal contact can be found at
www.siemens.com/lowvoltage/contact

Catalog LV 10 · 04/2023

You will find the latest edition and all future editions at www.siemens.com/lowvoltage/catalogs

You can find the current prices at
www.siemens.com/lowvoltage/mall



The products and systems described in this catalog are manufactured/distributed under application of a certified quality management system in accordance with EN ISO 9001 (for the Certified Registration Nos., see www.siemens.com/system-certificates/ep). The certificate is recognized by all IQNet countries.

Technical specifications

The technical specifications are for general information purposes only. Always heed the operating instructions and notices on individual products during assembly, operation and maintenance.

All illustrations are not binding.

© Siemens 2023

Low-Voltage Power Distribution and Electrical Installation Technology

	Introduction	I/2
Protecting	Air Circuit Breakers	1/1
	Molded Case Circuit Breakers	2/1
	Miniature Circuit Breakers	3/1
	Residual Current Protective Devices/Arc Fault Detection Devices (AFDDs)	4/1
	Switching Devices	5/1
	Overvoltage Protection Devices	6/1
	Fuse Systems	7/1
Protecting, Switching and Isolating	Switch Disconnectors	8/1
Switching and Isolating	Transfer Switching Equipment and Load Transfer Switches	9/1
Measuring and Monitoring	Measuring Devices, Power Monitoring and Digitalization Solutions	10/1
	Monitoring Devices	11/1
Distribution	Transformers, Power Supply Units and Socket Outlets	12/1
	Busbar Systems	13/1
	Terminal Blocks	14/1
	Switchboards, Distribution Boards and Small Distribution Boards	15/1
	Busbar Trunking Systems	16/1
	System Cubicles, System Lighting and System Air-Conditioning	17/1
	Appendix	A/1

I

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

A

Well-monitored – well-protected


Monitoring devices perform numerous functions to protect people and machinery: At dusk, they switch on automatically, control the temperature or signal the location where a fuse has tripped.

They also ensure reliable switchover to emergency power supply, monitor the emergency lighting, ensure overload-free operation of motors and neutral monitoring for breakage and overvoltages.

Monitoring devices can do even more, e.g., underload monitoring of asynchronous motors in no-load operation.



Monitoring Devices



All the information you need	11/2
System overview	11/4
Monitoring devices for electrical values	11/6
5SV8 residual current monitors	11/6
5SV8 modular residual current device	11/8
5TT3 undervoltage relays	11/12
5TT3 short-time voltage relay	11/14
5TT3 undervoltage and overvoltage relays	11/15
5TT6 current relays	11/16
5TT3 fuse monitors	11/17
5TT3 phase monitors	11/18
5TT3 phase sequence monitors	11/19
5TT3 insulation monitors for industrial applications	11/20
Monitoring devices for plants and equipment	11/21
5TT5 EMERGENCY STOP modules	11/21
5TT3 level relays	11/22
5TT3 line circuit relays	11/23
7LQ2 twilight switches	11/24

A multitude of additional information ...

Information + ordering

All the important things at a glance

For information about monitoring devices, please visit our website www.siemens.com/lowvoltage

Your product in detail

The relevant tender specifications can be found at www.siemens.com/lowvoltage/tenderspecifications

Use our conversion tool for quick and easy conversion to Siemens products www.siemens.com/conversion-tool

Everything you need for your order

You will find an overview of your products at

- Monitoring devices sie.ag/2m3no4A

Direct forwarding to the individual products in the Industry Mall by clicking on the article number in the catalog or entering this web address incl. article number www.siemens.com/product_catalog_SIEP?Article No.

The fast track to the experts

Contact persons in your region

We offer a comprehensive portfolio of services. You can find your local contacts at www.siemens.com/lowvoltage/components/contact

You will find further information on services at www.siemens.com/service-offers

Competent expert advice on technical questions with a wide range of demand-optimized services for all our products and systems.

Assistance with technical queries is provided at www.siemens.com/support-request

... can be found in our online services

Commissioning + operation

Your product in detail

Detailed technical information is available to you at www.siemens.com/lowvoltage/product-support

- Operating instructions
- Characteristic curves
- Certificates

Comprehensive mobile support via the Siemens Industry Online Support app available for download from the [App Store](#) and [Play Store](#)

Provision of 3D data (step and u3d data formats)

- Siemens Industry Mall
www.siemens.com/lowvoltage/mall
- Image database
www.siemens.com/lowvoltage/picturedb

Engineering data for CAD or CAE systems are available in the CAX Download Manager at www.siemens.com/cax

Manuals

Manuals are available for downloading at www.siemens.com/lowvoltage/manuals

- Configuration Manual
– Monitoring devices ([45316099](#))

Technical overview – Monitoring devices



The fast way to get you to our online services

This page provides you with comprehensive information and links on monitoring devices
www.siemens.com/lowvoltage/product-support ([109769086](#))

System overview

Monitoring devices for electrical values



5SV8 residual current monitor



5SV8 modular residual current device



5TT3 and 5TT6 relay



5TT3 monitors

Accessories



Summation current transformer



Holders for DIN rails



Magnetic field centering sleeves

Monitoring devices for plants and equipment



5TT5 EMERGENCY STOP modules



5TT3 relay



7LQ2 twilight switches

Accessories



Immersion electrodes

Note:

You will find a detailed range of accessories with the basic units.

5SV8 residual current monitors

Type A and type AC

Mounting width	RCM analog		RCM digital	
	2 MW	3 MW	3 MW	3 MW
				
Rated operational voltage U_e	Rated residual current $I_{\Delta n}$		Response time Δt	
	Type A	Type AC		
230 V AC	0.03 ... 5 A	>3 A	0.02 ... 5 s	5SV8000-6KK
	0.03 ... 3 A	5 ... 30 A	0.02 ... 10 s, INS, SEL ¹⁾	5SV8001-6KK
				5SV8200-6KK

Further technical specifications



Further technical specifications		5SV8000-6KK	5SV8001-6KK	5SV8200-6KK
Standards				
Standards		EN 62020, IEC 62020		
Approvals		–	UL	
Supply				
Rated operational voltage U_e		230 V AC		
Frequency		50/60 Hz		
Rated residual current $I_{\Delta n}$	Type A	0.03 ... 3 A		5 ... 30 A
	Type AC	>3 A		
Response time Δt		0.02 ... 5 s	0.02 ... 10 s, INS, SEL ¹⁾	
Relay contacts				
Relay contacts		1× alarm	1× pre-alarm, 1× alarm	1× pre-alarm, 4× alarm
Rated voltage		230 V AC		
Rated current		6 A		
Summation current transformer				
Diameter		20 ... 210 mm		
Equipment				
Maximum cable length RCM/CT		10 m (shielded cable)		
Conductor cross-section		1.5 mm²		
Test/reset		Yes/Yes		
External tripping operation/external reset		–/Yes	Yes/Yes	
Safety				
Degree of protection	Contacts	IP20		
	Front	IP41		
Ambient conditions				
Operating temperature		–10 ... +50 °C		

¹⁾ INS: Instantaneous,
SEL: Selective

Accessories

Summation current transformers

- Including holder for DIN rail or wall mounting
- Standard ☺



Mounting options	Lowest measurable residual current $I_{\Delta n \min}$	Rated current I_n	Maximum current ²⁾ $I_{\max}$	Internal diameter	Article No.
DIN rail	30 mA	≤40 A	240 A	20 mm	5SV8700-0KK
		≤63 A	380 A	30 mm	5SV8701-0KK
Wall mounting, DIN rail ¹⁾	30 mA	≤80 A	480 A	35 mm	5SV8702-0KK
		≤200 A	1200 A	70 mm	5SV8703-0KK
Wall mounting	100 mA	≤250 A	1500 A	105 mm	5SV8704-0KK
	300 mA	≤500 A	3000 A	140 mm	5SV8705-0KK
		≤600 A	3600 A	210 mm	5SV8706-0KK

Holders for DIN rails



- Suitable for summation current transformers with internal diameter of 20 mm, 30 mm, 35 mm, 70 mm
- Cannot be used together with magnetic field centering sleeves

Article No.
5SV8900-1KK

Magnetic field centering sleeves



Internal diameter	Article No.
35 mm	5SV8902-1KK
70 mm	5SV8903-1KK
105 mm	5SV8904-1KK
140 mm	5SV8905-1KK
210 mm	5SV8906-1KK

¹⁾ The holder for DIN rails is additionally required for mounting onto the DIN rail.

²⁾ Short-time starting current, up to 2 s

5SV8 modular residual current device

Type A

Mounting width

MRCD
3 MW



Rated operational voltage U_e	Rated residual current $I_{\Delta n}$ Type A	Response time Δt	
230 V AC	0.03 ... 3 A	0.02 ... 10 s, INS, SEL ¹⁾	5SV8101-6KK

Further technical specifications


Standards		
Standards		EN 60947-2 (Annex M), IEC 60947-2 (Annex M)
Approvals		–
Supply		
Rated operational voltage U_e		230 V AC from a 1-phase auxiliary voltage source (also externally)
Frequency		50/60 Hz
Rated residual current $I_{\Delta n}$	Type A	0.03 ... 3 A (default setting: 30 mA)
	Type AC	–
Response time Δt	$I_{\Delta n} = 30 \text{ mA}$	INS instantaneous
	$I_{\Delta n} > 30 \text{ mA}$	INS – SEL – 0.06 ... 10 s ¹⁾ (default setting INS)
Relay contacts		
Relay contacts		1× alarm, 1x tripping operation
Rated voltage		230 V AC
Rated current		6 A
Summation current transformer		
Diameter		35 ... 210 mm
Equipment		
Maximum cable length RCM/CT		10 m (shielded cable)
Conductor cross-section		0.125 ... 2.08 mm ²
Test/reset		Yes/Yes
External tripping operation/external reset		Yes/Yes
Safety		
Degree of protection	Contacts	IP20
	Front	IP41
Ambient conditions		
Operating temperature		–10 ... +50 °C

¹⁾ INS: Instantaneous,
SEL: Selective

Accessories

Summation current transformers

- Including holder for wall mounting
- Standard ☉



Mounting options	Lowest measurable residual current $I_{\Delta n \min}$	Rated current I_n	Maximum current ²⁾ $I_{\max}$	Internal diameter	Article No.
Wall mounting, DIN rail ¹⁾	30 mA	≤80 A	480 A	35 mm	5SV8702-0KK
	30 mA	≤200 A	1200 A	70 mm	5SV8703-0KK
Wall mounting	100 mA	≤250 A	1500 A	105 mm	5SV8704-0KK
	300 mA	≤500 A	3000 A	140 mm	5SV8705-0KK
		≤600 A	3600 A	210 mm	5SV8706-0KK

Holders for DIN rails



- Suitable for summation current transformers with internal diameter of 20 mm, 30 mm, 35 mm, 70 mm
- Cannot be used together with magnetic field centering sleeves

Article No.
5SV8900-1KK

Magnetic field centering sleeves




Internal diameter	Article No.
35 mm	5SV8902-1KK
70 mm	5SV8903-1KK
105 mm	5SV8904-1KK
140 mm	5SV8905-1KK
210 mm	5SV8906-1KK

¹⁾ The holder for DIN rails is additionally required for mounting onto the DIN rail.

²⁾ Short-time starting current, up to 2 s

Tested combination options



5SV8101-6KK/- (tested combinations)

① Modular residual current device

5SV8101-6KK

② DIN rail

EN 60715 – TH35 – 7.5 35 – 15

③ Summation current transformers

Magnetic field centering sleeves

Ø 35 mm	5SV8702-0KK	5SV8902-1KK
Ø 70 mm	5SV8703-0KK	5SV8903-1KK
Ø 105 mm	5SV8704-0KK	5SV8904-1KK
Ø 140 mm	5SV8705-0KK	5SV8905-1KK
Ø 210 mm	5SV8706-0KK	5SV8906-1KK

④ Molded case circuit breakers

⑤ Trip element

3VL17... 3VL27... 3VL37... 3VL47... 3VA10... 3VA11... 3VA20... 3VA21... 3VA22... 3VA12... 3VA23... 3VA24...

3VL9400-1UP00

3VA9908-0BB11

3VA9908-0BB20

3VA9908-0BB24

3VA9908-0BB25

3VA9908-0BB11

3VA9908-0BB20

3VA9908-0BB24

5SV8 modular residual current device

Type B

Mounting width **MRCD digital**
2 MW



Rated operational voltage U_e	Rated residual current $I_{\Delta n}$ Type B	Response time Δt	
230 V AC	0.03 ... 1 A	0 ... 10 s	5SV8101-4KK
24 V DC	0.03 ... 1 A	0 ... 10 s	5SV8111-4KK

Further technical specifications


5SV8101-4KK

5SV8111-4KK

Standards		
Standards		EN 60947-2 (Annex M), IEC 60947-2 (Annex M)
Supply		
Supply voltage U_s		230 V AC (70 ... 300 V AC)24 V DC (9.6 ... 94 V DC)
Frequency		50/60 Hz–
Power consumption		<6.5 VA
Relay contacts		
Relay contacts		1× alarm, 1× tripping operation
Rated voltage		250 V AC
Rated current		5 A
External summation current transformer		
Internal diameter		35 ... 210 mm (5SV8701-2KK, 5SV8701-2KP, 5SV8702-2KK, 5SV8702-2KP, 5SV8703-2KK, 5SV8704-2KK)
Rated voltage	(Summation current transformers)	690 V
Response characteristic	Acc. to IEC 60947-2 (M)	Type B
Rated frequency		0 ... 2 kHz
Response residual current	$I_{\Delta n1}$ (AL1 alarm)	50 ... 100% of $I_{\Delta n2}$ (factory setting: 50%)
	$I_{\Delta n2}$ (TP2 tripping)	30 mA ... 1 A (factory setting: 30 mA)
Response delay	t_{on1} (alarm)	0 ... 10 s (factory setting: 1 s)
	t_{on2} (tripping)	0 ... 10 s (factory setting: 0 s)
Equipment		
Maximum cable length MRCD/converter		10 m (6 × 0.75 mm²)
Password		Off/0 ... 999 (factory setting: 0)
Safety		
Degree of protection	Components (IEC 60529)	IP30
	Terminals (IEC 60529)	IP20
EMC		IEC 60947-2 (M)
Overvoltage category		III
Pollution degree		3
Mechanical data		
Width		36 mm (2 MW)
Depth		64 mm
Height		85 mm
Weight		150 g
Mounting		DIN rail
Enclosure material		Polycarbonate
Electrical connection		Screw terminals
Conductor cross-section	Rigid	0.2 ... 4 mm²
	Flexible, with end sleeve	0.2 ... 2.5 mm² (AWG 24 ... 12)
Stripped length		8 ... 9 mm
Tightening torque		0.5 ... 0.6 Nm
Ambient conditions		
Operating temperature		–25 ... + 55 °C

Accessories

Summation current transformers



Lowest measurable residual current $I_{\Delta n \min}$	Rated current I_n	Maximum current ¹⁾ $I_{\max}$	Internal diameter	Version	Article No.
10 mA	≤ 80 A	500 A	35 mm	Standard	5SV8701-2KK
				With shield	5SV8701-2KP
	≤ 160 A	1000 A	60 mm	Standard	5SV8702-2KK
				With shield	5SV8702-2KP
100 mA	≤ 330 A	2000 A	120 mm	Standard	5SV8703-2KK
300 mA	≤ 630 A	3800 A	210 mm	Standard	5SV8704-2KK


Holders for DIN rails



Suitable for summation current transformers	Article No.
5SV8701-2KK, 5SV8701-2KP	5SV8900-2KK
5SV8702-2KK, 5SV8702-2KP	5SV8900-3KK

¹⁾ Short-time starting current, up to 2 s

Tested combination options



5SV8101-4KK/5SV8111-4KK (tested combinations)

1 Modular residual current device

5SV8101-4KK/5SV8111-4KK

2 DIN rail

EN 60715 – TH35 – 7,5 35 – 15

3 Summation current transformers

Ø 35 mm 5SV8701-2KK/5SV8701-2KP


Ø 60 mm 5SV8702-2KK/5SV8702-2KP

Ø 120 mm 5SV8703-2KK

Ø 210 mm 5SV8704-2KK

4 Relay contacts

DC:



AC: max. 230 V, 5 A

5 Molded case circuit breakers

3VA1...

3VA20...

3VA21...

3VA22...

3VA23...

3VA24...

6 Trip element

3VA9908-0BB11

3VA9908-0BB24

3VA9908-0BB25

3VA9908-0BB11

3VA9908-0BB25

5TT3 undervoltage relays

Without response delay

	For the monitoring of		
	1, 2 or 3 phases against N	2 CO	3 phases against N
Contacts	1 CO	2 CO	2 CO
Mounting width	1 MW	2 MW	2 MW
			

Rated operational voltage U_e	Rated operational current I_e	Switching thresholds	Hysteresis			
Not adjustable						
230 V AC	4 A	$0.7 \text{ and } 0.9 \times U_c$	–	5TT3400	5TT3402	5TT3404
		$0.85 \text{ and } 0.95 \times U_c$	–	5TT3401	–	5TT3405
Adjustable						
230 V AC	4 A	$0.7 \dots 0.95 \times U_c$	5%	–	–	5TT3406
		$0.9 \dots 0.95 \times U_c$	–	–	5TT3403	–

Further technical specifications

Standards				
Standards			IEC 60255, DIN VDE 0435-110, DIN VDE 0435-303	
Supply				
Rated control circuit voltage U_c			230/400 V AC	
Primary operating range (overload capability)			$1.1 \times U_c$	
Rated frequency			50/60 Hz	
Contacts				
μ contact		AC-11	4 A	
Response values		ON-switching	$0.9/0.95 \times U_c$	4% hysteresis
		OFF-switching	$0.7/0.85 \times U_c$	$0.7 \dots 0.95 \times U_c$
Minimum contact load			10 V/100 mA	
Safety				
Rated insulation voltage U_i		Between coil/contact	4 kV	
Electrical isolation, creepage distances and clearances		Actuator/contact	3 mm	5.5 mm
Rated impulse withstand voltage U_{imp}		Actuator/contact	>2.5 kV	>4 kV
Functions				
Phase asymmetry		Setting accuracy	–	Approx. 5 ... 10%
		Repeat accuracy	–	1
Phase failure detection		At L1 or L2 or L3	100 ms	
Functions		Monitoring of 1/2 phases against N	Yes	–
		Monitoring of 3 phases against N	Yes	
		Asymmetry (failure) detection	–	Yes
		Reverse (failure) detection	–	Yes
		Phase failure detection	Yes	
		N-conductor monitoring	–	Yes
Connection				
Terminals		± Screw (Pozidriv)	PZ 1	
Conductor cross-sections		Rigid	Max. 2x 2.5 mm ²	
		Flexible, with end sleeve	Min. 1x 0.5 mm ²	
Ambient conditions				
Permissible ambient temperature			–20 ... +60 °C	
Resistance to climate			Acc. to EN 60068-1	
			20/60/4	

5TT3 undervoltage relays

With response delay

For the monitoring of 1, 2 or 3 phases against N	
Contacts	1 CO
Mounting width	1 MW
	2 CO
	1 MW
	
	

Rated operational voltage U_e	Rated operational current I_e	Switching thresholds	Hysteresis	Standard	With TEST pushbutton
Not adjustable					
230 V AC	4 A	$0.85 \times U_c$	5%	5TT3414	5TT3415

Further technical specifications

Further technical specifications		5TT3414	5TT3415
Supply			
Rated control circuit voltage U_c		230/400 V AC	
Primary operating range (overload capability)		$1.15 \times U_c$	
Rated frequency		50/60 Hz	
Contacts			
Contacts	AC-15	1 CO	2 CO
Response values	ON-switching	5% hysteresis	
	OFF-switching	$0.85 \times U_c$	
Response delay		0.5 s	
Return transfer delay		60 s	
Minimum contact load		10 V/100 mA	
Electrical endurance in operating cycles	AC-15 (1 A, 230 V AC)	1×10^5	
Safety			
Rated insulation voltage U_i	Between coil/contact	–	
Rated impulse withstand voltage	Acc. to IEC 60664-1	6 kV	
Pollution degree		2	
Functions			
Phase failure detection	At L1 or L2 or L3	500 ms	
Functions	Monitoring of 1 or 2 phases against N	Yes	
	Monitoring of 3 phases against N	Yes	
	Phase failure detection	Yes	
Connection			
Terminals	– Screw (slot)	3.5 mm	
Conductor cross-sections	Rigid	$1 \times 4 \text{ mm}^2$	
	Flexible, with end sleeve	$1 \times 2.5 \text{ mm}^2$	
Ambient conditions			
Permissible ambient temperature		–25 ... +60 °C	
Resistance to climate	Acc. to EN 60068-1	20/060/04	

5TT3 short-time voltage relay

Without response delay

For the monitoring of
1, 2 or 3 phases against N

Contacts 2 CO
Mounting width 2 MW



Rated operational voltage U_e	Rated operational current I_e	Switching thresholds	
Not adjustable			
230 V AC	4 A	$0.8 \dots 0.85 \times U_c$	5TT3407

Further technical specifications

Standards			
Standards		IEC 60255, DIN VDE 0435-303	
Supply			
Rated control circuit voltage U_c		230/400 V AC	
Primary operating range (overload capability)		$1.1 \times U_c$	
Rated frequency		50/60 Hz	
Rated operational power P_s	AC operation:	230 V and p.f. = 1	2000 VA
		230 V and p.f. = 0.4	1250 VA
	DC operation:	$U_e = 24 \text{ V}$ and $I_e = 6 \text{ A}$	Max. 100 W
		$U_e = 60 \text{ V}$ and $I_e = 1 \text{ A}$	Max. 100 W
		$U_e = 110 \text{ V}$ and $I_e = 0.6 \text{ A}$	Max. 100 W
		$U_e = 220 \text{ V}$ and $I_e = 0.5 \text{ A}$	Max. 100 W
Back-up fuse	Terminals L1/L2/L3	2 A	
Contacts			
μ contact	AC-11	3 A	
Response values	ON-switching	$0.85 \times U_c$	
	OFF-switching	$0.8 \times U_c$	
Automatic reclosing delay (return transfer delay)		0.2 ... 2 s	
Minimum contact load		10 V/100 mA	
Safety			
Rated insulation voltage U_i	Between coil/contact	4 kV	
Electrical isolation, creepage distances and clearances	Actuator/contact	4 mm	
Rated impulse withstand voltage U_{imp}	Actuator/contact	>4 kV	
Functions			
Phase failure detection	At L1 or L2 or L3	≥20 ms	
Phase asymmetry	Setting accuracy	Approx. 5 ... 10%	
	Repeat accuracy	1	
Functions	Monitoring of 1 or 2 phases against N	Yes	
	Monitoring of 3 phases against N	Yes	
	Phase failure detection	Yes	
	N-conductor monitoring	Yes	
Connection			
Terminals	± Screw (Pozidriv)	PZ 1	
Conductor cross-sections	Rigid	Max. 2x 2.5 mm ²	
	Flexible, with end sleeve	Min. 1x 0.5 mm ²	
Ambient conditions			
Permissible ambient temperature		−20 ... +60 °C	
Humidity class	Acc. to IEC 60068-2-30	F	

5TT3 undervoltage and overvoltage relays

With adjustable response delay

	For the monitoring of 3 phases against N
Contacts	2 CO
Mounting width	2 MW



Rated operational voltage U_e	Rated operational current I_e	Switching thresholds	Hysteresis	
Adjustable				
230 V AC	4 A	0.7 and $1.1 \times U_c$ 0.9 and $1.3 \times U_c$	4% 4%	5TT3408

Further technical specifications

Standards			
Standards			IEC 60255, DIN VDE 0435-303
Supply			
Rated control circuit voltage U_c			230/400 V AC
Primary operating range (overload capability)			$1.35 \times U_c$
Rated frequency			50/60 Hz
Back-up fuse	Terminals L1/L2/L3		2 A
Contacts			
μ contact	AC-11		1 A
Response values	Overvoltage:	ON-switching	4% hysteresis
		OFF-switching	$0.9 \dots 1.3 \times U_c$
	Undervoltage:	ON-switching	4% hysteresis
		OFF-switching	$0.7 \dots 1.1 \times U_c$
OFF-delay (response delay)			0.1 ... 20 s
Automatic reclosing delay (return transfer delay)			–
Minimum contact load			10 V/100 mA
Safety			
Rated insulation voltage U_i	Between coil/contact		4 kV
Electrical isolation, creepage distances and clearances	Contact/contact		4 mm
	Actuator/contact		4 mm
Rated impulse withstand voltage U_{imp}	Actuator/contact		>4 kV
Functions			
Phase failure detection	At L1 or L2 or L3		100 ms
Phase asymmetry	Setting accuracy		Approx. 5 ... 10%
	Repeat accuracy		1
Functions	Monitoring of 1 or 2 phases against N		–
	Monitoring of 3 phases against N		Yes
	Asymmetry detection		Yes
	Reverse voltage detection		Yes
	Phase failure detection		Yes
	N-conductor monitoring		Yes
Connection			
Terminals	± Screw (Pozidriv)		PZ 1
Conductor cross-sections	Rigid		Max. 2x 2.5 mm ²
	Flexible, with end sleeve		Min. 1x 0.5 mm ²
Ambient conditions			
Permissible ambient temperature			–20 ... +60 °C
Humidity class	Acc. to IEC 60068-2-30		F

5TT6 current relays

For 1-phase loads up to 230 V AC

				Auxiliary voltage and load voltage				
				Not isolated		Electrically isolated		
Mounting width				1 MW	1 MW	2 MW	2 MW	2 MW
								
Rated operational voltage U_e	Rated operational current I_e	Contacts	Rated control current I_c	Monitoring Undercurrent	Monitoring Overcurrent	Monitoring Undercurrent	Monitoring Overcurrent	Overcurrent/undercurrent
230 V AC	5 A	1 CO	1 ... 10 A	5TT6111	5TT6112	–	–	–
		2 CO	0.1 ... 1 A, 0.5 ... 5 A, 1 ... 10 A, 1.5 ... 15 A	–	–	5TT6113	5TT6114	5TT6115

Further technical specifications

Standards						5TT6113 5TT6114 5TT6115
Standards					IEC 60255	IEC 60255 DIN VDE 0435-303
Supply						
Rated control current I_c					1 ... 10 A	0.1 ... 1 A, 0.5 ... 5 A, 1 ... 10 A, 1.5 ... 15 A
Rated control circuit voltage U_c					230 V AC	
Primary operating range					0.9 ... 1.1 × U_c	
Overload capability				Continuous	15 A	20 A
				At 50 °C ambient temperature max. 3 s	20 A	–
				Independent of measuring range, max. 3 s	–	30 A
Rated frequency					50/60 Hz	
Contacts						
μ contact (AC-15)				NO	3 A	5 A
				NC	1 A	
Response values				ON-switching	Infinitely variable	
				OFF-switching	Permanent, 4% hysteresis	
Switching delay t_v					0.1 ... 20 s, continuously adjustable	
Response time				Non-adjustable	Current corresponds to the rated operational power of the continuous-flow heater	See Siemens Service and Support Portal, search term "Article No.", e.g. 5TT6113
Minimum contact load					10 V/100 mA	
Safety						
Rated insulation voltage U_i				Between coil/contact	2.5 kV	
Electrical isolation, creepage distances and clearances				Actuator/contact	3 mm	
Rated impulse withstand voltage U_{imp}				Actuator/contact	>4 kV	
Connection						
Terminals				± Screw (Pozidriv)	PZ 1	
Conductor cross-sections				Rigid	Max. 2x 2.5 mm ²	
				Flexible, with end sleeve	Min. 1x 0.5 mm ²	
Ambient conditions						
Permissible ambient temperature					–20 ... +60 °C	
Resistance to climate				Acc. to EN 60068-1	20/60/4	

5TT3 fuse monitors

For all low-voltage fuse systems

Mounting width 2 MW



Rated operational voltage U_e	Rated operational current I_e	Rated control circuit voltage U_c	
Adjustable			
250 V AC	4 A	380 ... 415 V AC	5TT3170

Further technical specifications

Standards		
Standards		IEC 60255, DIN VDE 0435-110
Supply		
Rated operational voltage U_e		250 V AC
Rated operational current I_e	AC-1	4 A
Rated control circuit voltage U_c	3 AC	380 ... 415 V
Primary operating range		$0.8 \dots 1.1 \times U_c$
Rated frequency		50 ... 400 Hz
Contacts		
Internal resistance of measuring paths		>1000 Ω/V
Max. permissible rear feed		90%
Response/release time		<50 ms
Electrical endurance AC-11	In switching cycles at 1 A	1.5×10^5
Safety		
Rated impulse withstand voltage U_{imp}	Input/output	>4 kV
Application		
Area of application		Asymmetric, systems afflicted with harmonics, regenerative motors
Message		Also for disconnected loads
Connection		
Terminals	$\pm$ Screw (Pozidriv)	PZ 1
Conductor cross-sections	Rigid	Max. 2x 2.5 mm ²
	Flexible, with end sleeve	Min. 1x 0.5 mm ²
Ambient conditions		
Permissible ambient temperature		−20 ... +45 °C
Resistance to climate	Acc. to EN 60068-1	20/45/4

5TT3 phase monitors

For monitoring of voltages in a three-phase system

Mounting width 1 MW



Rated operational voltage U_e	Rated operational current I_e	Contacts	Rated control circuit voltage U_c	With 3 green LEDs for 3 phases
250 V AC	4 A	1 CO	230/400 V	5TT3421

Further technical specifications

Standards			
Standards			IEC 60255, DIN VDE 0435
Supply			
Rated operational voltage U_e			250 V AC
Rated operational current I_e			4 A
Rated control circuit voltage U_c			230/400 V AC
Primary operating range			$0.8 \dots 1.1 \times U_c$
Rated frequency			50/60 Hz
Rated power dissipation P_v		Electronics	9 VA
		Contacts	0.2 VA
Contacts			
μ contact		AC-11	3 A
Minimum contact load			10 V/100 mA
Safety			
Rated insulation voltage U_i		Between coil/contact	4 kV
Electrical isolation, creepage distances and clearances		Actuator/contact	4 mm
Rated impulse withstand voltage U_{imp}		Actuator/contact	>2.5 kV
Degree of protection		Acc. to EN 60529	IP20, with connected conductors
Protection class		Acc. to EN 61140/VDE 0140-1	II
Connection			
Terminals		$\pm$ Screw (Pozidriv)	PZ 1
Conductor cross-sections		Rigid	Max. $2 \times 2.5 \text{ mm}^2$
		Flexible, with end sleeve	–
Ambient conditions			
Permissible ambient temperature			$-20 \dots +60 \text{ }^\circ\text{C}$
Resistance to climate		Acc. to EN 60068-1	20/60/4

5TT3 phase sequence monitors

For monitoring of phase sequence in a three-phase system

Mounting width 1 MW



Rated operational voltage U_e	Rated operational current I_e	Contacts	Rated control circuit voltage U_c	With one green LED, which lights up for right-rotating field
250 V AC	4 A	1 CO	400 V	5TT3423

Further technical specifications

Standards			
Standards			IEC 60255, DIN VDE 0435
Supply			
Rated operational voltage U_e			250 V AC
Rated operational current I_e			4 A
Rated control circuit voltage U_c			400 V AC
Primary operating range			$0.8 \dots 1.1 \times U_c$
Rated frequency			50/60 Hz
Rated power dissipation P_v	Electronics		9 VA
	Contacts		0.2 VA
Contacts			
μ contact			AC-11
Minimum contact load			3 A
Safety			10 V/100 mA
Rated insulation voltage U_i			Between coil/contact
Electrical isolation, creepage distances and clearances			4 kV
Rated impulse withstand voltage U_{imp}			Actuator/contact
Degree of protection			4 mm
Protection class			>2.5 kV
Terminals			Acc. to EN 60529
Conductor cross-sections			IP20, with connected conductors
Ambient conditions			Acc. to EN 61140/VDE 0140-1
Permissible ambient temperature			II
Resistance to climate			
Acc. to EN 60068-1			
20/60/4			

5TT3 insulation monitors for industrial applications

Are used for protection of persons and against fire in non-grounded systems (IT systems)

Mounting width 2 MW



Measurement voltage range U_{meas}	Measuring range	Contacts	Rated control circuit voltage U_c	
0 ... 500 V AC	5 ... 100 k Ω	2 CO	230 V AC	5TT3470
12 ... 280 V DC	5 ... 200 k Ω	2 CO	–	5TT3471

Further technical specifications

		5TT3470	5TT3471
Supply			
Rated operational voltage U_e		230 V AC	12 ... 280 V DC
Rated operational current I_s	Thermal current I_{th}	4 A	
	DC-13 at 24 V DC	–	2 A
	DC-13 at 250 V DC	–	0.2 A
	AC-15	–	3 A
	AC-15 NO	5 A	–
	AC-15 NC	2 A	–
Supply voltage U_c	For AC supply	220 ... 240 V AC	–
Primary operating range	For AC supply	$0.8 \dots 1.1 \times U_c$	–
Frequency range for U_c		45 ... 400 Hz	–
Rated power dissipation P_v	For AC supply	Approx. 2 VA	–
	For DC supply	–	Approx. 1 W
Contacts			
μ contact		2 CO	
Switching hysteresis	At R_{meas} 50 k Ω	15%	10 ... 15%
Measuring circuit			
Measuring circuit		For 3-phase and AC systems	For direct voltage systems
Measurement voltage range U_{meas}		0 ... 500 V AC	12 ... 280 V DC
Measurement voltage U_{meas}	Internal	Approx. 15 V DC	–
Primary operating range		$0 \dots 1.1 \times U_{\text{meas}}$	$0.9 \dots 1.1 \times U_{\text{meas}}$
Frequency range for U_{meas}		10 ... 10000 Hz	–
Alarm values	Measuring shunt R_{AL}	5 ... 100 k Ω	5 ... 200 k Ω
Setting of alarm value	On absolute scale	Infinitely variable	Infinitely variable
Alternating current internal resistance	Internal testing resistance	>250 k Ω	–
Direct current internal resistance	Internal testing resistance	>250 k Ω	–
	L+ and L- to PE	–	75 k Ω each
Max. measurement current I_{meas}	Short circuit	<0.1 mA	0.2 ... 4 mA, depending on the voltage
Direct interference voltage	Max. permissible	500 V DC	–
Response delay at R_{AL} 50 k Ω and 1 μ F	∞ to $0.9 \times R_{\text{meas}}$	<1.3 s	0.8 s
	R_{meas} from ∞ to 0 Ω	<0.7 s	0.4 s
Safety			
Rated impulse withstand voltage U_{imp}	Terminals A1 to A2	<4 kV	
	Terminals L to PE	<4 kV	
	Terminals A1, A2 to L, PE	<4 kV	<3 kV
	Terminals against contacts	<6 kV	
Degree of protection	Terminals (according to EN 60529)	IP20	
	Enclosure (according to EN 60529)	IP40	
Connection			
Terminals	$\pm$ Screw (Pozidriv)	PZ 2	
Conductor cross-sections	Rigid	Max. 2x 2.5 mm ²	
	Flexible, with end sleeve	Min. 1x 0.50 mm ²	
Ambient conditions			
Permissible ambient temperature		–20 ... +60 °C	
Resistance to climate	Acc. to EN 60068-1	20/060/04	

5TT5 EMERGENCY STOP modules

Efficient personal and machine protection in small units

Mounting width 4 MW



Rated operational voltage U_e	Rated operational current I_e	Rated control circuit voltage U_c	
400 V AC	5 A	230 V AC	5TT5200

Further technical specifications

Standards		
Standards		ISO 13849-1: 2015; EN 62061: 2005 + AC: 2010 + A1: 2013 + A2: 2015; ISO 13850: 2015; EN 60204-1: 2006 + A1: 2009 + AC: 2010 (in extracts); EN 60947-5: 2004 + A1: 2009; EN 50178: 1997; EN 61508 Parts 1-7: 2010; EN 50156-1: 2005 (in extracts)
Certification		German Technical Inspectorate Rheinland
Supply		
Primary operating range		$0.8 \dots 1.1 \times U_c$
Rated frequency f_n		50 Hz
Rated power dissipation P_v	Coil/drive	3.5 VA
	Contact per pole	0.8 VA
Control voltage	Terminal Y1	24 V AC/DC
Control current	Terminal Y1	45 mA
Contacts		
Contacts	NO AC-15	3 A
	NC AC-15	2 A
	NO/NC AC-1	5 A
Contact gap		>1 mm
Electrical endurance	AC-15 (2 A, 230 V AC)	10^5 operating cycles
Reliable switching frequency		600 operating cycles/h
Recovery time		500 ms
Safety		
Rated impulse withstand voltage U_{imp}	Actuator/contact	>4 kV
Electrical isolation, creepage distances and clearances	Actuator/contact	3 mm
Vibration resistance	Amplitude acc. to EN 60068-2-610 (up to 55 Hz)	0.35 mm
Connection		
Terminals	± Screw (Pozidriv)	PZ 1
Conductor cross-sections of main current paths	Rigid	Max. $2 \times 2.5 \text{ mm}^2$
	Flexible, with end sleeve	Min. $1 \times 0.50 \text{ mm}^2$
Ambient conditions		
Permissible ambient temperature		$0 \dots +50 \text{ °C}$
Resistance to climate	Acc. to EN 60068-1	0/55/04

5TT3 level relays

For level monitoring and control

Mounting width 2 MW



Rated operational voltage U_e	Rated operational current I_e	Rated control circuit voltage U_c	
250 V AC	5 A	230 V AC	5TT3435

Further technical specifications

Standards		
Standards		IEC 60255; DIN VDE 0435-110
Supply		
Rated operational voltage U_e		250 V AC
Rated operational current I_e		5 A
Rated control circuit voltage U_c		230 V AC
Primary operating range		$0.8 \dots 1.1 \times U_c$
Rated frequency f_n		50/60 Hz
Measuring circuit		
Setting range of the liquid level		2 ... 450 kΩ
Switching point hysteresis of setting value	At 450 kΩ	3%
	At 2 kΩ	6%
Electrode voltage		Max. approx. 10 V AC
Electrode current		Max. approx. 1.5 mA AC
Response delay	Adjustable	0.2 ... 20 s
OFF-delay	Adjustable	0.2 ... 20 s
Test voltage	Input/auxiliary circuit	4 kV
	Input/output circuit	4 kV
	Auxiliary/output circuit	4 kV
Voltage temperature influence	From setting value	<2%
Max. cable length to the electrodes at 100 μF/km	Setting value 450 kΩ	50 m
	Setting value 100 kΩ	200 m
	Setting value 35 kΩ	500 m
	Setting value 10 kΩ	1500 m
	Setting value 5 kΩ	3000 m
Connection		
Terminals	± Screw (Pozidriv)	PZ 2
Conductor cross-sections	Rigid, max.	Max. 2x 2.5 mm ²
	Flexible, with end sleeve	Min. 1x 0.50 mm ²
Ambient conditions		
Permissible ambient temperature		-20 ... +60 °C
Resistance to climate	Acc. to EN 60068-1	20/60/4

Accessories

Immersion electrodes



- Made of stainless steel, with PG13 sealing cap
- Suitable for pure water in open containers

Temperature range	Connection	Article No.
0 ... 60 °C	Terminal connection	5TG8223

5TT3 line circuit relays

To interrupt circuits where there are no active loads

Mounting width 1 MW



Rated operational voltage U_e	Rated operational current I_e	Contacts	Rated control circuit voltage U_c	
250 V AC	16 A	1 NC	230 V AC	5TT3171

Further technical specifications

Standards		
Standards		IEC 60255; DIN VDE 0435-110
Supply		
Rated operational voltage U_e		250 V AC
Rated operational current I_e	AC-1	16 A
Rated control circuit voltage U_c		230 V AC
Primary operating range		0.85 ... 1.15 × U_c
Rated frequency		50/60 Hz
Rated power dissipation P_v	Electronics	5 VA
	Contacts	2.6 VA
Contacts		
Response value	Adjustable	2 ... 20 VA
Release value	% of the response value	70%
Electrical endurance	In switching cycles at 3 A (AC-11)	5 × 10 ⁵
Safety		
Rated impulse withstand voltage U_{imp}	Input/output	>4 V
Degree of protection	Acc. to IEC/EN 60529	IP20, with connected conductors
Protection class	Acc. to EN 61140/VDE 0140-1	II
Monitoring voltage		3 V
Connection		
Terminals	± Screw (Pozidriv)	PZ 1
Conductor cross-sections	Rigid	Max. 2x 2.5 mm ²
	Flexible, with end sleeve	Min. 1× 0.50 mm ²
Ambient conditions		
Permissible ambient temperature		−20 ... +45 °C
Humidity class	Acc. to IEC 60068-2-30	F

Accessories

Base load resistors for electronic devices	
With 15 cm connection wires, end sleeves and shrink sleeving	
	Article No.
	5TG8222

7LQ2 twilight switches

For lighting system monitoring and control

Mounting width 1 MW



Rated operational voltage U_e	Rated operational current I_e	Contacts	Rated control circuit voltage U_c	
230 V AC	16 A	1 NO	250 V AC	7LQ2300

Further technical specifications

Standards		
Standards		EN 60669-1
Supply		
Rated operational voltage U_e		230 V AC
Rated frequency f_n		50/60 Hz
Safety		
Degree of protection		IP30
Contacts		
Incandescent lamp/halogen lamp load		2000 W
Energy-saving lamp load		1000 W
Fluorescent lamp load	Series corrected	2000 W
	Parallel corrected (at max. 70 μ F)	1000 W
LV halogen lamp load ECG		2000 W
Luminosity setting		1 ... 100000 Lux
Measuring circuit		
ON/OFF-delay		Approx. 90 s
Connection		
Terminals	$\pm$ Screw (Pozidriv)	PZ1
Conductor cross-sections	Rigid	Max. 2 $\times$ 1.5 mm ²
Mechanical data		
Width		17.5 mm (1 MW)
Mounting		DIN rail
Ambient conditions		
Permissible ambient temperature		-20 ... +55 °C

Spare part

Light sensor		
	- Included in the 7LQ2300 package - Degree of protection IP65	
	Temperature range	Article No.
	-20 ... +70 °C	7LQ2920



Appendix



Conditions of sale and delivery _____ A/2

Link directory _____ A/4

Conditions of sale and delivery

1. General Provisions

By using this catalog you can purchase products (hardware, software and services) described therein from Siemens Aktiengesellschaft subject to the following Terms and Conditions of Sale and Delivery (hereinafter referred to as „T&C“). Please note that the scope, the quality and the conditions for supplies and services, including software products, by any Siemens entity having a registered office outside Germany, shall be subject exclusively to the General Terms and Conditions of the respective Siemens entity. The following T&C apply exclusively for orders placed with Siemens Aktiengesellschaft, Germany.

1.1 For customers with a seat or registered office in European Union

For customers with a seat or registered office in European Union, the following terms and conditions apply subordinate to T&C:

- for products, which include specific terms and conditions in the description text, these specific terms and conditions shall apply and subordinate thereto,
- for stand-alone software products and software products forming a part of a product or project, the „General License Conditions for Software Products for Automation and Drives for Customers with a Seat or registered Office in Germany“¹⁾ and/or
- for consulting services the „Allgemeine Geschäftsbedingungen für Beratungsleistungen der Division DF – Deutschland“ (available only in German) and/or
- for other services, the „Supplementary Terms and Conditions for Services (‘‘BL’’)¹⁾ and/or
- for other supplies the „General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry“¹⁾.

In case such supplies should contain Open Source Software, the conditions of which shall prevail over the „General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry“¹⁾, a notice will be contained in the scope of delivery in which the applicable conditions for Open Source Software are specified. This shall apply mutatis mutandis for notices referring to other third party software components.

1.2 For customers with a seat or registered office outside European Union

For customers with a seat or registered office outside European Union, the following terms and conditions apply subordinate to T&C:

- for products, which include specific terms and conditions in the description text, these specific terms and conditions shall apply and subordinate thereto,
- for consulting services the „Standard Terms and Conditions for Consulting Services of the Division DF for Customers with a Seat or Registered Office Outside of Germany“¹⁾ and/or
- for other services the „International Terms & Conditions for Services“¹⁾ supplemented by „Software Licensing Conditions“¹⁾ and/or
- for other supplies of hard- and software the „International Terms & Conditions for Products“¹⁾ supplemented by „Software Licensing Conditions“¹⁾

1.3 For customers with master or framework agreement

To the extent our supplies and/or services offered are covered by an existing master or framework agreement, the terms and conditions of that agreement shall apply instead of T&C.

2. Additional Terms and Conditions

The dimensions are in mm. In Germany, according to the German law on units in measuring technology, data in inches apply only to devices for export.

Illustrations are not binding.

Insofar as there are no remarks on the individual pages of this catalog – especially with regard to data, dimensions and weights given – these are subject to change without prior notice.

¹⁾ The text of the Terms and Conditions of Siemens AG can be downloaded at https://mall.industry.siemens.com/legal/ww/en/terms_of_trade_en.pdf

3. Export Regulations

We shall not be obligated to fulfill any agreement if such fulfillment is prevented by any impediments arising out of national or international foreign trade or customs requirements or any embargoes and/or other sanctions.

Export may be subject to license. We shall indicate in the delivery details whether licenses are required under German, European and US export lists.

Our products are controlled by the U.S. Government (when labeled with „ECCN“ unequal „N“) and authorized for export only to the country of ultimate destination for use by the ultimate consignee or end-user(s) herein identified. They may not be resold, transferred, or otherwise disposed of, to any other country or to any person other than the authorized ultimate consignee or end-user(s), either in their original form or after being incorporated into other items, without first obtaining approval from the U.S. Government or as otherwise authorized by U.S. law and regulations. Products labeled with „AL“ unequal „N“ are subject to European/national export authorization.

The export indications can be viewed in advance in the description of the respective goods on the Industry Mall, our online catalog system. Only the export labels „AL“ and „ECCN“ indicated on order confirmations, delivery notes and invoices are authoritative.

Products without label, with label „AL:N“/„ECCN:N“, or label „AL:9X9999“/„ECCN: 9X9999“ may require authorization from responsible authorities depending on the final end-use, or the destination.

If you transfer goods (hardware and/or software and/or technology as well as corresponding documentation, regardless of the mode of provision) delivered by us or works and services (including all kinds of technical support) performed by us to a third party worldwide, you shall comply with all applicable national and international (re-)export control regulations. In any event of such transfer of goods, works and services you shall comply with the (re-) export control regulations of the Federal Republic of Germany, of the European Union and of the United States of America.

Prior to any transfer of goods, works and services provided by us to a third party you shall in particular check and guarantee by appropriate measures that

- there will be no infringement of an embargo imposed by the European Union, by the United States of America and/or by the United Nations by such transfer, by brokering of contracts concerning those goods, works and services or by provision of other economic resources in connection with those goods, works and services, also considering the limitations of domestic business and prohibitions of by-passing those embargos;
- such goods, works and services are not intended for use in connection with armaments, nuclear technology or weapons, if and to the extent such use is subject to prohibition or authorization, unless required authorization is provided;
- the regulations of all applicable Sanctioned Party Lists of the European Union and the United States of America concerning the trading with entities, persons and organizations listed therein are considered.

If required to enable authorities or us to conduct export control checks, you, upon request by us, shall promptly provide us with all information pertaining to the particular end customer, the particular destination and the particular intended use of goods, works and services provided by us, as well as any export control restrictions existing.

You acknowledge that under the EU embargo regulations against Iran, Syria and Russia respectively the sale of certain listed goods and related services is subject to authorization by the competent export control authorities of the European Union. If (1) the goods or services ordered by you are destined for Iran, Syria or Russia, and (2) the contract for our supplies and/or services is subject to prior authorization of the competent export control authorities of the European Union, the contract between you and us shall come into force in this respect only upon granting of such authorization.

The products listed in this catalog may be subject to European/ German and/or US export regulations. Any export requiring approval is therefore subject to authorization by the relevant authorities. Errors excepted and subject to change without prior notice.

Link directory

Catalog LV 10


General information

Information on low-voltage power distribution and electrical installation technology	www.siemens.com/lowvoltage
Tender specifications	www.siemens.com/lowvoltage/tenderspecifications
Conversion tool	www.siemens.com/conversion-tool
Image database	www.siemens.com/lowvoltage/picturedb
CAX download manager	www.siemens.com/cax
Newsletter system	www.siemens.com/lowvoltage/newsletter
Siemens YouTube channel	www.youtube.com/Siemens
Catalog LV 10	www.siemens.com/lv10
Catalog LV 13	www.siemens.com/lv13
Catalog LV 18	www.siemens.com/lv18
Brochures/catalogs	www.siemens.com/lowvoltage/catalogs
Operating instructions/manuals	www.siemens.com/lowvoltage/manuals
Comprehensive information about your product	www.siemens.com/lowvoltage/product-support
My Documentation Manager (MDM)	www.siemens.com/lowvoltage/mdm
Configurators	www.siemens.com/lowvoltage/configurators
Siemens product catalog and online ordering system	www.siemens.com/lowvoltage/mall
Direct forwarding to the Industry Mall	www.siemens.com/product_catalog_SIEP?Article No.
Training	www.siemens.com/sitrain-lowvoltage
Local contacts	www.siemens.com/lowvoltage/contact www.siemens.com/lowvoltage/components/contact www.siemens.com/lowvoltage/systems/contact www.siemens.com/lowvoltage/software/contact
Technical Support	www.siemens.com/support-request
Information on services	www.siemens.com/service-offers
Manual for the generation, transmission and distribution of electrical energy	www.siemens.com/power-engineering-guide
Control panels for the North American market	www.siemens.com/northamerican-standards
Control panel building	www.siemens.com/controlpanel
Energy savings and amortization	www.automation.siemens.com/sinasave
SIMATIC Energy Suite	www.siemens.com/energysuite
SITOP power supplies	www.siemens.com/sitop
Power distribution with Totally Integrated Power	www.siemens.com/tip

Catalogs and further information



LV 10
**Low-Voltage Power Distribution and
 Electrical Installation Technology**
 SENTRON • SIVACON • ALPHA
 PDF (E86060-K8280-A101-B7-7600)




ET D1
Switches and Socket Outlets
 DELTA
 PDF



LV 13
3WA Air Circuit Breakers
 SENTRON
 PDF (E86060-K8280-B101-A1-7600)



Industry Mall
 Information and Ordering Platform
 on the Internet:
www.siemens.com/industrymall



LV 18
**Air Circuit Breakers and Molded Case
 Circuit Breakers with UL Certification**
 SENTRON
 PDF (E86060-K8280-E347-A9-7600)



SITRAIN
 Digital Industry Academy
www.siemens.com/sitrain



IC 10
Industrial Controls
 SIRIUS
 PDF (E86060-K1010-A101-B5-7600)



Siemens TIA Selection Tool
 for the selection, configuration and
 ordering of TIA products and devices
www.siemens.com/tst

The catalogs listed above and additional catalogs are
 available in PDF format at
www.siemens.com/lowvoltage/catalogs

Further information on low-voltage power distribution
 and electrical installation technology is available on the
 Internet at www.siemens.com/lowvoltage

Get more information

www.siemens.com/lowvoltage

Published by
Siemens AG

Smart Infrastructure
Electrical Products
Siemensstraße 10
93055 Regensburg, Germany

For the U.S. published by
Siemens Industry Inc.

100 Technology Drive
Alpharetta, GA 30005
United States

PDF (Catalog Extract
E86060-K8280-A101-B7-7600)
KG 0623 32 En
Produced in Germany
© Siemens 2023

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, systems, machines and networks.

In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial security concept. Siemens' products and solutions constitute one element of such a concept.

Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place.

For additional information on industrial security measures that may be implemented, please visit <https://www.siemens.com/industrialsecurity>.

Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats.

To stay informed about product updates, subscribe to the Siemens Industrial Security RSS Feed under <https://www.siemens.com/cert>.

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

All product designations may be trademarks or other rights of Siemens AG, its affiliated companies or other companies whose use by third parties for their own purposes could violate the rights of the respective owner.